






SPECIFICATIONS

	T550 / T500	JZ750 / JZ700	JX680 / JX650 JX620 / JX600	AX650 / AX600	JV500
Number of effective pixels*1	16.0 million pixels	14.0 million pixels	JX680 / JX650: 16.0 million pixels JX620 / JX600: 14.0 million pixels	AX650: 16.0 million pixels AX600: 14.0 million pixels	14.0 million pixels
Image sensor	1/2.3-inch CCD with primary color filter	1/2.3-inch CMOS with primary color filter	1/2.3-inch CCD with primary color filter	1/2.3-inch CCD with primary color filter	1/2.3-inch CCD with primary color filter
Lens	f=4.3mm-51.6mm, equivalent to 24-288mm on a 35mm format (F3.4-6.9)	f=4.3mm-34.4mm, equivalent to 24-192mm on a 35mm format (F3.6-6.3)	f=4.6mm-23mm, equivalent to 26-130mm on a 35mm format (F3.5-6.3)	f=5.9mm-29.5mm, equivalent to 33-165mm on a 35mm format (F3.3-5.9)	f=6.8mm-20.4mm, equivalent to 38-114mm on a 35mm format (F3.9-5.9)
Aperture	F3.4/F8.6(Wide) F6.9/F17.6 (Telephoto) with ND filter	F3.6/F8.2(Wide) F6.3/F15.0 (Telephoto) with ND filter	F3.5/F8.0(Wide) F6.3/F15.0 (Telephoto) with ND filter	F3.3/F8.0(Wide) F5.9/F14.4 (Telephoto) with ND filter	F3.9(Wide) F5.9 (Telephoto)
Sensitivity	Auto, Equivalent to ISO 100/200/400/800/1600/3200* (Standard Output Sensitivity) *ISO 3200 is effective in S mode (except JZ750 / JZ700).				Auto, Equivalent to ISO 100/200/400/800/1600 (Standard Output Sensitivity)
Image Stabilizer	OIS (Lens Shift)	OIS (Lens Shift)	—	—	—
Anti blur	—	—	✓	✓	✓
LCD	T550: 3.0-inch 460K-dot LCD T500: 2.7-inch 230K-dot LCD	JZ750: 3.0-inch 460K-dot LCD JZ700: 2.7-inch 230K-dot LCD	JX680 / JX620: 3.0-inch 230K-dot LCD JX650 / JX600: 2.7-inch 230K-dot LCD	2.7-inch 230K-dot LCD	2.7-inch 230K-dot LCD
Movie recording					
Battery*2	Li-ion Battery T550: approx. 200 frames (Auto mode) T500: approx. 230 frames (Auto mode)	Li-ion Battery JZ750: approx. 185 frames (Auto mode) JZ700: approx. 210 frames (Auto mode)	Li-ion Battery JX600 / JX620: approx. 210 frames (Auto mode) JX650 / JX680: approx. 230 frames (Auto mode)	AA Battery*3 Approx. 160 frames (Auto mode), Alkaline Approx. 420 frames (Auto mode), NiMH	Li-ion Battery Approx. 200 frames (Auto mode)
Dimensions	99.4(W) x 57.0(H) x 25.8(D) mm / 3.9(W) x 2.2(H) x 1.0(D) in. (Minimum depth: 18.6mm/0.7in.)	99.4(W) x 57.0(H) x 22.6(D) mm / 3.9(W) x 2.2(H) x 0.8(D) in. (Minimum depth: 18.6mm/0.7in.)	JX680 / JX620: 95.1(W) x 57.1(H) x 21.4(D) mm / 3.7(W) x 2.2(H) x 0.8(D) in. (Minimum depth: 19.4mm/0.7in.) JX650 / JX600: 95.1(W) x 57.1(H) x 21.3(D) mm / 3.7(W) x 2.2(H) x 0.8(D) in. (Minimum depth: 19.3mm/0.7in.)	93.0(W) x 60.2(H) x 27.8(D) mm / 3.6(W) x 2.3(H) x 1.0(D) in. (Minimum depth: 22.0mm/0.8in.)	96.0(W) x 59.8(H) x 32.0(D) mm / 3.8(W) x 2.4(H) x 1.3(D) in. (Minimum depth: 18.3mm/0.7in.)
Weight	T550: Approx. 141g / 4.9 oz. (including battery and memory card) T500: Approx. 136g / 4.7 oz. (including battery and memory card)	JZ750: Approx. 139g / 4.9 oz. (including battery and memory card) JZ700: Approx. 134g / 4.7 oz. (including battery and memory card)	JX680 / JX620: Approx. 120g / 4.2 oz. (including battery and memory card) JX650 / JX600: Approx. 113g / 3.9 oz. (including battery and memory card)	Approx. 168g / 5.9oz. (including battery and memory card)	Approx. 120g / 4.2oz. (including battery and memory card)

*1: Number of effective pixels: The number of pixels on the image sensor which receive input light through the optical lens, and which are effectively reflected in the final output data of the still image.

*2: Fujifilm research based on CIPA standards.

*3: Manganese dry and nickel-cadmium batteries cannot be used with this product.



For more information, please visit our Website:
http://www.fujifilm.com/products/digital_cameras/index.html

Specifications are subject to change without notice.
All sample photos are simulated images.

FUJIFILM

SLIM+ ZOOM



STYLISH+ SPEEDY

JZ



EASY+ SIMPLE

JX



COMPACT

JV



CONVENIENT

AX



FINEPIX

T/JZ/JX/AX/JV SERIES

FUJIFILM
FUJIFILM Corporation

©2013 FUJIFILM Corporation

T550 / 500

Powerful 12x Zoom in a Sleek, Stylish Body

16 million pixels	CCD	12x Optical Zoom	OIS (Lens Shift)		T550	T500
					3.0-inch 460K-dot LCD	2.7-inch 230K-dot LCD




- 24mm* wide angle, 12x Optical Zoom and 24x Intelligent Digital Zoom
- Stylish sleek body with aluminum facing
- Optical Image Stabilization (Lens Shift)
- Wide range of shooting functions: Advanced filter (6 special effects), Motion Panorama, Individual shutter 3D, and more
- USB Charge



T550 Black

Optional Accesories
Li-ion battery NP-45A, Battery charger BC-45W, HD Player HDP-L1, AV cable AV-C1, FINEPIX REAL 3D V3



JZ750 / 700

Slim Compact with Full HD Movie and High-speed Continuous Shooting

14 million pixels	CMOS	8x Optical Zoom	OIS (Lens Shift)		JZ750	JZ700
					3.0-inch 460K-dot LCD	2.7-inch 230K-dot LCD




- CMOS sensor delivers great image quality, high-speed continuous shooting
- 24mm* wide angle, 8x Optical Zoom and 16x Intelligent Digital Zoom
- Stylish body with aluminum facing
- Optical Image Stabilization (Lens Shift)
- Wide range of shooting functions: Advanced filter (6 special effects), HDR (dynamic range), Motion Panorama 360, and more



JZ750 White

Optional Accesories
Li-ion battery NP-45A, Battery charger BC-45W, FINEPIX REAL 3D V3



JX680 / 650 / 620 / 600

Easy to Operate Compact with 5x Zoom

CCD	5x Optical Zoom		JX680	JX650	JX620	JX600
			16 million pixels CCD	16 million pixels CCD	14 million pixels CCD	14 million pixels CCD
			3.0-inch 230K-dot LCD	2.7-inch 230K-dot LCD	3.0-inch 230K-dot LCD	2.7-inch 230K-dot LCD




- Simple, intuitive GUI
- 26mm* wide angle, 5x Optical Zoom
- Slim, stylish design
- Wide range of shooting functions: Advanced filter (6 special effects), Motion Panorama, Individual shutter 3D, and more
- Dedicated "Movie recording button"



JX680 Red

Optional Accesories
Li-ion battery NP-45A, Battery charger BC-45W, AV cable AV-C1, HD Player HDP-L1, FINEPIX REAL 3D V3



AX650 / 600

CCD	5x Optical Zoom		AX650	AX600
			16 million pixels	14 million pixels
			2.7-inch 230K-dot LCD	2.7-inch 230K-dot LCD

Compact Convenience with 5x Zoom




- 5x Optical Zoom
- Powered by convenient AA batteries
- Simple, affordable compact

JV500

14 million pixels	CCD		JV500
			3x Optical Zoom
			2.7-inch 230K-dot LCD

Simple, Affordable Compact



- Easy-to-use, affordable compact
- Enjoy shooting movies too
- 2.7-inch 230K-dot LCD

*35mm format equivalent