

HP Power Bank Charging Module



Minimize classroom disruptions with streamlined power bank¹ charging

Keep your fleet of up to eight USB-C™ or 4.5mm power banks¹ charged and ready to go for students any time of day with the HP Multi Power Bank Charging Module, which delivers convenient, simple, and secure storage and charging for the devices.

Clutter free

Recharge up to eight of your power banks¹ from just one AC cable connection between the Module and a standard wall outlet.

Easy access

Slide the interior shelves as needed to quickly load and unload the banks¹ and plug them into the Module's USB-C™ or 4.5mm barrel connectors. Store extra accessories in the handy bottom drawer.

Lock it up

Secure your power banks¹ inside the Module with an optional HP master key locking solution.²

1. Compatible with the HP Notebook Power Bank and HP USB-C Notebook Power Bank, each sold separately.

2. Sold separately.

Specifications



HP Power Bank Charging Module

Part number	2WP85AA
Device capacity	Up to 8 Power Bank Devices
Slot size	W195 x D98 x H28 mm Per Slot. W190 x D135.8 x H42.2 mm for Drawer
Cabinet dimensions (L x W x H)	L291 x W261 x H415 (11.06 x 10.28 x 16.34 in)
Power bank bay dimensions (D x H x W)	W169 x D74 x H23 mm W174 x D72 x H21.5 mm W178.5 x D72.5 x H23 mm
Shelves	Sliding Shelves for easy access to devices, Qty 8
Cabinet weight (estimated, w/o computer equipment)	8.3 kg / 18.29lb
Cabinet weight (estimated, with computer equipment)	9.8 kg / 21.60lb
Casters	None
Door	Front ABS + Mesh. Latch w/ key
Operating assumptions	Yes, 100-240V full range operation
Power delivery	Fixed USB "C" & 4.5mm Barrel Cables
Liquid ingress protection requirement	Grade "0;" Cart structurally engineered to preclude liquids
Charging	USB C channel support 5, 9, 10, 12, 15, 20V output and up to max 3A Via fixed USB C Fixed 4.5 Barrel cable support up to 20V max 3A
Device charging status	None
Warranty	1 year



Specifications

Controller box	None
Cooling	Cabinet vented, internal temp 1 fan
DC power	24V 500 W
Power cord to cart (from cart to the wall)	1.8M (5.90ft) detachable country-specific straight cord
External power switch	ON-OFF Switch, Green= LED On
Product storage and transportation temperature	-40° to +60° C (-40°to 140° F)
Relative humidity (storage)	5 to 95% (non condensing)
Operating temperature	0 to 30° C (32 to 86° F)
Operating relative humidity	10 to 90% (non condensing)
Altitude	2,000 meters maximum
Power rating	Input: AC 100-240V, 10A Output: 5, 9, 10, 12, 15, 20V, maximum 3A
Overall cabinet and electrical certifications assumed	RoHS REACH UL60950-1 CAN/CSA C22.2 No. 60950 ICES-003 Issue 4, ClassA And others as required
Firmware	Secure Firmware update via USB cable (USB A male to USB C female)
Packaging	EPE Foam>Poly Bag>Carton
In-the-box	Powercord, QSP, Warranty, Product Notice

Sign up for updates
hp.com/go/getupdated



Share with colleagues



Rate this document

