

USB 3.0 to DisplayPort External Video Card Multi Monitor Adapter – 2560x1600

StarTech ID: USB32DPPRO



The USB32DPPRO USB 3.0 to DisplayPort® Multi Monitor Adapter functions as an external DisplayPort video card, turning an available USB 3.0 port into a DisplayPort output, with support for high resolution 2560x1600 video, and 5.1 surround sound audio. The USB 3.0 DisplayPort adapter delivers a convenient, high-performance external video solution that makes it easy to add multi-monitor capability to a USB 3.0-enabled desktop or laptop computer (optimal performance from USB 3.0, backward compatible with USB 2.0).

Leveraging the high-bandwidth (5 Gbps) SuperSpeed USB 3.0 interface, the adapter delivers smooth, high-definition content to your DisplayPort-capable display, and can be used to mirror your primary desktop, showing the same image on each display, or to extend your desktop to double your workspace and increase your productivity.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Recommended System Requirements:

CPU: Quad Core 2.4GHz or Higher (i5 recommended)

RAM: 4GB or higher

Applications

- Add a secondary DisplayPort display and extend your desktop, without taking apart your computer to install a new video card
- Add multi-monitor capability to a single computer, to enhance multimedia presentations
- Great for researchers and writers, offering the ability to have reference material on one display while working on a separate document on another
- Increase productivity by running multiple applications on different screens - check your email on one display and search the web on the other
- View large or several spreadsheets across multiple displays
- A compact, lightweight solution for traveling business associates using USB 3.0-capable laptop PCs, enabling connection to a secondary display/projector

Features

- SuperSpeed USB 3.0 (5 Gbps) Interface, backward compatible with USB 2.0
- Supports resolutions up to 2560x1600
- DisplayLink 4K Plug-and-Display certified - automatic driver installation and updates
- USB-powered - No external power adapter required
- Choose between Mirrored, Extended or Primary display configurations
- Driver software supports display rotation
- Supports the Windows® Aero interface
- Supports 5.1 channel audio
- Supports the use of multiple USB32DPPRO USB 3.0 DisplayPort adapters on a single system (up to 5)

Technical Specifications

Warranty	2 Years
Audio	Yes
Chipset ID	DisplayLink - DL3500
Industry Standards	Standard DisplayPort, SuperSpeed USB 3.0, USB 2.0
Memory	512MB DDR II
Output Signal	DisplayPort
USB Pass-Through	No
Audio Specifications	5.1-Channel Surround (48Khz)
General Specifications	This USB video adapter uses a DisplayLink family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, please avoid using devices with a Trigger or Fresco family chipset.
Maximum Digital Resolutions	2560x1600
Note	If using OS X 10.8, Apple update 10.8.3 must be installed before installing DisplayLink software. 10.8.3 fixes several serious OS X bugs exposed when DisplayLink software is installed.
Supported Resolutions	Widescreen(16/32 bit): 2560x1600, 2560x1440, 2048x1152, 1920x1200, 1920x1080, 1680x1050, 1600x900, 1440x900, 1360x768, 1280x800, 1280x768, 1280x720 Standard(16/32 bit): 1600x1200, 1400x1050, 1280x1024, 1280x960, 1152x864, 1024x768, 800x600
Wide Screen Supported	Yes
Connector A	1 - USB Type-A (9 pin) USB 3.0 Male
Connector B	1 - DisplayPort (20 pin) Female
OS Compatibility	Windows® 10 (32/64), 8/8.1 (32/64), 7 (32/64), Vista (32/64), XP (32/64), 2000 (Aero 3D interface supported) Apple® OSX El Capitan (10.11), Yosemite (10.10), Mavericks (10.9) Mountain Lion (10.8), Lion (10.7), Snow Leopard (10.6)
Note	Connect a maximum of five USB32DPPRO adapters on a single PC - See manual for system requirements
System and Cable	1~2 USB Displays Office Application:

Requirements	CPU: i3 Dual core 2.8GHz RAM: 2GB or higher
	Full HD Video: CPU: Quad Core 2.4GHz or Higher (i5 recommended) RAM: 4GB or higher
Power Source	USB-Powered
Humidity	20°C to 80°C (68°F to 176°F)
Operating Temperature	0°C to 35°C (32°F to 95°F)
Storage Temperature	-5°C to 40°C (23°F to 104°F)
Cable Length	3 ft [0.9 m]
Color	Black
Enclosure Type	Plastic
Product Height	0.4 in [11 mm]
Product Length	3.2 in [81 mm]
Product Weight	0.7 oz [20 g]
Product Width	1 in [26 mm]
Shipping (Package) Weight	6.2 oz [175 g]
Included in Package	1 - USB 3.0 to Displayport Adapter
Included in Package	1 - Driver CD
Included in Package	1 - Installation Guide

Certifications, Reports and Compatibility

