



EVO Impact

Impact Receipt Printer

The EVO Impact high-speed receipt printer is built to last. Perfect for extreme environments such as kitchens and , the EVO Impact delivers the steadfast performance expected from a best-of-breed impact printer. The EVO Impact features 5 lines per second printing, drop-in paper loading, swappable interfaces (USB, Parallel, Serial and Ethernet), and includes the cable in every box.




receipt printer

Key Features

- Multiple interfaces: USB, Parallel, Serial, Ethernet
- 5 lines per second print speed
- ESC/POS and OPOS compatible
- Swappable interface cards
- Interface cable included
- 3-year warranty including 2-day Advance Exchange service

EVO Impact Receipt Printer Specifications

PART NUMBER	EVO-PK2-1AP	EVO-PK2-1BP	EVO-PK2-1AS	EVO-PK2-1BS	EVO-PK2-1AU	EVO-PK2-1BU	EVO-PK2-1AE	EVO-PK2-1BE
SPECIFICATIONS								
Interfaces	Parallel IEEE-1284		Serial RS-232C		USB 2.0		Ethernet 10/100	
Emulation	Epson /Citizen /Star							
Print Method	9-pin Serial Dot Matrix							
Printing Speed	5 lines/sec							
Number of Total Dots	400 Dots/line							
Resolution	160 DPI/ 80 DPI							
Printing Direction	Bi-directional with logical seeking							
Effective Printing Width	2.5"							
Font Size	7 x 9 9 x 9							
CASH DRAWER PORTS	2 Circuits (24 V, 1 A max)							
RELIABILITY								
MCBF	18,000,000 Lines							
Printhead	120 Million Characters							
PAPER								
Type	Roll Paper							
Width	3" (76.2 mm)							
Roll Diameter	3" (76.2 mm)							
Copies	Original + 2 Copies							
NUMBER OF COLUMNS	Epson TM-U200 Emulation 42/35, 40/33 Other Emulation 40/33							
INK RIBBON	EPSON ERC-38 Black, Purple, Black/Red							
AUTO CUTTER								
Type	Guillotine	Tear Bar	Guillotine	Tear Bar	Guillotine	Tear Bar	Guillotine	Tear Bar
Cutting Method	Full/Partial Cut	n/a	Full/Partial	n/a	Full/Partial	n/a	Full/Partial	n/a
Auto Cutter Life	1,500,000 Cuts							
Paper Thickness	0.002" (0.065 mm) - 0.005"(0.13 mm)							
PHYSICAL								
Dimension	6.14"(w) x 9.57"(D) x 5.91"(H)							
Weight	5.4 lbs							
Color	Black							
ELECTRICAL	(input)120-230 VAC 60 Hz (output) 24 VDC/1.5 A							
ENVIROMENTAL								
Temperature	41°F to 104°F operating -4° F to 140° F storage							
Humidity	35%-80% non condensing (operation)				10%-90% non condensing (storage)			
WARRANTY	3-Year includes 2-Day Advance Exchange Warranty Service, 2-Year on Autocutter and Print Head							
CERTIFICATIONS	FCC, MIC, UL, CE, CCC, RoHs(TUV)							
OPERATING SYSTEM	WIN 95/WIN 98/WIN 2000/WIN XP/VISTA/OPOS driver available							



ACCESSORIES

RPCARD-P1	Parallel Interface Card for EVO Impact
RPCARD-S1	Serial Interface Card for EVO Impact
RPCARD-E1	Ethernet Interface Card for EVO Impact
RPCARD-U1	USB Interface Card for EVO Impact
ZOE-CRW3	3-Year Overnight Exchange
ZOE-CRW5	5-Year Overnight Exchange