

Model Number: V1206-PD, V1206-PDF

## V1206-PD Zero Client

*Tera2 PCoIP Portal Processor, Dual DP + DVI Display Capability*

The V1206-PD is the latest 10ZiG TERA2 PCoIP Zero Client optimized for VMware and Amazon AWS VDI environments. This device supports the efficiency and security of centralized computing while offering an uncompromised desktop experience. The V1206-PD's TERA2 chipset delivers a powerful, secure and easy to manage desktop environment. This Zero Client offers a seamless solution with dynamic features and performance that will meet the needs of any VDI environment.

Specifically designed with a small carbon footprint, the V1206-PD consumes only 8 watts of power. This helps organizations save on power consumption, resulting in a much lower total cost of ownership.

This Zero Client eliminates the need for running, managing, maintaining and securing high maintenance PCs, while still delivering a high end computing experience. With six USB ports, rich multimedia playback, HD audio and dual monitor support, the V1206-PD is the perfect fit for any VDI environment.



- ▶ Zero Operating System / Zero Virus Exposure
- ▶ 2560 x 1600 (Max Resolution Single Screen)
- ▶ SFP Ready (V1206-PDF)
- ▶ Dual Monitor Support (DP + DVI Standard)
- ▶ VESA Mounting Capability
- ▶ FREE Centralized Management
- ▶ TAA Compliant
- ▶ 6 x USB Ports

# V1206-PD Zero Client

## TERA2 PCoIP Zero Client Series



### SPECIFICATIONS

1. Power Button/Power LED
2. Front USB (4)
3. Line Out
4. Mic In
5. Rear USB (2)
6. Ethernet - RJ45 LAN
7. Single Link DVI-I
8. DP (DisplayPort)
9. DC Jack
10. Kensington Lock (left side)

### System Specifications

Management Utility	Teradici Management
Form Factor	Slim Line
Processor	Teradici PCoIP™ Portal Processor - TERA2
Chipset	TERA2321 PCoIP™

### Dimensions

Device	1.063"(W) x 6.772"(H) x 5.209"(D) - 27mm x 172mm x 132mm
Weight	2.53 lbs (1.15kg)

### Connections

Ports	USB 2.0 x 6, DP (DisplayPort) x 1, Single Link DVI-I x 1, Mic-In x 1, Line-Out x 1, RJ-45 LAN, DC Jack x 1
Video Resolution	1 Screen = (2560 x 1600) (DP) - 2 Screens = (1920 x 1200)

### Networking

Ethernet	10/100/1000 Base-T
Fiber	Optional SFP Fiber Connector (100/1000Mbps)

### Environmental

Operating Temp.	32-104F (0-40C), 10-90% non-condensing humidity
Power	8 Watt Consumption, 36 Watt, DC-12V/3A External Power Adapter

### Certifications

CE, FCC, CAN ICES-3/NMB-3, VCCI, UL, TUV-GS, C-Tick, GOST, BSMI, RoHS

**WARRANTY:** All Zero Clients include a 3-Year Advanced Exchange Warranty



Americas  
EMEA  
APAC

P: 866-865-5250  
P: +44 (0) 116 214 8650  
P: 1300 768 799

E: info@10ZiG.com  
E: info@10ZiG.eu  
E: info@10ZiG.com.au

W: www.10ZiG.com  
LN: 20160823

