

40M IR VARI-FOCAL BULLET CAMERA

I4-390IPAVF



1/3" CMOS Sensor
 2 Mega-Pixel
 True Day & Night (IR Cut Removable)
 H.264+ Compression
 0 Lux (IR On) Min. Illumination

ONVIF
 Digital WDR
 3D Noise Reduction
 Motion Detection and Privacy Masking
 2.8-12mm Vari-Focal Lens

30m IR Illumination
 PoE Support
 1 Way Audio
 IP 66 Protection

Specifications

Camera	Video	Model	I4-390IPAVF
		Image Sensor	1/3" CMOS
		Effective Pixels	1920×1080
		Electronic Shutter	1/25s ~ 1/100000s
		Day & Night	ICR
	Audio	Audio compression	G711A/U
		Communication	One Way Audio
	Image Enhancement	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto / Manual) ROI (Region of interest) Setting Sharpness, Saturation, Brightness & Contrast Adjustable
		WDR Range	Digital WDR
		Noise Reduction	3D-DNR
Image Orientation		Mirror/Flip/Vertical Mode	
Privacy Zone		Yes	
Compression	Video Compression	H.264+	
	Resolution	1080P (1920×1080), 720P (1280×720), VGA, QVGA	
	Multi-stream	1920×1080 (1~30fps) / 1280×720 (1~30fps) / 1280×720 (1~30fps) / 640×480 (1~30fps) / 320×240 (1~30fps)	
	Bit rate	128Kbps ~ 6Mbps	
	Encode Mode	VBR/CBR	
Image Quality	Five levels under VBR; Free adjustment under CBR		

Housing	IR Distance	40m (48 IR LED)
	Lens	2.8-12mm
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Water-proof	IP66
	Bracket	3-Axis
	Dimensions	Φ112mm×326mm
Connectivity	Weight(gross)	1115g
	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	No
	Mic Connectivity	1Ch Input
	SD Card	No
	RS485	No
Network	Alarm	No
	Remote Monitoring	IE Browsing, CMS Control Software
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Others	ONVIF	Yes
	Ethernet	100Mbps
	PoE	Yes
Power Supply	Power Supply	DC12V~600mA / PoE/~8.5W
	Work Environment	-10 C ~50 C, 10%~90% Humidity

