



mPLUS2

Mini panel printer

- High print quality (204 DPI)
- Paper width: 58mm
- 100% compatible with the previous MiniPLUS version
- Paper weight: 55-70gr/mq
- Power supply: 4-7.5Vdc \pm 10%
- 4MB internal flash memory for logos and fonts
- Interfaces on board: USB, Serial RS232 and serial TTL (selectable with lever switch)
- It prints 1D and 2D barcodes (QRCODE and PDF417)
- Font: any language available
- Sensors: head temperature, paper end, cover open
- UL, CE, FCC approved
- The ideal solution for tough environments: from -20 up to +70 degrees
- **Energy-efficient** functionality to reduce consumption

CHARACTERISTICS

APPLICATIONS:

- Workshop equipment
- Medical equipment
- Weighing instruments
- Sterilisation equipment
- Control and measurement instruments
- Taximeters



CePrinterSet SOFTWARE : to update logos, edit characters, set operating parameters and update the printer firmware. It allows you to create a file including the different SW customizations and send them to the printer via the interface provided, for easy and fast setting.


AVAILABLE VERSIONS:

- Serial RS232/TTL and USB, 5Vdc
 - Mechanical version (without electronic board)
-

TECHNICAL SHEET

| | |
|-----------------------|---|
| Printing Method | Thermal |
| Number of dots | 8 dots/mm |
| Columns | 24/40 |
| Resolution | 203 DPI |
| Printing (mm/sec) | max 50mm/sec (in absence of energy-efficient functionality) |
| Character set | International fonts on board: All European, Russian, Turkish, Arabic, Chinese (GB18030), Katakana |
| Supported Barcode | UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32 and Barcode 2D PDF417 and QRcode |
| Paper width | 58 mm |
| Paper weight | from 55 to 70 g/m ² |
| Roll Dimension | External diameter: max 30mm Internal diameter: 13mm |
| Sensors | head temperature, paper end, cover open |
| Emulation | Escape Command compatibility |
| Interfaces | RS232/TTL, mini USB |
| Data Buffer | 2 kB |
| Flash Memory | 4 MB |
| Graphic Memory | 1 MB internal flash memory + 4MB external flash memory; 128 KB internal RAM + 8MB external RAM |
| Drivers | Windows Linux Android |
| Software Tools | CePrinterSet |
| Power supply | 4-7.5 Vdc ±10% |
| Operating temperature | from -20 °C to +70 °C |
| Marks | UL, CE, FCC |
| Dimensions | 63.9 (L) x 61.2 (H) x 87.2 (W) mm |
| Weight | 98gr |

MODELS



915CW170100333

PRINTER 57MM MPLUS2 USB

RS232 TTL



CUSTOM SPA - Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: T180W10

The technical data on this website are not binding and may be changed without advanced notice.
Last update: 01 September 2020