



Eclipse Surge Suppressors

Total protection against power surges, spikes, nearby lightning strikes* and line noise

Advanced Features

- ▶ Up to 1020 joule rating
- ▶ Master On/Off switch
- ▶ Instantaneous response time
- ▶ Visual Alarm(s)
- ▶ Audible Alarm (except Personal)
- ▶ Circuit Breaker and Thermal Fuse Protection
- ▶ 360° Rotating Plug (except Personal)

The **Eclipse** product line brings affordable surge protection to your PC, peripherals and other devices in the event of nearby lightning strikes, surges and spikes. In addition, Eclipse provides line noise reduction to minimize interference from the utility power. All Eclipse models include a "load protected" status LED to notify you in case of surge protection failure. On the EclipsePro and ProTel models, an audible alarm provides warning in combination with the LED.

EclipsePro and ProTel models feature a "ground OK" LED to warn of building wiring faults which can potentially interfere with Eclipse's ability to arrest surges and spikes.

Eclipse is available in three models for individual applications:

- ▶ Eclipse Personal for home appliance or home/office PC use
- ▶ EclipsePro and Eclipse ProTel for professional use including networked PCs, servers and business equipment
- ▶ Eclipse ProTel provides a fax/modem protector in addition to all the features of EclipsePro

MGE Eclipse, your choice of surge suppressor where quality and affordability are a must.

M G E

Office Protection Systems

| Characteristics | Eclipse Personal | Eclipse Pro/ProTel |
|------------------------------|---|---|
| Clamping voltage | 330 volts AC | 330 volts AC |
| Joules | 270 joules energy dissipation* | 1020 joules energy dissipation* |
| Response time | <1nanosecond | <1nanosecond |
| EMI-RFI noise suppression | Up to 40 db | Up to 58 db |
| Agencies | UL 1449, 1363 listed, (cUL) | UL 1449, 1363, 1283, (497A ProTel) listed, (cUL) |
| Nominal ratings | 120 VAC, 15A, 1800 watts, 60Hz | 120 VAC, 15A, 1800 watts, 60Hz |
| Input and output connections | NEMA 5-15 straight plug with 4 foot cord 6 receptacles | NEMA 5-15 360° plug with 6 foot cord (6 foot single line telephone cord with Eclipse ProTel), 8 receptacles |
| LEDs | "Load protected" control and overload protection | "Ground OK", "load protected" (audible alarm), master on/off switch, 15A circuit breaker and thermal fuse |
| Dimensions (L x W x H) | 11" x 2" x 1-1/4" | 9-3/4" x 3-7/8" x 1-5/16" |
| Weight | 1 pound/unit | 1.5 pounds/unit |
| Standard package | 20 per master carton | 20 per master carton |
| Part Number | 83500 | Pro: 83501 / ProTel: 83502 |

