

Power & Charge with 100W Power Delivery 3.0

With support for USB PD 3.0 (up to 100W), the USB Type-C multiport adapter lets you power and charge your laptop, and power your peripherals when connected to a USB-C power adapter. The USB-C hub features PD passthrough so you can use your laptop's own charger to power the hub (requires 15W) and power or charge your laptop simultaneously.

All the Essential Ports with USB

The USB-C to USB 3.0 hub gives you one USB-C port (power & data) and two USB-A ports to connect your latest and legacy USB devices.



Includes Ports to Do More with SD, Audio & Gigabit Ethernet

Access your multimedia content, audio, and network with ease. The multiport adapter provides direct access to your:

- SD, SDHC™ and SDXC™ memory cards or microSD cards via the SD card slot
- Audio content via headphones or microphone through the 3.5mm 4- position audio port
- Ethernet network via the GbE port using a hard-wired connection

DKT30CHVAUSP is backed by a StarTech.com 3-year warranty and free lifetime technical support.



Certifications, Reports and Compatibility



Applications

- Seamlessly create a familiar and productive workstation wherever you travel
- Creative professionals can use the built-in card reader to access multimedia

Features

- Connect an HDMI or VGA monitor to your host device with this USB-C multiport adapter
- Extended length 30cm attached host cable for more flexible connectivity, plus plug-and-play setup
- Supports 100W Power Delivery 3.0 and PD passthrough to power both the multiport adapter and your laptop, using your laptop's USB-C power adapter
- Provides ports for USB peripherals when travelling with 2x USB 3.0 Type A and 1x USB 3.0 Type-C ports
- USB Type-C multiport adapter also includes SD/Micro SD card reader, 3.5mm 4-position audio and Gigabit Ethernet ports
- Ideal for portability, travel and creating small workstations

Hardware	Warranty	3 Years
	4K Support	Yes
	Audio	Yes
	Bus Type	USB 3.1 Gen 1
	Chipset ID	VIA Labs - VL102
		VIA Labs - VL161
		VIA Labs - VL817
		Genesys Logic - GL823K
		ITE Tech - IT6564
		Realtek - RTL8153B
		Cmedia - HS100-B
		Displays Supported
	Fast-Charge Port(s)	No
	Port Style	Cable Adapters
	Ports	7
Performance	Audio Specifications	3.5mm Audio
	Compatible Networks	10/100/1000 Mbps
	Maximum Analog Resolutions	1920 x 1200 @ 60Hz (VGA)
	Maximum Cable Length	11.8 in [30 cm]
	Maximum Digital Resolutions	3840 x 2160 @30Hz, 4096 x 2160 @24hz, 3440 x 1440 @60Hz (HDMI)
	MTBF	372518 hours
	Power Reservation	15W
	Type and Rate	USB 3.1 Gen 1 - 5 Gbit/s
Connector(s)	External Ports	1 - HDMI Receptacle
		1 - VGA (15 pin, High Density D-Sub) Receptacle
		1 - RJ-45 Receptacle
		2 - USB 3.1 USB Type-A (9 pin, Gen 1, 5 Gbps) Receptacle
		1 - SD Slot Receptacle
		1 - 3.5 mm Audio Receptacle Input
		1 - 3.5 mm Audio Receptacle Output
		1 - USB Type-C (24 pin) USB 3.0 (5Gbps) Receptacle

	Host Connectors	1 - USB Type-C (24 pin) USB 3.0 (5Gbps) Plug
Power	Power Delivery	100W
	Power Source	Not Included (not required for standard applications)
Environmental	Humidity	5%~90%
	Operating Temperature	0~45°C
	Storage Temperature	-10~82°C
Physical Characteristics	Cable Length	11.8 in [30 cm]
	Color	Black & Space Gray
	Material	Aluminum and Plastic
	Product Height	116.000
	Product Length	0.6 in [1.5 cm]
	Product Width	60.000
	Weight of Product	114.000
Packaging Information	Package Height	30.000
	Package Length	170.000
	Package Width	142.000
	Shipping (Package) Weight	0.3 lb [0.1 kg]
What's in the Box	Included in Package	1 - USB-C Docking Station 1 - Quick-Start Guide

Product appearance and specifications are subject to change without notice.