

Everything small workgroups need to create high-quality colour print every time.

i-SENSYS
LBP7210Cdn

you can



A compact A4 colour laser printer ideal for small workgroups that demand high-quality print.

This energy efficient network ready, compact colour laser printer is ideal for small workgroups needing fast, professional output with productive automatic double-sided printing.

Key features

- Compact, low profile colour laser printer
- Ideal for small workgroups needing fast output
- 20ppm in colour and mono
- Up to 9600 x 600 dpi equivalent resolution with Automatic Image Refinement
- No waiting with Quick First-Print technologies
- Productive automatic double-sided printing
- 550-sheet max capacity, to keep downtime to a minimum
- Network ready
- Energy efficient and silent in standby
- Maintenance-free All-in-One colour cartridges

What's in the box

Main unit, 718 C/M/Y/K starter cartridge, power cable, CD with driver, manual and starter guide, warranty card.

Dimensions (W x D x H)

414mm x 499mm x 328mm

Supported OS

Windows 7 (32/64bit) / Vista (32/64bit) / XP (32/64bit) / Server 2003 (32/64bit) / Server 2008 (32/64bit) / Server 2008 R2 (64bit)

Mac OS 10.5 and up
(Web distribution only)

Linux (Web distribution only)

Citrix



PRINT



COPY



FAX



SCAN

Canon



- 1** 50-sheet multi purpose tray
- 2** 250-sheet cassette
- 3** Cartridge 718:
5 cartridges available: Black, Cyan, Magenta, Yellow and Black Value Pack

Specifications:

PRINTER ENGINE	Print speed Up to 20ppm colour and mono (A4) Printing method Colour laser beam printing Print quality Up to 9600 x 600 dpi with Automatic Image Refinement Print resolution Up to 600 x 600 dpi Warm-up time Approx. 22 seconds or less from power on First Page Out Time Approx. 16 seconds or less Duty cycle Max. 40,000 pages per month ¹ Print margins 5mm – top, bottom, left and right
MEDIA HANDLING	Paper input (Standard) 250-sheet cassette 50-sheet multi-purpose tray Paper input (Option) 250-sheet cassette Paper output 125-sheet face down Media types Plain paper, Heavy paper, Transparency, Label, Envelope, Recycled paper, Coated paper, Index card Media sizes Cassette (Standard and optional): A4, B5, A5, Legal, Letter, Executive, Statement, Foolscap, Envelope DL, Envelope COM10, Envelope C5, Envelope B5, Custom sizes: Width: 100.0mm to 215.9mm; Length: 148.0mm to 355.6mm Multi-purpose tray: A4, B5, A5, Legal, Letter, Executive, Statement, Foolscap, Envelope DL, Envelope COM10, Envelope C5, Envelope Monarch, Envelope B5, Index Card, Custom sizes: Width: 76.2mm to 215.9mm; Length: 127.0mm to 355.6mm Media weights Cassette (Standard and optional): 60 to 220 g/m ² Multi-purpose tray: 60 to 220 g/m ² Double sided printing Automatic
GENERAL FEATURES	Power requirements 220-240V (±10%) 50/60Hz (±2Hz) Power consumption Maximum: 1170 W or less Active: Average approx. 430 W Standby: Average approx. 20 W Sleep: Average approx. 3 W Typical Electricity Consumption (TEC): 2.2 kWh/week Noise level Sound power ² : Active: 6.7 B or less Standby: 4.3 dB(A) Sound pressure ² : Active: 52 dB(A) or less Standby: 24 dB(A) Dimensions (W x D x H) 414mm x 499mm x 328mm Weight Approx. 22.3kg Operating environment Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation) Control panel 9 LED indicators 1 Operation key

CONTROLLER	Memory 16 MB Printer languages CAPT (Canon Advanced Printing Technology) Interface and connectivity USB 2.0 High-Speed, 10BASE-T/100BASE-TX Software and printer management NetSpot Device Installer, Remote User Interface (RUI) Operating systems compatibility Windows 7 (32/64bit) / Vista (32/64bit) / XP (32/64bit) / Server 2003 (32/64bit) / Server 2008 (32/64bit) / Server 2008 R2 (64bit) / Mac OS 10.5 and up ^{3,4,5} / Linux ^{3,4} / Citrix
CONSUMABLES	All-in-One cartridges Cartridge 718 Black (3,400 pages ^{6,7}) Cartridge 718 Cyan (2,900 pages ^{6,7}) Cartridge 718 Magenta (2,900 pages ^{6,7}) Cartridge 718 Yellow (2,900 pages ^{6,7}) Cartridge 718 Black VP (6,800 pages ^{6,7})
ACCESSORIES / OPTIONS	Items Paper Feeder PF-701
Standard disclaimers. All specifications subject to change without notice. 1] Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product 2] Declared noise emission in accordance with ISO 9296 3] English driver only 4] Web distribution only 5] The driver will be released in February 2013 6] Based on ISO/IEC 19798 7] Printer ships with 1,200-page K (Black) and 1,400-page CMY (Cyan, Magenta and Yellow) starter cartridges	

