

# Delock USB Condenser Microphone Omnidirectional for Conferences

## Description

This table microphone by Delock is suitable for use in conferences.

### Optimal recordings

The microphone has a circle pattern (omnidirectional) and therefore captures the acoustic signal ideally. Due to a high power, low self-noise and precise performance, even the finest sounds are optimally recorded.

### Touch mute button & status LED

The touch mute button quickly mutes the microphone. The LED is red when muted and green when recording.

### Headphone output

The microphone has a 3.5 mm stereo jack output for connecting headphones or speakers.

### Plug & Play

Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as Windows, Mac OS, Chrome OS and Linux.



1,5 m

## Specification

- Connectors:
  - 1 x USB 2.0 Type-A male
  - 1 x 3.5 mm 3 pin stereo jack female
- Directivity: omnidirectional
- Sensitivity: -16 dB +/- 3 dB
- Frequency range: 100 Hz - 10 kHz
- Sample rate: 16 Bit / 44.1 kHz
- Signal-to-noise ratio (SNR): ca. 65 dB
- Mute-Button
- Status LED
- Cable length: ca. 1.5 m
- Colour: black
- Dimensions (Ø x H): ca. 75 x 19 mm
- USB bus powered
- Plug & Play

## System requirements

- Chrome OS
- Linux Kernel 4.4 or above
- Mac OS 10.9 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

## Package content

- USB microphone
- User manual

## Item no. 20672

EAN: 4043619206728

Country of origin: China

Package: • Retail Box



Images



operational

muted

**General**

Function:	Plug & Play
Supported operating system:	Chrome OS Mac OS 10.9 or above Windows 7 32-bit Windows 7 64-bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Linux Kernel 4.4 or above

LED indicator:	1 x
----------------	-----

**Interface**

connector:	1 x USB 2.0 Type-A male
------------	-------------------------

**Technical characteristics**

Frequency range:	100 Hz - 10 kHz
Voltage:	USB bus powered
Sensibility:	-16 dB +/- 3 dB
Sample rate:	16 Bit / 44.1 kHz
Signal noise ratio (SNR):	ca. 65 dB
Directivity:	omnidirectional

**Physical characteristics**

Cable length:	1.5 m
Diameter:	75 mm
Height:	19 mm
LED colour:	red green