

Technical Specifications



1. Power Button

Technical Specifications

HP Z27k G3 4K USB-C Display



- 1. OSD control
- 2. Security cable slot
- **3.** Master power switch
- **4.** Power connector
- 5. HDMI port
- **6.** DisplayPort connector
- 7. DisplayPort connector OUT

Back

- **8.** USB Type-C[™] port with DP Alt Mode 1.4, USB upstream data, and maximum power delivery up to 100 W
- 9. RJ-45 (network) jack
- 10. USB port
- 11. USB port (Battery charging 1.2, 7.5W)
- 12 USB port
- **13.** USB port (Battery charging 1.2, 7.5W)

Technical Specifications

Panel Specifications Display Size (Diagonal) 27"

Panel TechnologyIPSRefresh Rate60 Hz

Panel Bit Depth 10 bit (8 bit + FRC)

Aspect Ratio 16:9
Brightness (Typical) 350 nits
Contrast Ratio (Static) 1000:1
Contrast Ratio Minimum (Static) 700:1
Dynamic Contrast Ratio 10M:1
Flicker Free Yes

Pixel Pitch 0.1554 x 0.1554 mm

Pixels Per Inch (Ppi) 163 PPI Backlight Lamp Life Minimum (To Half 40 k

Brightness - In Hours)

Backlight TypeEdge-litScreen TreatmentAnti-glareHardness3HHaze25%

Response Time (Typical) 5ms GtG (with overdrive)

Horizontal Viewing Angle (Typical 178°

Cr>10)

Vertical Viewing Angle (Typical Cr>10) 178°

Panel Active Area (W X H) 596.736(H) x 335.664(V)

NOTE: Performance Specifications Represent The Typical Specifications Provided By HP's Component

Manufacturers; Actual Performance May Vary Either Higher Or Lower.

Color Management Factory Color Calibrated Yes (Delta E <=2)

Calibrated Color Presets sRGB, BT.709, (Color Match)

RGB Channel Adjust Yes, Gain **Default Color Temperature** sRGB

Color sRGB 99 % P3 D65 85%

Monitor Specifications Bezel 4-sided Micro Edge

Color (Head) Turbo Silver ; (Stand) Turbo Silver

Tilt -5 to +20°
Swivel ±45°
Pivot ±90
Height Adjust Range 150mm

VESA Mounting 100 mm x 100 mm (bracket included)

Security Lock Ready Standard Security Lock Slot

Detachable Stand Yes

Warranty (Number Of Years)

3/3/0 for LA, NA, EMEA, APJ; (3/3/3 in select APJ Countries)

Low Blue Light Mode

Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution

certified)

Display Management Software HP Display Center

On Screen Display Brightness +, Color, Image, Input, Power, Menu,

Management, Information, Exit

User-Assignable Function Buttons Yes, 4 buttons

Native Resolution4K UHD (3840 x 2160)Maximum Resolution3840 x 2160 @ 60HZ



Technical Specification

tions	
Preset Graphic Modes/Supported Resolutions	640 x 480 @ 60Hz 800 x 600 @ 60Hz 1024 x 768 @ 60Hz 1280 x 720 @ 60Hz 1280 x 800 @ 60Hz 1280 x 1024 @ 60Hz 1440 x 900 @ 60Hz 1600 x 900 @ 60Hz 1600 x 1200 @ 60Hz 1680 x 1050 @ 60Hz
	1920 x 1080 @ 60Hz 1920 x 1200 @ 60Hz 2560 x 1440 @ 60Hz 2560 x 1600 @ 60Hz 3840 x 2160 @ 23Hz 3840 x 2160 @ 24Hz 3840 x 2160 @ 30Hz 3840 x 2160 @ 60Hz
High Definition Video Formats	720 x 480i @ 60Hz 720 x 480p @ 60Hz 1280 x 720p @ 60Hz 1920 x 1080i @ 60Hz 720 x 576i @ 50Hz 720 x 576p @ 50Hz 1280 x 720p @ 50Hz 1920 x 1080i @ 50Hz 1920 x 1080p @ 60Hz 1920 x 1080p @ 60Hz 640 x 480p @ 60Hz
Minimum Vertical Scan Rate	50 Hz
Maximum Vertical Scan Rate	60 Hz
Minimum Horizontal Scan Rate	30.0 kHz
Maximum Horizontal Scan Rate	80.0 kHz
Maximum Pixel Clock	600 MHz
User Programmable Modes	20
Languages	10 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese and S-Chinese)
DisplayPort™	1 DisplayPort™ 1.4
DisplayPort™ Out	1 DisplayPort™ 1.4-out
HDMI	1 HDMI 2.0
USB Type-C™ Video Input	1 USB Type-C™ (DP Alt Mode 1.4, power delivery up to
	100W)
USB- A	4 USB-A 3.2 Gen1 (2 for battery charging 1.2, 7.5W)
Ethernet	Yes
Picture-in-Picture, Picture-by-Picture	Yes
DaisyChain/DisplayPort Multi stream Transport (MST)	Yes
User Updateable Firmware	Yes
Power Supply	Internal
Power Source	100 – 240 VAC 50 / 60 Hz
Power Consumption- MAX	165 W
Energy Saving/Stand By Mode	0.5 W
Power Consumption- Typical	42 W



Specs

Connector Types

Special Features

Power & Operating

Power Consumption- Typical

42 W

Technical Specifications

recnnical Specifications					
	Power Cable Length	1.9 m			
ENERGY STAR Data	Operational Mode at 100 VAC	28.08 W			
	Operational Mode at 115 VAC Operational Mode at 230 VAC	28.02 W 27.98 W			
EU Energy Efficiency Class (Ec1062)	On-mode Power Consumption (EC 1062/2010)	29.1 W			
etass (Ec.1002)	Annual Power Consumption (EC 1062/2010)	43 kWh			
	Energy Efficiency Class (EC 1062/2010)	Α			
Operating Conditions	Operating Temperature - Celsius Operating Temperature - Fahrenheit Non-Operatin Temperature - Celsius Non-Operating Temperature -	5° – 35°C 41° – 95°F –34° – 60°C 29° – 140°F			
	Fahrenheit Operating Humidity Non-Operating Humidity Operating Altitude Non-operating Altitude	20 – 80% Relative Humidity 5 – 95% 0 – 5,000 m (16,400 ft.) 0 – 12.192 m (40,000 ft.)	(non-condensing)		
Environmental Features and Certifications	Mercury-free LED display backlighting Arsenic-Free Display Glass Low Halogen	Yes, Mercury-free LED backl Yes Yes WW application			
	Agency Approvals And Certifications	CE,CB,KC/KCC/NOM/PSB/EAC Low Blue Light/ BIS/cTUVus/ Star/TCO/TCO Certified Edge/VCCI/FCC/BSMI/WEEE/	CCC/CEL/CECP/SEPA/Energy		
	Microsoft WHQL Certification	Yes			
	ENERGY STAR® Certified	Yes			
	EPEAT® Registered	Yes			
	Regions need to verify by country				
	China Energy Label TCO Certified Edge	CEL Grade 1 Yes			
	TCO Certified	Yes			
	SmartWay Transport Partnership - NA only	Yes (NA sku)			
Contains Recycled Plastics	Contains Recycled Plastics	86.3%			
	Recyclable Packaging (Box, packing materials)	100% recyclable packaging.			
Unit Product/Package Specifications	Product Dimensions (Unpacked with stand) (W x D x H)	61.23 x 20.50 x 53.03 cm	24.11 x 8.07 x 20.88 in		
-	Product Dimensions (Packed) (W x D x H)	69.8 x 42.3 x 16.3 cm	27.48x 16.65 x 6.42 in		
	Display Head Dimensions (Unpacked without stand) (W x D x H)	61.23 x 6.35 x 35.61 cm	24.11 x 2.50 x 12.02 in		



Technical Specifications

Base Area Footprint (w x d mm)	246 x 205 mm	9.69 x 8.07 in
Product Weight (Unpacked with stand)	6.2 kg	13.7 lb
Product Weight (Packed)	9.4 kg	20.7 lb
Product Weight (Head Only)	4.6 kg	10.14 lb

What's in the box? Documentation kit

DP1.4 Cable (1.8m)

USB3.2 Gen2 Type C to C (1m)

Power cable VESA Adapter Cable Holder

User Guide and Warranty Languages **User Guide Languages**

Warranty Languages

English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.

Turk

English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and

Turkish.

Technical Specifications

Copyright © 2021 HP Development Company, L.P.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency.



Summary

Change Log					
	V1 to V2				

