

9-PIN WIDE CARRIAGE IMPACT PRINTER

# LX-300+II

**EPSON**  
EXCEED YOUR VISION




**Minimum cost,  
maximum workload**

- Improved processing speed with a 64KB Input Data Buffer
- Fast print speed of up to 337 Characters Per Second (12 CPI)
- Achieve optimum efficiency with 5 Part Forms printout (1 original + 4 copies)
- Greater connectivity with built-in USB, Serial and Parallel Interface options
- Choice of 8 Built-in Bar Code formats for maximum versatility

# SPECIFICATIONS

Weight – approx. 4.4 kg



## OPTIONS

FABRIC RIBBON CARTRIDGE (BLACK)  
 FABRIC RIBBON PACK (BLACK)  
 FABRIC RIBBON CARTRIDGE (COLOUR)  
 SINGLE BIN CUT SHEET FEEDER  
 PULL TRACTOR UNIT  
 COLOUR UPGRADE KIT  
 ROLL PAPER HOLDER

## 9-PIN WIDE CARRIAGE IMPACT PRINTER

# LX-300+II

<b>PRINT DIRECTION</b>	Bi-directional with logic seeking		
<b>PRINT SPEED</b>	HIGH SPEED DRAFT HIGH SPEED DRAFT CONDENSED DRAFT DRAFT CONDENSED NLQ	10/12/15 CPI 17/20 CPI 10/12/15 CPI 17/20 CPI 10/12/15/17/20 CPI	300/337/337 cps 321/300 cps 225/270/225 cps 191/225 cps 56/67/56/47/56 cps
<b>PRINT CHARACTERISTICS</b>	CHARACTER SETS BITMAP FONTS BAR CODE FONT	13 International character sets; 13 character code tables (Standard); Italic, PC437, PC850, PC860, PC861, PC863, PC865, Abicomp, BRASCI, Roman 8, ISO Latin 1, PC858, ISO 8859-15 Epson Draft: 10, 12, 15 CPI; Epson Roman and Sans Serif: 10, 12, 15 CPI, Proportional EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, PostNet	
<b>PRINTABLE COLUMNS</b>	PITCH (CPI) 10 CPI 12 CPI 15 CPI 17 CPI CONDENSED 20 CPI CONDENSED	Character per line 80 96 120 137 160	
<b>PAPER HANDLING PAPER PATH</b>	MANUAL INSERTION: PUSH TRACTOR: PULL TRACTOR: CUT SHEET FEEDER:	Rear in, Top out Rear in, Top out Rear/Bottom in, Top out Rear in, Top out	
<b>PAPER SIZE CUT SHEET</b>	MANUAL INSERTION	Width: Length: Thickness:	100 ~ 257 mm (3.9 ~ 10.1") 100 ~ 364 mm (3.9 ~ 14.3") 0.065 ~ 0.14 mm (0.0025 ~ 0.0055")
	CSF SINGLE-BIN	Width: Length: Thickness:	182 ~ 216 mm (7.2 ~ 8.5") 257 ~ 356 mm (10.1 ~ 14.0") 0.07 ~ 0.14 mm (0.0028 ~ 0.0055")
	MULTI PART	Width: Length: Thickness:	100 ~ 257 mm (3.9 ~ 10.1") 100 ~ 364 mm (3.9 ~ 14.3") 0.12 ~ 0.39 mm (0.0047 ~ 0.015") (Total)
<b>ENVELOPE</b>	No. 6	Width: Length: Thickness:	165 mm (6.5") 92 mm (3.6") 0.16 ~ 0.52 mm (0.0063 ~ 0.0205") (Total)
	No. 10	Width: Length: Thickness:	241 mm (9.5") 105 mm (4.1") 0.16 ~ 0.52 mm (0.0063 ~ 0.0205") (Total)
<b>CONTINUOUS PAPER</b>		Width: Length: Thickness:	101.6 ~ 254 mm (4.0 ~ 10.0") 101.6 ~ 558.8 mm (4.0 ~ 22.0") 0.065 ~ 0.39 mm (0.0025 ~ 0.015") (Total)
<b>LABEL</b>		Width: Length: Thickness:	101.6 ~ 254 mm (4.0 ~ 10.0") 101.6 ~ 558.8 mm (4.0 ~ 22.0") 0.07 ~ 0.09 mm (0.0028 ~ 0.0035") (Base)
<b>ROLL PAPER</b>		Width: Length: Thickness:	0.16 ~ 0.19 mm (0.0063 ~ 0.0075") (Total) 216 mm (8.5") –
<b>PAPER FEEDING</b>	STANDARD	Friction: Push Tractor: Pull Tractor: Cut Sheet Feeder: Push-Pull Tractor:	0.07 ~ 0.09 mm (0.0028 ~ 0.0035") Rear in, Top out Rear in, Top out Rear/Bottom in, Top out Rear in, Top out Rear in, Top out
	OPTIONAL		Original + 4 copies 1/6 inch or programmable by 1/216 inch
<b>COPIES LINE SPACING</b>			
<b>INPUT DATA BUFFER</b>			64 KByte
<b>INTERFACE</b>	STANDARD		Bi-directional parallel interface (IEEE-1284 nibble mode supported); Serial interface; USB interface (ver 1.1)
<b>RIBBON CARTRIDGE</b>	STANDARD	FABRIC RIBBON CARTRIDGE (BLACK)	RIBBON LIFE: Approx. 3 million characters (Draft 10 CPI, 14 dots/character)
	OPTION	FABRIC RIBBON CARTRIDGE (COLOUR)	RIBBON LIFE: Black Approx. 1 million characters (Draft 10 CPI, 14 dots/character) Magenta Approx. 0.7 million characters (Draft 10 CPI, 14 dots/character) Cyan Approx. 0.7 million characters (Draft 10 CPI, 14 dots/character) Yellow Approx. 0.5 million characters (Draft 10 CPI, 14 dots/character)
<b>ACOUSTIC NOISE</b>			Approx. 49dB (A) (ISO 7779 pattern)
<b>RELIABILITY</b>	MVBF (Mean Print Volume Between Failure) MTBF (Mean Time Between Failure) PRINT HEAD LIFE		12 million lines (Except print head) 6000 POH (25% duty cycle) Approx. 400 million strokes/wire
<b>CONTROL PANEL</b>			4 switches, 4 LEDs
<b>ENVIRONMENTAL CONDITIONS (OPERATING)</b>	TEMPERATURE HUMIDITY		5 ~ 35 °C 10 ~ 80 % RH
<b>ELECTRICAL SPECIFICATIONS</b>	RATED VOLTAGE RATED FREQUENCY POWER CONSUMPTION		AC 120 V, AC 220 ~ 240 V 50 ~ 60 Hz Approx. 23 W (ISO/IEC 10561 Letter Pattern); ENERGY STAR compliant
<b>DIMENSIONS (D X W X H)</b>			275 x 366 x 159 mm
<b>WEIGHT</b>			Approx. 4.4 kg
<b>PRINTER DRIVER /UTILITY</b>	OS UTILITY		Microsoft® Windows® 98/2000/Me/XP and Microsoft® Windows® NT® 4.0 Epson Status Monitor 3 (Microsoft® Windows® 98/2000/Me/XP and Microsoft® Windows® NT® 4.0 environment only)

Epson is the registered trademark of SEIKO Epson CORPORATION.

All other product names and other company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Scan/Print samples shown herein are simulations. Specifications are subject to change without notice.

# EPSON

EXCEED YOUR VISION

1 Harbourfront Place  
 #03-02 HarbourFront Tower One  
 Singapore 098633

(65) 6586 5500  
 (65) 6334 2710

Dealer's Stamp