

### Overview

### HP ProBook 650 G4



#### Right

- |                               |  |
|-------------------------------|--|
| 1. Webcam (Select models)     | 9. HDMI port (Cable not included)      |
| 2. Webcam LED (Select models) | 10. USB 3.1 Gen 1 port                 |
| 3. Internal microphones (2)   | 11. USB 3.1 Gen 1 charging port        |
| 4. Power connector            | 12. USB Type-C™ charging port          |
| 5. MicroSD card slot          | 13. Audio combo jack                   |
| 6. Docking connector          | 14. HDD LED indicator                  |
| 7. VGA port                   | 15. Fingerprint reader (Select models) |
| 8. Ethernet port              | 16. Clickpad                           |

### Overview



#### Left

- 1. Smart Card Reader (Select models)
- 2. Optical drive (Select models)
- 3. Security lock slot
- 4. Power button

### Overview

#### AT A GLANCE

- Windows 10 versions, NeoKylin Linux 64<sup>1</sup> or FreeDOS 2.0
- Precision-crafted slim design with fingerprint resistant modern, fresh and comfortable natural silver finish
- Choice of 8th Generation Intel® Core™processors, with integrated graphics or optional AMD RX540 Radeon™ 128 bit Discrete Graphics
- HP Advanced keyboard, spill resistant with optional backlit design
- Large Clickpad with gestures support
- Enhanced security features including TPM2.0, HP Privacy Camera, optional Smart Card Reader, optional Finger Print Reader, and HP Sure Start Gen4.
- LED-backlit display  
39.6 cm (15") diagonal HD and FHD or Touch FHD with camera and with WWAN
- HDMI port for connecting to high-resolution displays
- Optional Integrated ODD
- Optional HD webcam with dual-microphone array for video conferencing
- Two USB 3.1 Gen1 ports (1 charging) and one USB-C port (PD+DP, Gen1)
- VGA or Serial Port
- Flexible wireless connectivity options
- Battery hours up to 13 hours with fast charging technology
- Dual storage combines SSD fast boot up and app access with cost effective HDD mass storage
- Passed MIL-STD 810G testing<sup>2</sup>

1. Linux not offered in Americas Region

2. MIL-STD-810G testing is conducted on select HP products. Testing is not intended to demonstrate fitness of U.S. Department of Defense (DoD) contract requirements or for military use. Test results are not a guarantee of future performance under these test conditions. Accidental damage requires an optional HP Accidental Damage Protection Care Pack.

**NOTE: See important legal disclosures for all listed specs in their respective features sections.**

## Technical Specifications

### PRODUCT NAME

HP ProBook 650 G4

### OPERATING SYSTEM

<b>Preinstalled</b>	Windows 10 Pro 64 <sup>1</sup> Windows 10 Pro (National Academic only) <sup>1,2</sup> Windows 10 Home 64 <sup>1</sup> Windows 10 Home Single Language 64 <sup>1</sup> FreeDOS 2.0
---------------------	---

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com/>.

2. Some devices for academic use will automatically be updated to Windows 10 Pro Education with the Windows 10 Anniversary Update. Features vary; see <https://aka.ms/ProEducation> for Windows 10 Pro Education feature information.

### PROCESSORS

Intel® Core™ i7-8650U with Intel® UHD graphics 620  
(1.9 GHz base frequency, up to 3.9 GHz with Intel® Turbo Boost Technology, 8 MB cache, 4 cores)<sup>3,4,5</sup>  
Intel® Core™ i7-8550U with Intel® UHD graphics 620  
(1.8 GHz base frequency, up to 4 GHz with Intel® Turbo Boost Technology, 8 MB cache, 4 cores)<sup>3,4,5</sup>  
Intel® Core™ i5-8350U with Intel® UHD Graphics 620  
(1.7 GHz base frequency, up to 3.6 GHz with Intel® Turbo Boost Technology, 6 MB cache, 4 cores)<sup>3,4,5</sup>  
Intel® Core™ i5-8250U with Intel® UHD Graphics 620  
(1.6 GHz base frequency, up to 3.4 GHz with Intel® Turbo Boost Technology, 6 MB cache, 4 cores)<sup>3,4,5</sup>  
Intel® Core™ i5-7300U with Intel® HD Graphics 620  
(2.6 GHz base frequency, up to 3.5 GHz with Intel® Turbo Boost Technology, 3 MB cache, 2 cores)<sup>3,4,5</sup>  
Intel® Core™ i5-7200U with Intel® HD Graphics 620  
(2.5 GHz base frequency, up to 3.1 GHz with Intel® Turbo Boost Technology, 3 MB cache, 2 cores)<sup>3,4,5</sup>  
Intel® Core™ i3-8130U with Intel® HD Graphics 620  
(2.2 GHz, 4 MB cache, 2 cores)<sup>3,4,5,6</sup>

#### Processor Family

8th Generation Intel® Core™ i7 processor (i7-8650U, i7-8550U models)<sup>5</sup>  
8th Generation Intel® Core™ i5 processor (i5-8350U, i5-8250U models)<sup>5</sup>  
8th Generation Intel® Core™ i3 processor (i3-8130U model)<sup>5,6</sup>  
7th Generation Intel® Core™ i5 processor (i5-7300U, i5-7200U models)<sup>5</sup>

3. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.

4. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

5. NOTE: In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>.

6. Intel® Core™ i3-8130U processor is planned to be available in 2Q 2018.

### Technical Specifications

#### CHIPSET

Chipset is integrated with processor

---

#### GRAPHICS

##### Integrated

Intel® UHD graphics 620<sup>7</sup>

Intel® HD graphics 620<sup>7</sup>

Note: View processor section for details.

##### Discrete

AMD Radeon™ RX540 (2 GB GDDR5 dedicated)<sup>8</sup>

7. HD content required to view HD images.

8. AMD Dynamic Switchable Graphics technology requires an Intel processor, plus an AMD Radeon™ discrete graphics configuration and is not available on FreeDOS and Linux OS. With AMD Dynamic Switchable Graphics technology, full enablement of all discrete graphics video and display features may not be supported on all systems (e.g. OpenGL applications will run on the integrated GPU or the APU as the case may be).

---

#### DISPLAY

##### Non-Touch HD

39.6 cm (15.6") diagonal HD SVA eDP anti-glare LED-backlit, 220 cd/m<sup>2</sup>, 45% sRGB (1366 x 768)<sup>7,9</sup>

39.6 cm (15.6") diagonal HD SVA eDP anti-glare LED-backlit, 220 cd/m<sup>2</sup>, 45% sRGB, for camera (1366 x 768)<sup>7,9</sup>

39.6 cm (15.6") diagonal HD SVA eDP anti-glare LED-backlit, 220 cd/m<sup>2</sup>, 45% sRGB, for WWAN (1366 x 768)<sup>7,9</sup>

39.6 cm (15.6") diagonal HD SVA eDP anti-glare LED-backlit, 220 cd/m<sup>2</sup>, 45% sRGB, for camera and WWAN (1366 x 768)<sup>7,9</sup>

##### Non-Touch FHD

39.6 cm (15.6") diagonal FHD IPS eDP anti-glare LED-backlit, 220 cd/m<sup>2</sup>, 45% sRGB (1920 x 1080)<sup>7,9</sup>

39.6 cm (15.6") diagonal FHD IPS eDP anti-glare LED-backlit, 220 cd/m<sup>2</sup>, 45% sRGB, for camera (1920 x 1080)<sup>7,9</sup>

39.6 cm (15.6") diagonal FHD IPS eDP anti-glare LED-backlit, 220 cd/m<sup>2</sup>, 45% sRGB, for WWAN (1920 x 1080)<sup>7,9</sup>

39.6 cm (15.6") diagonal FHD IPS eDP anti-glare LED-backlit, 220 cd/m<sup>2</sup>, 45% sRGB, for camera and WWAN (1920 x 1080)<sup>7,9</sup>

##### Touch FHD

39.6 cm (15.6") diagonal FHD IPS eDP LED-backlit touch screen, 220 cd/m<sup>2</sup>, 45% sRGB, for camera and WWAN (1920 x 1080)<sup>7,9</sup>

7. HD content required to view HD images.

9. Resolutions are dependent upon monitor capability, and resolution and color depth settings.

---

## Technical Specifications

### STORAGE AND DRIVES

#### Primary Storage

500 GB 7200 rpm<sup>10</sup>  
500 GB 7200 rpm Self Encrypting Drive (FIPS-140-2)<sup>10</sup>  
1 TB 7200 rpm<sup>10</sup>

#### Primary M.2 Storage

16GB PCIe NVMe 3D X (Need to work with HDD) (Planned to be available in 2Q 2018)  
118GB PCIe NVMe 3D X (Planned to be available in 3Q 2018)  
128 GB SATA-3 SS TLC<sup>10</sup>  
256 GB SATA-3 TLC OPAL2<sup>10</sup>  
256 GB PCIe NVMe SS Value<sup>10</sup>  
256 GB PCIe Gen3x4 NVMe SS TLC<sup>10</sup>  
360 GB Intel PCIe Gen3x4 NVMe SS TLC<sup>10</sup>  
512 GB SATA SS TLC (FIPS)<sup>10</sup>  
512 GB PCIe Gen3x4 NVMe SS TLC<sup>10</sup>  
1 TB PCIe Gen3x4 NVMe SS TLC<sup>10</sup>

10. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10) is reserved for system recovery software.

### MEMORY

#### Maximum Memory

32 GB DDR4-2400 SDRAM<sup>11</sup>

#### Memory

4 GB Total System Memory (4 GB x 1)<sup>11</sup>  
8 GB Total System Memory (4 GB x 2)<sup>11</sup>  
8 GB Total System Memory (8 GB x 1)<sup>11</sup>  
12 GB Total System Memory (8 GB + 4 GB)<sup>11</sup>  
16 GB Total System Memory (16 GB x 1)<sup>11</sup>  
16 GB Total System Memory (8 GB x 2)<sup>11</sup>  
32 GB Total System Memory (16 GB x 2)<sup>11</sup>

#### Memory Slots

2 SODIMM  
Both slots are customer accessible / upgradeable  
DDR4 PC4 SODIMMS - System supports run rate at 2133 in 7th Gen Processor, 2400 in 8th Gen processor  
Supports Dual Channel Memory

11. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

## Technical Specifications

### NETWORKING/COMMUNICATIONS

#### WLAN

Intel® Dual Band Wireless-AC 3168 802.11a/b/g/n/ac (1x1) Wi-Fi® and Bluetooth® 4.2 Combo, non-vPro™<sup>12</sup>

Intel® Dual Band Wireless-AC 8265 802.11a/b/g/n/ac (2x2) Wi-Fi® and Bluetooth® 4.2 Combo, vPro™<sup>12</sup>

Intel® Dual Band Wireless-AC 8265 802.11a/b/g/n/ac (2x2) Wi-Fi® and Bluetooth® 4.2 Combo, non-vPro™<sup>12</sup>

Realtek RTL8822BE 802.11ac 2x2 Wi-Fi® and Bluetooth® 4.2 Combo Adapter<sup>12</sup>

Realtek RTL8821CE 802.11ac 1x1 Wi-Fi® and Bluetooth® 4.2 Combo Adapter<sup>12</sup>

#### WWAN

LTE CAT4: Huawei HP Lt4132, LTE/HSPA+ w/GPS M.2<sup>13</sup>

LTE CAT9: Fibocom Intel(R) XMM(TM) 7360 LTE-Advanced Lt4210 LTE/HSPA+ w/GPS<sup>13</sup>

#### NFC

NXP NPC300 Near Field Communication Module<sup>14</sup>

#### WPAN Bluetooth

BT 4.2 supported via all supported WLAN modules<sup>12</sup>

#### Ethernet

Intel® Ethernet Connection I219-LM 10/100/1000 (vPro™)<sup>15</sup>

Intel® Ethernet Connection I219-V 10/100/1000 (Non-vPro™)<sup>15</sup>

12. Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited. The specifications for the 802.11ac WLAN are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ac WLAN devices.

13. WWAN module requires separately purchased service contract. Check with service provider for coverage and availability in your area. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products, in all regions.

14. Sold separately or as an optional feature.

15. The term "10/100/1000" or "Gigabit" Ethernet indicates compatibility with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

### AUDIO/MULTIMEDIA

#### Audio

2 Integrated stereo speakers

Integrated dual array microphone

#### Webcam

720p HD HP Privacy Camera<sup>7,14,16</sup>

#### Optical Drive

DVD-ROM (defeatured combo)

DVD Writer SATA

7. HD content required to view HD images.

14. Sold separately or as an optional feature.

16. Internet access required.

## Technical Specifications

### KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

#### Keyboard

HP Advanced Keyboard  
ClickPad, Spill-resistant with drain  
ClickPad, Spill-resistant with drain, DuraKeys & Backlit  
Dual Point, Spill-resistant with drain, DuraKeys & Backlit  
Dual Point, Spill-resistant with drain, DuraKeys & Backlit Privacy

#### Function Keys

ESC: system information  
F1 - Display Switching  
F2 - Blank or Privacy  
F3 - Brightness Down  
F4 - Brightness Up  
F5 - Speaker Mute  
F6 - Volume Down  
F7 - Volume Up  
F8 - Mic Mute  
F9 - Backlight Toggle (for backlit keyboard) or Blank  
F10 - NumLock  
F11 - Wifi Toggle  
F12 - Sleep

#### Clickpad requirements:

On/off control by driver  
Taps enabled as default  
Gestures:  
(Win 10):  
Disabled by default:  
3 Finger Flick  
2 Finger Rotate  
Momentum Motion  
1 Finger Vertical Scroll  
Win 10:  
Support PTP with Miniport driver  
Settings enabled by default by MSFT:  
2 Finger Scrolling  
2 Finger Zoom (Pinch)  
OSD (enable/disable)  
3 finger tap - Cortana  
3 finger flick - App switch  
4 finger tap - Action Center



### Technical Specifications

#### SOFTWARE AND SECURITY

##### Preinstalled Software

###### BIOS

HP BIOSphere Gen4<sup>18</sup>  
HP DriveLock & Automatic DriveLock  
BIOS Update via Network  
Master Boot Record Security  
Power On Authentication  
Secure Erase<sup>19</sup>  
Absolute Persistence Module<sup>20</sup>  
Pre-boot Authentication  
HP Wireless Wakeup

###### Software

HP Native Miracast Support<sup>17</sup>  
HP LAN-Wireless Protection  
HP Velocity  
HP 3D DriveGuard  
HP ePrint + JetAdvantage<sup>21</sup>  
HP Hotkey Support - CMIT  
HP Recovery Manager  
HP Jumpstart  
HP Support Assistant<sup>22</sup>  
HP Noise Cancellation Software  
HP Host Based MAC Address Manager  
HP PhoneWise<sup>29</sup>  
Buy Office

##### Manageability Features

HP Driver Packs<sup>23</sup>  
HP System Software Manager (SSM)  
HP BIOS Config Utility (BCU)  
HP Client Catalog  
HP Manageability Integration Kit Gen2<sup>24</sup>  
Ivanti Management Suite<sup>25</sup>

##### Client Security Software

HP Client Security Suite Gen4 including:<sup>26</sup>  
HP Security Manager<sup>27</sup> (including Credential Manager, HP Password Manager, HP Spare Key)  
Power On Authentication  
HP Fingerprint Sensor<sup>30</sup>

### Technical Specifications

HP Device Access Manager  
Microsoft Defender<sup>28</sup>

#### Security Management

Secure Erase<sup>19</sup>  
TPM 2.0 Embedded Security Chip shipped with Windows 10 (Common Criteria EAL4+ Certified)<sup>31</sup>  
SATA 0,1 port disablement (viaBIOS)  
RAID configurations<sup>31</sup>  
Serial, USB enable/disable (viaBIOS)  
Power-on password (viaBIOS)  
Setup password (viaBIOS)  
Support for chassis padlocks and cable lock devices  
Integrated hood sensor  
HP Sure Click<sup>32</sup>  
HP Sure Start Gen4

#### Security

##### TPM

Model: TPM SLB9670 VQ2.0 FW7.63RS3 913310-002  
Version: TPM 2.0  
Revision: 1.16  
FIPS 140-2 Compliant: No

##### Smartcard Reader

Model number: Alcor AU9560  
FIPS 201 Compliant: Yes

##### IPv6 Certification

No

##### MD5 Hash

Please follow the instructions below to access MD5 Hash.

Log-on to <http://hp.com/support>, enter your product name, select software and drivers, select OS, select driver. After selecting the driver, click on “Associated files” and then click on “Download”. When opening the file, under “Purpose” you should see the appropriate “SOFTPAQ MD5:” Field

##### Is the BIOS on this notebook ISO/IEC 19678:2015 (formerly NIST 800-147) compliant?

Yes

UEFI version: 2.5

### Technical Specifications

17. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming
18. HP BIOSphere Gen4 features may vary depending on the PC platform and configurations. Requires Intel® or AMD 8th generation processors.
19. Secure Erase for the methods outlined in the National Institute of Standards and Technology Special Publication 800-88. Supported on Elite platforms with BIOS version F.03 or higher.
20. Absolute agent is shipped turned off, and will be activated when customers activate a purchased subscription. Subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. The Absolute Recovery Guarantee is a limited warranty. Certain conditions apply. For full details visit: <http://www.absolute.com/company/legal/agreements/computrace-agreement>. Data Delete is an optional service provided by Absolute Software. If utilized, the Recovery Guarantee is null and void. In order to use the Data Delete service, customers must first sign a Pre-Authorization Agreement and either obtain a PIN or purchase one or more RSA SecurID tokens from Absolute Software.
21. HP ePrint Driver requires an Internet connection to HP web-enabled printer and HP ePrint account registration (for a list of eligible printers, supported documents and image types and other HP ePrint details, see [www.hp.com/go/eprintcenter](http://www.hp.com/go/eprintcenter)). Print times and connection speeds may vary.
22. HP Support Assistant requires Windows and Internet access.
23. HP Driver Packs not preinstalled, however available for download at <http://www.hp.com/go/clientmanagement>.
24. HP Manageability Integration Kit can be downloaded from <http://www8.hp.com/us/en/ads/clientmanagement/overview.html>
25. Ivanti Management Suite subscription required.
26. HP Client Security Suite Gen 4 requires Windows and Intel® or AMD 8th generation processors.
27. HP Password Manager requires Internet Explorer or Chrome or FireFox. Some websites and applications may not be supported. User may need to enable or allow the add-on / extension in the internet browser.
28. Microsoft Defender Opt in and internet connection required for updates.
29. HP PhoneWise Client is only available on select platforms. For supported platforms and HP PhoneWise system requirements see <http://www.hp.com/go/HPPhoneWise>.
30. HP Fingerprint Sensor sold separately or as an optional feature.
31. RAID configuration is optional and does require a second hard drive.
32. HP Sure Click is available on select HP platforms and supports Microsoft® Internet Explorer and Chromium™. Check <http://h20195.www2.hp.com/v2/GetDocument.aspx?docname=4AA7-0922ENW> for all compatible platforms as they become available.

### Technical Specifications

#### POWER

##### Power Supply

HP Smart 45 W right angle 4.5 mm AC Adapter<sup>36</sup>

HP Smart 65 W right angle 4.5 mm AC Adapter<sup>36</sup>

HP Smart 45 W right angle 4.5 mm AC Adapter 2-prong (Japan only)<sup>36</sup>

45W Straight USB Type C AC Adapter

65W Straight USB Type C AC adapter

##### Primary Battery

HP Long Life 3-cell, 48 Wh Li-ion<sup>37</sup>

HP Fast Charge Technology - 90% in 90 minutes

##### Power Cord

3-wire plug (C5), 1.8m, Sticker, Conventional<sup>36</sup>

3-wire plug (C5), 1.0m, Sticker, Conventional<sup>36</sup>

2-wire plug (C5), 1.0m, Sticker, Conventional (Japan only)<sup>36</sup>

Duckhead power cord (C5) 1.0m, Sticker, Premium (For USB Type C AC adapters)

Duckhead power cord (C5) 1.8m, Sticker, Premium (For USB Type C AC adapters)

##### Battery Life

Up to 13 hours with Intel® 7th Gen CPU (with SSD)<sup>38</sup>

Up to 12 hours and 45 minutes with Intel® 8th Gen CPU (with SSD)<sup>38</sup>

33. Availability may vary by country.

34. Battery is internal and not replaceable by customer. Serviceable by warranty.

35. Windows 10 MM14 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See <http://www.bapco.com> for additional details.

#### WEIGHTS & DIMENSIONS

##### Weight

Starting at 4.8 lb (non-touch); Starting at 5.29 lb (touch)<sup>39</sup>

Starting at 2.18 kg (non-touch); Starting at 2.40 kg (touch)<sup>39</sup>

##### Dimensions (w x d x h)

###### Non-touch

14.85 x 10.12 x 0.95 in

37.7 x 25.7 x 2.395 cm

###### Touch

14.85 x 10.12 x 0.99 in

37.7 x 25.7 x 2.495 cm

36. Weight will vary by configuration.

## Technical Specifications

### PORTS/SLOTS

**Ports**

- 1 USB 3.1 Type-C™ (charging)
- 1 USB 3.1 Gen 1 (charging)
- 1 USB 3.1 Gen 1
- 1 HDMI 1.4<sup>40</sup>
- 1 RJ-45
- 1 VGA or Serial Port
- 1 headphone/microphone combo
- 1 AC power

**Expansion Slots**

- 1 docking connector
- 1 microSD (multi-format digital media reader)

[37. HDMI cable sold separately.](#)

---

### SERVICE AND SUPPORT

HP Services offers 3 year and 1 year limited warranties and 90 day support options depending on country. Long Life batteries which will have same 1-year or 3-year limited warranty as the platform. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc><sup>38</sup>

[38 HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit <http://www.hp.com/go/cpc>. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.](#)

---

## Technical Specifications

### SYSTEM UNIT

<b>Stand-Alone Power Requirements</b> (AC Power)	<b>Nominal Operating Voltage</b>	19V
	<b>Average Operating Power</b>	Win 10
	<b>Integrated Graphics</b>	6.78W
	<b>Discrete Graphics</b>	18W
	<b>Max Operating Power</b>	Discrete < 65W UMA < 45W
<b>Temperature</b>	<b>Operating</b>	32° to 95° F (0° to 35° C) (not writing optical) 41° to 95° F (5° to 35° C) (writing optical)
	<b>Non-operating</b>	-4° to 140° F (-20° to 60° C)
<b>Relative Humidity</b>	<b>Operating</b>	10% to 90%, non-condensing
	<b>Non-operating</b>	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature
<b>Shock</b>	<b>Operating</b>	40 G, 2 ms, half-sine
	<b>Non-operating</b>	200 G, 2 ms, half-sine
<b>Random Vibration</b>	<b>Operating</b>	0.75 grms
	<b>Non-operating</b>	1.50 grms
<b>Altitude</b> (unpressurized)	<b>Operating</b>	-50 to 10,000 ft (-15.24 to 3,048 m)
	<b>Non-operating</b>	-50 to 40,000 ft (-15.24 to 12,192 m)
<b>Planned Industry Standard Certifications</b>	<b>UL</b>	Yes
	<b>CSA</b>	Yes
	<b>FCC Compliance</b>	Yes
	<b>ENERGY STAR®</b>	Select models <sup>1</sup>
	<b>EPEAT®</b>	Registered Gold in United States <sup>2</sup>
	<b>ICES</b>	Yes
	<b>Australia / NZ A-Tick Compliance</b>	Yes
	<b>CCC</b>	Yes
	<b>Japan VCCI Compliance</b>	Yes
	<b>KC</b>	Yes
	<b>BSMI</b>	Yes
	<b>CE Marking Compliance</b>	Yes
	<b>BNCI or BELUS</b>	Yes
	<b>CIT</b>	Yes
	<b>GOST</b>	Yes
	<b>Saudi Arabian Compliance (ICCP)</b>	Yes
	<b>SABS</b>	Yes
<b>UKRSERTCOMPUTER</b>		

39. Configurations of the HP Probook 650 G4 that are ENERGY STAR® qualified are identified as Probook 650 G4 ENERGY STAR on HP websites and on <http://www.energystar.gov>.

40. EPEAT® registered where applicable. EPEAT registration varies by country. See <http://www.epeat.net> for registration status by country. Search keyword generator on HP's 3rd party option store for solar generator accessories at <http://www.hp.com/go/options>.

### Technical Specifications

#### DISPLAYS

**15.6" diagonal FHD UWVA anti-glare flat LED backlit non-touch; 220 cd/m<sup>2</sup>; 45% sRGB (1920 x 1080)**

<b>Outline Dimensions (W x H)</b>	360.0 x 224.3mm max
<b>Active Area</b>	344.16 x 193.59
<b>Weight</b>	360g max.
<b>Diagonal Size</b>	15.6 (inch)
<b>Thickness</b>	3.2mm max
<b>Interface</b>	eDP 1.2
<b>Surface Treatment</b>	Anti-Glare (AG)
<b>Touch Enabled</b>	None
<b>Contrast Ratio</b>	600:1 (typical)
<b>Refresh Rate</b>	60Hz
<b>Brightness</b>	220 nits
<b>Pixel Resolution</b>	1920 x 1080 (FHD)
<b>Format</b>	RGB
<b>Backlight</b>	LED
<b>Color Gamut Coverage</b>	45%
<b>Color Depth</b>	6 bits + FRC
<b>Viewing Angle</b>	UWVA 85/85/85/85

### Technical Specifications

<b>15.6" diagonal FHD UWVA anti-glare flat LED backlit touch; 220 cd/m<sup>2</sup>; 45% sRGB (1920 x 1080)</b>	<b>Outline Dimensions (W x H)</b>	360.0 x 224.3mm max
	<b>Active Area</b>	344.16 x 193.59
	<b>Weight</b>	360g max.
	<b>Diagonal Size</b>	15.6 (inch)
	<b>Thickness</b>	3.2mm max
	<b>Interface</b>	eDP 1.2
	<b>Surface Treatment</b>	BV
	<b>Touch Enabled</b>	Yes
	<b>Contrast Ratio</b>	600:1 (typical)
	<b>Refresh Rate</b>	60Hz
	<b>Brightness</b>	220 nits
	<b>Pixel Resolution</b>	1920 x 1080 (FHD)
	<b>Format</b>	RGB
	<b>Backlight</b>	LED
	<b>Color Gamut Coverage</b>	45%
	<b>Color Depth</b>	6 bits + FRC
<b>Viewing Angle</b>	UWVA 85/85/85/85	



### Technical Specifications

<b>15.6" diagonal HD SVA anti-glare LED-backlit non-touch; 220 cd/m<sup>2</sup>; 45% sRGB (1366 x 768)</b>	<b>Outline Dimensions (W x H)</b>	360 x 224.3 (mm) max
	<b>Active Area</b>	344.2 x 193.5 (mm)
	<b>Weight</b>	370 g max
	<b>Diagonal Size</b>	15.6 (inch)
	<b>Thickness</b>	3.2 (mm) max
	<b>Interface</b>	eDP 1.2
	<b>Surface Treatment</b>	Anti-Glare (AG)
	<b>Touch Enabled</b>	None
	<b>Contrast Ratio</b>	300:1 (typical)
	<b>Refresh Rate</b>	60 Hz
	<b>Brightness</b>	220 nits
	<b>Pixel Resolution</b>	1366 x 768 (HD)
	<b>Format</b>	RGB
	<b>Backlight</b>	LED
	<b>Color Gamut Coverage</b>	45%
<b>Color Depth</b>	6 bits + Hi FRC	
<b>Viewing Angle</b>	SVA 45/45/25/35	

### Technical Specifications

#### STORAGE

<b>HDD 500 GB 7200RPM 7mm SATA</b>	<b>Drive Weight</b>	0.21 lbs (95 g)
	<b>Rotation speed</b>	7200RPM
	<b>Cache Buffer</b>	Up to 32MB
	<b>Height</b>	0.28 in (7 mm)
	<b>Width</b>	2.75 in (69.85 mm)
	<b>Interface</b>	ATA-8, SATA 3.0
	<b>Transfer Rate</b>	600 MB/s
	<b>Seek Time</b>	Single Track: 2 ~ 1.5 ms; Average: 11 ~ 13 ms; Maximum: 18 ~ 22 ms
	<b>Logical Blocks</b>	976773168
	<b>Operating Temperature</b>	32° to 140°F (0° to 60°C) [ambient temp]
	<b>Security Features</b>	ATA Security
	<b>Features</b>	S.M.A.R.T., NCQ, Ultra DMA

<b>HDD 500 GB 7200RPM 7mm FIPS SATA Opal2</b>	<b>Drive Weight</b>	0.21 lbs (95 g)
	<b>Rotation speed</b>	7200 rpm
	<b>Cache Buffer</b>	Up to 32MB
	<b>Height</b>	n/a
	<b>Width</b>	0.28 in (7 mm)
	<b>Interface</b>	2.75 in (69.85 mm)
	<b>Transfer Rate</b>	ATA-8, SATA 3.0
	<b>Seek Time</b>	Single Track: 2 ~ 1.5 ms; Average: 11 ~ 13 ms; Maximum: 18 ~ 22 ms
	<b>Logical Blocks</b>	976,773,168
	<b>Operating Temperature</b>	32° to 140°F (0° to 60°C) [ambient temp]
	<b>Security Features</b>	ATA Security; TCG Opal 2.x, FIPS
	<b>Features</b>	S.M.A.R.T., NCQ, Ultra DMA

### Technical Specifications

<b>HDD 1 TB 7200RPM 7mm SATA 2.5in</b>	<b>Drive Weight</b>	90g
	<b>Rotation speed</b>	7200rpm
	<b>Cache Buffer</b>	128MB
	<b>Height</b>	7.2mm Max.
	<b>Width</b>	69.85mm
	<b>Interface</b>	ATA-8, SATA 3.0
	<b>Transfer Rate</b>	600 MB/s
	<b>Seek Time</b>	Single Track: 1.5 ms; Average: 13 ms; Maximum: 32 ms
	<b>Logical Blocks</b>	1,953,525,168
	<b>Operating Temperature</b>	0~60°C
	<b>Security Features</b>	ATA Security
	<b>Features</b>	S.M.A.R.T., NCQ, Ultra DMA, TRIM

<b>SSD 128 GB 2280 M2 SATA-3 TLC</b>	<b>Drive Weight</b>	0.02 lb (10 g)
	<b>Capacity</b>	128GB
	<b>NAND Type</b>	TLC
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Interface</b>	ATA-8, SATA 3.0
	<b>Maximum Sequential Read</b>	Up To 520 MB/s
	<b>Maximum Sequential Write</b>	Up To 450 MB/s
	<b>Logical Blocks</b>	250,069,680
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
	<b>Features</b>	DIPM; TRIM; DEVSLP

### Technical Specifications

<b>SSD 256 GB 2280 M2 PCIe-3x4 SS NVMe TLC</b>	<b>Drive Weight</b>	0.02 lb (10 g)
	<b>Capacity</b>	256GB
	<b>NAND Type</b>	TLC
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Interface</b>	PCIe NVMe Gen3X4
	<b>Maximum Sequential Read</b>	Up To 2600 MB/s
	<b>Maximum Sequential Write</b>	Up To 900 MB/s
	<b>Logical Blocks</b>	500,118,192
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
<b>Features</b>	TRIM; L1.2	

<b>SSD 256 GB 2280 M2 SATA-3 Self Encrypted OPAL2 TLC</b>	<b>Drive Weight</b>	0.02 lb (10 g)
	<b>Capacity</b>	256GB
	<b>NAND Type</b>	TLC
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Interface</b>	ATA-8, SATA 3.0
	<b>Maximum Sequential Read</b>	Up To 530 MB/s
	<b>Maximum Sequential Write</b>	Up To 515 MB/s
	<b>Logical Blocks</b>	500,118,192
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
<b>Features</b>	DIPM; TRIM; DEVSLP	

<b>256 GB 2280 PCIe NVMe Value Solid State Drive</b>	<b>Drive Weight</b>	0.02 lb (10 g)
	<b>Capacity</b>	256GB
	<b>NAND Type</b>	MLC
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Interface</b>	PCIe NVMe Gen3X4
	<b>Maximum Sequential Read</b>	Up To 1700 MB/s
	<b>Maximum Sequential Write</b>	Up To 600 MB/s
	<b>Logical Blocks</b>	703,282,608
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
<b>Features</b>	TRIM; L1.2	

### Technical Specifications

<b>SSD 512 GB 2280 M2 PCIe-3x4 SS NVMe TLC</b>	<b>Drive Weight</b>	0.02 lb (10 g)
	<b>Capacity</b>	512GB
	<b>NAND Type</b>	TLC
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Interface</b>	PCIe NVMe Gen3X4
	<b>Maximum Sequential Read</b>	Up To 2600 MB/s
	<b>Maximum Sequential Write</b>	Up To 1400 MB/s
	<b>Logical Blocks</b>	1,000,215,216
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
<b>Features</b>	TRIM; L1.2	

<b>SSD 512 GB 2280 M2 SATA-3 TLC FIPS</b>	<b>Drive Weight</b>	0.02 lb (10 g)
	<b>Capacity</b>	512GB
	<b>NAND Type</b>	TLC
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Interface</b>	ACS-3, SATA 3.2
	<b>Maximum Sequential Read</b>	Up To 530 MB/s
	<b>Maximum Sequential Write</b>	Up To 400 MB/s
	<b>Logical Blocks</b>	1,000,215,216
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
<b>Features</b>	DIPM; TRIM; DEVSLP	

<b>SSD 1 TB 2280 PCIe-3x4 NVMe TLC SS</b>	<b>Drive Weight</b>	0.02 lb (10 g)
	<b>Capacity</b>	1TB
	<b>NAND Type</b>	TLC
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Interface</b>	PCIe NVMe Gen3X4
	<b>Maximum Sequential Read</b>	2900
	<b>Maximum Sequential Write</b>	2000
	<b>Logical Blocks</b>	2000409263
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
<b>Features</b>	TRIM; L1.2	

### Technical Specifications

<b>SSD 16 GB 2280 PCIe-3x2 NVMe 3D Xpoint</b>	<b>Form Factor</b>	M.2 2280
	<b>Capacity</b>	16 GB
	<b>NAND Type</b>	Xpoint
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Interface</b>	PCIe NVMe Gen3X2
	<b>Maximum Sequential Read</b>	1400
	<b>Maximum Sequential Write</b>	300
	<b>Logical Blocks</b>	28,181,188
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
	<b>Features</b>	L1.2

### POWER

<b>AC Adapter 65 Watt nPFC USB type C™</b>	<b>Dimensions</b>	74x74x28.5mm	
	<b>Weight</b>	unit: 245g +/- 10g	
	<b>Input</b>	<b>Input Efficiency</b>	81.5% min at 115 Vac/ 230Vac @ 5V/3A 86.7% min at 115 Vac/ 230Vac @ 9V/3A 88% min at 115 Vac/ 230Vac @ 10V/5A 88% min at 115 Vac/ 230Vac @ 12V/5A 89% min at 115 Vac/ 230Vac @ 15V/4.33A 89% min at 115 Vac/ 230Vac @ 20V/3.25A
		<b>Input frequency range</b>	47 ~ 63 Hz
	<b>Output</b>	<b>Input AC current</b>	1.7 A at 90 VAC and maximum load
		<b>Output power</b>	65W
		<b>DC output</b>	5V/9V/10V/12V/15V/20V
		<b>Hold-up time</b>	5ms at 115 Vac input
		<b>Output current limit</b>	<8.0A
	<b>Connector</b>	Duck head / duck head power cord, without Smart ID DC connector	
	<b>Environmental Design</b>	<b>Operating temperature</b>	32°F to 95°F (0° to 35°C)
		<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20° to 85°C)
		<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
		<b>Humidity</b>	5% to 95%
		<b>Storage Humidity</b>	5% to 95%
<b>EMI and Safety Certifications</b>	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. MTBF - over 100,000 hours at 25°C ambient condition.		

### Technical Specifications

<b>AC Adapter 45 Watt nPFC USB type C</b>	<b>Dimensions</b>	62.0x62.0x28.5mm	
	<b>Weight</b>	unit: 220g +/- 10g	
<b>Output</b>	<b>Input</b>	<b>Input Efficiency</b> Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec:5V : 81.5%9V : 86.7%10V : 87.5%12V : 87.8%15V : 87.8%20V : 87.8%	
	<b>Output</b>	<b>Input frequency range</b>	47 ~ 63Hz
		<b>Input AC current</b>	Max. 1.4 A at 90 Vac
		<b>Output power</b>	5V/15W 9V/27W 10V/37.5W 12V/45W 15V/45W 20V/45W
		<b>DC output</b>	5V / 9V / 10V /12V / 15V / 20V
		<b>Hold-up time</b>	5ms at 115 Vac input
	<b>Connector</b>	<b>Output current limit</b>	<5.0A
	<b>Environmental Design</b>	USB Type-C™	
		<b>Operating temperature</b>	32°F to 95°F (0°to 35°C)
		<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20°to 85°C)
<b>Altitude</b>		0 to 16,400 ft (0 to 5000m)	
<b>Safety Certifications</b>	<b>Humidity</b>	20% to 95%	
	<b>Storage Humidity</b>	10% to 95%	
	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. MTBF - over 200,000 hours at 25°C ambient condition.		

### Technical Specifications

<b>HP 45W Smart AC adapter</b>	<b>Dimensions</b>	62.0x62.0x28.5mm	
	<b>Weight</b>	unit: 220g +/- 10g	
	<b>Input</b>	<b>Input Efficiency</b>	87.74% at 115Vac and 88.4% at 230Vac
		<b>Input frequency range</b>	47 to 63 Hz
		<b>Input AC current</b>	1.4 A at 90 VAC
	<b>Output</b>	<b>Output power</b>	45W
		<b>DC output</b>	19.5V
		<b>Hold-up time</b>	5 ms at 115 VAC input
		<b>Output current limit</b>	<8.0A
	<b>Connector</b>	4.5mm Barrel Type, 3 pin/grounded, mates with interchangeable cords	
	<b>Environmental Design</b>	<b>Operating temperature</b>	32° to 95° F (0° to 35° C)
		<b>Non-operating (storage) temperature</b>	-4° to 185° F (-20° to 85° C)
		<b>Altitude</b>	0 to 16,400 ft (0 to 5,000 m)
<b>Humidity</b>		20% to 95%	
<b>Safety Certifications</b>	<b>Storage Humidity</b>	10% to 95%	
	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. MTBF - over 200,000 hours at 25°C ambient condition.		

<b>HP 65W Smart AC adapter</b>	<b>Dimensions</b>	107.0x47.0x30.0mm	
	<b>Weight</b>	unit: 250g +/- 10g	
	<b>Input</b>	<b>Input Efficiency</b>	88.0 % at 115 Vac and 89.0 % at 230Vac
		<b>Input frequency range</b>	47 ~ 63 Hz
		<b>Input AC current</b>	Max. 1.7 A at 90 Vac
	<b>Output</b>	<b>Output power</b>	65W
		<b>DC output</b>	19.5V
		<b>Hold-up time</b>	5ms at 115 Vac input
		<b>Output current limit</b>	<11.0A
	<b>Connector</b>	4.5mm Barrel Type	
	<b>Environmental Design</b>	<b>Operating temperature</b>	32° to 95° F (0° to 35° C)
		<b>Non-operating (storage) temperature</b>	-4° to 185° F (-20° to 85° C)
		<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
<b>Humidity</b>		20% to 95%	
<b>Safety Certifications</b>	<b>Storage Humidity</b>	10% to 95%	
	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. MTBF - over 200,000 hours at 25°C ambient condition.		



### Technical Specifications

<b>HP 65W EM Smart AC adapter</b>	<b>Dimensions</b>	102x55x30mm	
	<b>Weight</b>	270g +/- 10g	
	<b>Input</b>	<b>Input Efficiency</b>	87% min at 115V/230V
		<b>Input frequency range</b>	47 to 63 Hz
		<b>Input AC current</b>	1.7 A at 90 VAC and maximum load
	<b>Output</b>	<b>Output power</b>	
		<b>DC output</b>	65W(19.5V/3.33A)
		<b>Hold-up time</b>	5 ms at 115 VAC input
		<b>Output current limit</b>	<11A, Over voltage protection- 29V max automatic shutdown
		<b>Connector</b>	4.5mm Barrel Type, 3 pin/grounded, mates with interchangeable cords
	<b>Environmental Design</b>	<b>Operating temperature</b>	0° to 35° C
		<b>Non-operating (storage) temperature</b>	-20° to 85° C
		<b>Altitude</b>	0 to 5,000 m
		<b>Humidity</b>	0% to 95%
<b>Storage Humidity</b>		0% to 95%	
<b>Safety Certifications</b>	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. MTBF - over 200,000 hours at 25°C ambient condition.		

<b>HP 65W Watt Smart Travel Adapter</b>	<b>Dimensions</b>	120.0x57.6x16.7mm	
	<b>Weight</b>	unit: 250g +/- 10g	
	<b>Input</b>	<b>Input Efficiency</b>	88.0 % at 115 Vac and 89.0 % at 230Vac
		<b>Input frequency range</b>	47 ~ 63 Hz
		<b>Input AC current</b>	Max. 1.7 A at 90 Vac
	<b>Output</b>	<b>Output power</b>	65W
		<b>DC output</b>	19.5V/5V
		<b>Hold-up time</b>	5ms at 115 Vac input
		<b>Output current limit</b>	<11.0A
		<b>Connector</b>	4.5mm/7.4mm tips
	<b>Environmental Design</b>	<b>Operating temperature</b>	32°F to 95°F (0°to 35°C)
		<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20°to 85°C)
		<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
		<b>Humidity</b>	20% to 95%
<b>Storage Humidity</b>		10% to 95%	
<b>Safety Certifications</b>	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. MTBF - over 200,000 hours at 25°C ambient condition.		

### Technical Specifications

<b>Battery CD 3 Cell WHr 48 Long Life -PR+PL Fast Charge</b>	<b>Dimensions (H x W x L)</b>	8.05. x185.15x95 mm
	<b>Weight</b>	0.26 kg
	<b>Cells/Type</b>	3cell Lithium-Ion Polymer cell / 606072
	<b>Energy</b>	<b>Voltage</b> 11.4V
		<b>Amp-hour capacity</b> 4.212Ah /4.0Ah
		<b>Watt-hour capacity</b> 48Wh
	<b>Temperature</b>	<b>Operating (Charging)</b> 32° to 113° F (0° to 45° C)
		<b>Operating (Discharging)</b> 14° to 122° F (-10° to 60° C)
	<b>Fuel Gauge LED</b>	N/A
	<b>Warranty</b>	3 years <sup>6</sup>
<b>Optional Travel Battery Available</b>	No	

### COUNTRY OF ORIGIN

China

### Options and Accessories (sold separately and availability may vary by country)

Type	Description	Part #
<b>Cases</b>	HP 15.6 Business Top Load	2SC66AA
	HP Slim Top Load	F3W15AA
	HP Slim Backpack	F3W16AA
<b>Docking</b>	HP 2013 UltraSlim Docking Station	D9Y32AA
	HP USB-C Dock G4	3FF69AA
	HP USB-C Universal Dock	1MK33AA
<b>Input/Output</b>	HP Slim USB Keyboard and Mouse	T6T83AA
	HP Slim Wireless Keyboard and Mouse	T6L04AA
	HP Ultra Mobile Wireless Mouse	H6F25AA
	HP Comfort Grip Wireless Mouse	H2L63AA
	HP Wireless Premium Mouse	1JR31AA
	HP Slim Bluetooth Mouse	F3J92AA
	HP USB Premium Mouse	1JR32AA
	HP USB Travel Mouse	G1K28AA
	HP Elite Presenter Mouse	2CE30AA
	HP HDMI to DVI Adapter	F5A28AA
	HP HDMI to VGA	H4F02AA
	HP USB-C to DP	N9K78AA
	HP USB-C to USB-A Hub	Z6A00AA
	HP USB-C to VGA	N9K76AA
	HP Stereo 3.5mm Headset	T1A66AA
HP Stereo USB Headset	T1A67AA	
<b>Power</b>	HP 45W Smart AC Adapter	H6Y88AA
	HP 65W Smart AC Adapter	H6Y89AA
	HP 45W USB-C Power Adapter	1HE07AA
	HP 65W USB-C Power Adapter	1HE08AA
	HP USB-C Notebook Power Bank	2NA10AA
<b>Storage</b>	HP External USB Optical Drive	F2B56AA
	HP 128GB TLC M.2 SATA-3	2JB95AA
	HP 256GB TLC PCIe 3x4 NVMe M.2 SSD	1FU87AA
	HP 512GB TLC PCIe 3x4 NVMe M.2 SSD	1FU88AA
<b>Security</b>	HP Docking Station Cable Lock	AU656AA#XXX
	HP 14.0" Notebook Privacy Filter	J6E65AA
	HP Keyed Cable Lock 10mm	T1A62AA

### Options and Accessories (sold separately and availability may vary by country)

<b>Memory</b>	HP 4GB DDR4 Memory	Z4Y84AA
	HP 8GB DDR4 Memory	Z4Y85AA
	HP 16GB DDR4 Memory	Z4Y86AA
<b>UCC</b>	HP Wireless Collaboration Keyboard	Z9N39AA
	HP USB Collaboration Keyboard	Z9N38AA
	HP UC Speaker Phone	K7V16AA
	HP UC Wireless Mono Headset	W3K08AA
	HP UC Wireless Duo Headset	W3K09AA
<b>Displays</b>	HP ProDisplay P223 21.5-inch Monitor	X7R61AA
	HP ProDisplay P240va 23.8-inch Monitor	N3H14AA
	HP EliteDisplay E243 23.8-inch Monitor	1FH47AA

---

## Summary of Changes

Date of change:	Version History:	Update	Description of change:
March 6, 2018	Pre V1	Changed	56 GB 2280 PCIe NVMe Value Solid State Drive capacity fixed to 256 GB
	V1 to V2	Added	Footnote number 1 to first bullet in At a glance section

Copyright © 2018 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Celeron, Intel vPro and Thunderbolt are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. AMD is a trademark of Advanced Micro Devices, Inc. USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum. microSD is a registered trademark of SD-3C in the United States, other countries or both. Qualcomm is a trademark of Qualcomm Incorporated, registered in the United States and other countries, used with permission. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. All other trademarks are the property of their respective owners.