



**Infinite
Peripherals®**

DPP-250

General Specifications

Mobilize Your Enterprise™

2" thermal mobile printer, battery operated.
Mag stripe reader and Bluetooth® options available.
Compact form factor.
Long-life battery (approx. 2.5 paper rolls).

**Headquarters/
Main Warehouse**
2312 Touhy Avenue
Elk Grove Village, IL 60007

Office (847) 818-1260
Fax (847) 818-1287
Toll-Free (800) 278-7860
Email info@ipcprint.com

**Mobility Sales/
Technical Support Center**
1641 McGaw Avenue
Irvine, CA 92614

Office (949) 222-0300
Fax (949) 222-0375
Toll-Free (866) 278-7860
Email info@ipcprint.com

Standard Features



Li-ion
Battery

Optional Features



Bluetooth®



ipcprint.com

©2014 Infinite Peripherals, Inc.

PRINTING SPECIFICATIONS

Printing Method	Line thermal dot printing
Printing Speed	60mms/s (480 dots/sec) at 8.5 V
Print Width	48mm / 384 dots per line
Resolution	203dpi (8x9 dots/mm)
Dot Pitch	Horizontal - 0.125 mm (8 dots/mm) Vertical - 0.125 mm (8 dots/mm)
Resident Fonts	Font A: 12 x 24 dots (32 char. per line) Font B: 9 x 16 dots (42 char. per line)
Loadable Fonts	Font C: 12 x 24 dots (32 char. per line) Font D: 9 x 16 dots (42 char. per line)
Logo Registration	1 black and white size: 384 x 248 dots
Input Buffer	128 KB (131072 bytes)
Resident Barcodes	1D - EAN13, EAN8, UPC-A, UPC-E, Codebar, Code39, Code128 2D - PDF417, QR Code
Communications	RS232 C - max. 115200 bps. USB v 1.1, compatible with 2.0 Bluetooth
Emulation	ESC/POS Continuous paper mode
Thermal Paper	58mm +0/-1mm X 45mm diameter, thickness 60 µm
Reliability	Printing head: 50km (printing rate 25% max)

ELECTRICAL

Power Supply	Rechargeable Li-ion battery (7.4 V / 1100 mAh) Battery capacity: per charge (~20,000 lines) AC adapter - DC 9 V, 1 A AC 100 - 240 V, 1.3 A, 50/60 Hz
Magnetic Stripe Reader	3 track unencrypted MSR head, ISO7811 (optional)

MECHANICAL

Dimensions	6mm (W) x 113mm (D) x 57mm (H)
Weight	295 grams (without paper) 350 grams (with paper)

ENVIRONMENT

Operating Environment	Operating temperature 0°C to +45°C 32°F to 113°F Operating humidity 35 to 85% RH Storage temperature -20°C to +60°C -4°F to 140°F Storage humidity 10 to 90% RH
------------------------------	--

COMPATIBILITY

iOS Support	iOS6 and higher
Android™ Support	Android OS 2.1 and higher

Specifications subject to change without notice.
Android is a trademark of Google Inc.
The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc.

COMPATIBLE WITH

Infinea Tab® 4



Infinea Tab® M



Linea Pro® 5