



## CSHT706TC Home Theater Surge Protector

Offering vital surge protection for your home theater equipment from damaging electrical surges.

The CyberPower Home Theater Series CSHT706TC Surge Protector is ideal for home entertainment and Home Office protection with 1950 joules, 7 outlets, and a 6 ft. cord. The surge protector provides protection for HDTVs, cable/satellite receivers, personal computers, cable modems, phones/fax/DSL, printers, stereos, and CD/DVD players.

The CSHT706TC features seven (7) outlets with one (1) widely spaced outlet, MOV technology to guard the surge protector and connected electronics against line abnormalities and lightning surges, while EMI/RFI filters block unwanted line noise. Data line protection is provided for networking and telecommunication devices.

A Limited Lifetime Warranty ensures that this surge protector has passed our highest quality standards in design, assembly, material or workmanship and further protection is offered by a \$150,000 Connected Equipment Guarantee.

### Typical Applications

- HDTVs
- Cable/Satellite Receivers
- Desktop Computers
- Personal Electronics

### Features

- 7 Surge Protected Outlets
- 1950 Joules of Surge Protection
- DSL / Phone / Fax Protection – RJ11
- Cable / Satellite Protection – RG6
- 15A Circuit Breaker
- 6 ft. Cord
- EMI/RFI Noise Filters
- Lifetime Warranty

# CSHT706TC Home Theater Surge Protector

Offering vital surge protection for your home theater equipment from damaging electrical surges.

GENERAL	
Product Type	Surge Protector
INPUT	
Voltage	125V
Rotating Power Cord	None
Switch	Non Lighted On/Off - Reset
Circuit Breaker	15 Amp
Plug Type	NEMA 5-15P
Plug Style	Right Angle - 45° Offset
Cord Length	6'
OUTPUT	
Outlets - Total	7
Outlet Type	NEMA 5-15R
Outlets - Energy Saving	0
Outlets - Widely Spaced	1
SURGE PROTECTION & FILTERING	
Surge Suppression	1,950 Joules
Maximum Surge Current	90,000 Amps
Maximum Surge Current H-N	30,000 Amps
Maximum Surge Current H-G	30,000 Amps
Maximum Surge Current N-G	30,000 Amps
Clamping Voltage	400V (L-N, L-G, N-G)
Response Time	< 1 nanosecond
Phone Protection RJ11	1-In, 2-Out
Network Protection RJ45	None
Coaxial Protection RG6	1 Pair
EMI/RFI Filtration	150 kHz to 100 MHz
Attenuation	Up to 43dB
INDICATORS	
Indicators	Protected (Green), Grounded (Green)
PHYSICAL	
Keyhole Mounting Slots	No
Cord Management	Yes
Safety Covers	Yes
CERTIFICATIONS	
Safety	UL1363 / UL1449 3rd Edition, cUL
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	Limited Lifetime
Connected Equipment Guarantee	Lifetime
CEG Amount	\$150,000