

ADJDINKIT

Adjustable Rack Mount DIN Rail Kit with Top Hat/Mini/G Rails

Installation Guide

Packaging Contents

- 1 x Rack Mount DIN rail frame
- 1 x Adjustable DIN rail mount with Top Hat DIN rail
- 1 x Mini Top Hat DIN rail
- 1 x G-type DIN rail
- 2 x Carriage Bolt
- 2 x Nut
- 4 x Plastic Washer
- 2 x M5 Screw
- 2 x M5 Nut
- 1 x Installation Guide

Installation

1. Determine the necessary depth for the DIN rails and slide the adjustable DIN rail mount into the rackmount frame from the front.
2. Insert the two bolts with washers into the sides of the frame and through the openings in the adjustable DIN mount.
3. Use the nuts with washers to fasten the bolts from the inside of the frame.
4. The adjustable DIN rail mount comes preinstalled with the Top Hat DIN rail. To switch to one of the other DIN rail styles, remove the two screws that hold the DIN rail to the adjustable mount, replace the rail, and reattach the screws.
5. Mount the completed DIN rail kit into the rack/cabinet and secure to the mounting posts using the appropriate mounting hardware.

NOTE: M5 screws and nuts are provided for compatible racks/cabinets. Alternative mounting hardware should be obtained from the rack/cabinet manufacturer.

6. Mount the DIN rail compatible devices.

Warranty Information

This product is backed by a lifetime warranty.

In addition, StarTech.com warrants its products against defects in materials and workmanship for the periods noted, following the initial date of purchase. During this period, the products may be returned for repair, or replacement with equivalent products at our discretion. The warranty covers parts and labor costs only. StarTech.com does not warrant its products from defects or damages arising from misuse, abuse, alteration, or normal wear and tear.

Limitation of Liability

In no event shall the liability of StarTech.com Ltd. and StarTech.com USA LLP (or their officers, directors, employees or agents) for any damages (whether direct or indirect, special, punitive, incidental, consequential, or otherwise), loss of profits, loss of business, or any pecuniary loss, arising out of or related to the use of the product exceed the actual price paid for the product. Some states do not allow the exclusion or limitation of incidental or consequential damages. If such laws apply, the limitations or exclusions contained in this statement may not apply to you.

System Requirements

- EIA-310D compliant rack/cabinet
- Top Hat, Mini, or G-type DIN mountable equipment

Specifications

Material	SPCC (1.6mm frame/1.0mm rails)
Colour	Black
Mounting Height	2U
External Dimensions (WxHxD)	482.6mm x 88.9mm x 358.4mm
Net Weight	1720g
Standards	EIA-310D
Certifications	RoHS

