

Data Sheet

FUJITSU Display XL55-1 TOUCH

Multi-touch 139 cm (55 inch) Display for Enhanced Collaboration in Meeting Rooms

The FUJITSU Display XL55-1 TOUCH is a Full HD display with an interactive panel that supports up to 10 touch points for maximum collaboration during meetings. The display has powerful built-in speakers, a range of interfaces for easy connectivity and maximum flexibility and anti-glare screen for a distraction free viewing experience.

55-inch FHD multi-touch display ideal for meeting rooms and collaboration spaces in your office

VESA compatible interface for mounting display on walls or securing it on trolley stands for greater flexibility

Powerful 10W built-in stereo speakers for showcasing videos and multimedia presentations

Anti-glare screen with 8H hardness coating and protection glass ensures superb and consistent viewing experience while collaborating

In-Plane Switching (IPS) technology with wide viewing angle that delivers consistent clarity from any perspective

Compatible with ESPRIMO Q956/MRE Meeting Room Edition PC that can wirelessly connect employees from any location and back-pack support for ESPRIMO Q PC



Technical details

Special features

10 Finger IR Touch Technology, IR Remote Control, In-Plane Switching (IPS) technology, Integrated speakers, LED backlight panel, Backpack mount for ESPRIMO Q

Picture performance

Panel and backlit	In-Plane Switching (IPS) technology/LED
Multi-Touch Support	10-fingers Win 7/ 8.x/10 touch
Screen Surface Treatment	8H hard coating, Protection Glass, Anti-glare
Contrast - typical	1100:1
Response time gray to gray typical	12 ms
Viewing angle (h/v) - typical	178°/178° CR10:1
Color performance	16.7 million colors (8-bit)
Brightness - typical	450 cd/m ²
Aspect ratio	16:9
Diagonal Size	139 cm (55 inch)
Resolution (native)	1,920 x 1,080 pixel
Resolution (interpolated)	1,680 x 1,050 pixel, 1,400 x 900 pixel, 1,280 x 1,024 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 720 x 400 pixel, 640 x 480 pixel
Picture size	1209.6 x 680.4 mm
Pixel Pitch	0.630 mm

Frequencies

Horizontal	31.5 kHz - 91 kHz
Vertical	56 Hz - 85 Hz
Frequencies - bandwidth	165 MHz

Connectivity

DisplayPort	1 x DisplayPort 1.2
HDMI	2 x HDMI 1.4
DVI	1 x DVI-I
Audio signal output	3.5 mm stereo phone jack for head phone
Audio signal input	3.5 mm stereo phone jack
Audio sound output	2 x 10 W
USB upstream	1x USB 2.0 for Touch function

Ease-of-use menu

Notes	Complete OSD functions see User Manual
Direct Access Keys	Input, Audio, Menu
Languages	Dutch, English, Finnish, French, German, Italian, Polish, Swedish, Spanish, Russian
Brightness / Contrast	Brightness, Contrast, Black level, Gamma
Mode	Standard, sRGB, High Bright, Cinema
Color	3000K, 4000K, 5000K, 6500K, 7500K, 9300K, 10000K, Native, User
Image adjust	Sharpness, Expansion, H/V Position, Clock, Phase
Audio	Bass, Mute, Treble, Volume, Balance
Information	Model name, Serial number
Picture in Picture (PIP)	Mode, Input, Position

Power consumption (typical)

Soft switch off	0.45 W
Hard switch off	0.0 W
Power save mode	0.5 W
Operating with EPA settings	65 W
Operating maximum brightness	139 W
Power supply	integrated

Power notes	Speakers off, USB not connected ETEC and EPA refer to ENERGY STAR® 7.0
Electrical values	
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Compliance	
Europe	Energy Efficiency Class: B, CE Class A*, EN 60950, RoHS, WEEE, IT-Eco-Declaration
USA/Canada	FCC Class A, cTUVus
Global	ENERGY STAR® 7.0, ISO9241-307 (Pixel fault class II)
Compliance notes	* Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Dimensions / Weight / Environmental	
Dimension without stand (W x D x H)	1271 x 64 x 742 mm 50.04 x 2.52 x 29.21 inch
Dimension notes	Depth with handle 91.4 mm / 3.6 inch
Weight (packed)	40 kg 88 lbs
Weight (Monitor only)	31 kg 68.34 lbs
Operating ambient temperature	5 - 35 °C
Operating relative humidity	20 - 80 % (non condensing)
Miscellaneous	
Miscellaneous	VESA DDC/ CI, VESA Flat Display Mounting Interface MIS-F 400mm M6
Color	Matt black
Package content	
Display delivered accessories	Power cable for wall socket (2-pin IEC-320-C7) 3.0m USB-cable 1.8 m (USB-A to USB-B) DisplayPort data cable 1.8 m HDMI cable 3.0 m Quickstart flyer Safety notes
Display delivered accessories notes	Wall mount or trolley stand is necessary to install the display Data cables and USB cable detachable on display User manual and DisplayView Software is available via download
SAP order name	
Order Code	S26361-K1632-V160
EAN Code	4057185863643
Accessories information	Further helpful options: Available Adapters: http://global.sp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf
Warranty	
Warranty period	3 years (depending on country)
Warranty type	X - Collect & Return Service (depending on country specific requirements)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Service Weblink	http://www.fujitsu.com/fts/services/support

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU Display XL55-1 TOUCH, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Display XL55-1 TOUCH, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://www.fujitsu.com/fts/displays>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2017 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com/fts
2017-09-21 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2017 Fujitsu Technology Solutions GmbH