

Includes an ADSL2+ Modem 802.11n Wireless Router & an 802.11n 2.0 USB Adapter



ADSL2+ MODEM ROUTER WIRELESS N STARTER KIT

HIGH-SPEED ADSL2+ INTERNET CONNECTION

Latest ADSL2+ standard provides Internet transmission of up to 24Mbps downstream, 1Mbps upstream



TOTAL SECURITY & QoS

Firewall protection from Internet attacks, user access control, WPA/WPA2 wireless security and priority queues for smooth VoIP traffic/streaming multimedia



TOTAL WIRELESS PERFORMANCE

Embedded latest draft 802.11n technology for high-speed wireless connection, complete compatibility with 802.11b/g wireless devices



ULTIMATE INTERNET CONNECTION

The D-Link ADSL2+ Modem Router Wireless N Starter Kit includes an ADSL2+ Modem draft 802.11n Wireless Router and a draft 802.11n Wireless USB 2.0 Adapter. This kit delivers ADSL download speed of up to 24Mbps and wireless network transfer rate of up to 270Mbps for very fast Internet and wireless connection that a home or small office needs to establish a secure, fast remote link to the outside world.

ULTIMATE WIRELESS CONNECTION

The D-Link ADSL2+ Modem Router Wireless N Starter Kit provides wireless speeds that are many times faster than 802.11g. Maximize wireless performance and stay connected from virtually anywhere at home and in the office. This wireless LAN supports WPA/WPA2 and WEP for flexible user access security and data encryption methods.

FIREWALL PROTECTION & QoS

Security features prevents unauthorized access to the home and office network, be it from the wireless devices or from the Internet. The D-Link ADSL2+ Modem Wireless Router provides firewall security, such as Stateful Packet Inspection (SPI) and hacker attack logging. SPI inspects the contents of incoming packets before they are allowed in, while hacker logging helps to protect your network against Denial of Service (DoS) attacks. For Quality of Service (QoS), the router supports priority queues to enable a group of home or office users to experience the benefit of smooth network connection of inbound and outbound data without concern of traffic congestion.

COMPATIBILITY ASSURANCE

The D-Link ADSL2+ Modem Router Wireless N Starter Kit is backward compatible with existing 802.11b and 802.11g wireless equipment, ensuring compatibility with a wide range of wireless devices. In addition, its router includes four Ethernet ports ready for you to connect Ethernet-enabled PC, print server and other devices.

WHAT THIS PRODUCT DOES

Share your broadband Internet connection with multiple computers in your house by simply connecting the Wireless ADSL2+ Modem Router to your phone line and plugging in the wireless USB 2.0 Adapter to your laptop or desktop PC. Once connected, you can create a high-performance wireless network to share Internet access, documents, photos, video, music and streaming media. Four LAN ports on the Wireless ADSL2+ Modem Router let four additional computers and Ethernet devices hook up to the Internet through the network cables.

ADVANCED WIRELESS FUNCTIONS

The D-Link Wireless N Starter Kit includes everything you need to get a wireless network up and running.

- + Includes 802.11n draft Wireless ADSL2+ Modem Router and 802.11n Wireless USB 2.0 Adapter for notebook/desktop PC

- + Share your wireless Internet connection

- + ADSL2+ standard, up to 24Mbps downstream, 1Mbps upstream

- + 802.11n (draft), 802.11g and 802.11b standards

- + Wireless data rate of up to 270Mbps¹

- + Secure Wireless Encryption Using WPA, WPA2 or WEP

- + Built-in NAT and SPI Firewall

- + Integrated 4-port 10/100Mbps switch

- + Supports UPnP, DDNS, 802.11e WLAN Quality of Service (QoS)



TECHNICAL SPECIFICATIONS

MINIMUM SYSTEM REQUIREMENTS

- + ADSL Internet service
- + Computer with:
 - 200MHz Processor
 - 64MB Memory
 - CD-ROM Drive
 - Ethernet Adapter with TCP/IP Protocol Installed
 - Windows XP/2000/4
 - Internet Explorer v6 or later, FireFox v1.5
 - 20MB Hard Disk Space
 - Available USB Port
- + D-Link Click'n Connect Utility
- Computer with Windows 2000/XP

STANDARDS

- + ADSL standards: Multi-mode, ANSI T1.413 Issue 2, ITU G.992.1 (G.dmt) Annex A, ITU G.992.2 (G.lite) Annex A, ITU G.994.1 (G.hs)
- + ADSL2 standards: ITU G.992.3 (G.dmt.bis) Annex A/L/M, ITU G.992.4 (G.lite.bis) Annex A
- + ADSL2+ standards: ITU G.992.5 Annex A/L/M
- + IEEE 802.11n (draft) + IEEE 802.11g
- + IEEE 802.11b + IEEE 802.3
- + IEEE 802.3u + USB 2.0

DEVICE INTERFACES

- DSL-2740B:
 - + 1 RJ-11 ADSL port
 - + 4 10/100BASE-TX Ethernet LAN ports
 - + Draft 802.11n wireless LAN
 - + Factory default reset button
- DWA-140:
 - + Draft 802.11n wireless LAN
 - + USB 2.0 port

ADSL DATA RATES

- + G.dmt: 8Mbps downstream, 832Kbps upstream
- + G.lite: 1.5Mbps downstream, 512Kbps upstream
- + ADSL2: 12Mbps downstream, 1Mbps upstream
- + ADSL2+: 24Mbps downstream, 1Mbps upstream

ATM & PPP PROTOCOLS

- + ATM Forum UNI3.1/4.0 PVC (up to 16PVCs)
- + ATM Adaptation Layer Type 5 (AAL5)
- + ATM QoS (Traffic Shaping)
- + Bridged or routed Ethernet encapsulation
- + VC and LLC based multiplexing
- + PPP over Ethernet (PPPoE)
- + PPP over ATM (RFC 2364)
- + ITU-T I.610 OAM F4/F5

WIRELESS DATA RATES¹

- + 802.11b: 1/2/5.5/11Mbps
- + 802.11g: 6/9/12/18/24/36/48/54Mbps
- + 802.11n: 30/60/90/120/180/240/270Mbps

WIRELESS FREQUENCY RANGE

- + 2412 to 2462MHz (North America)
- + 2412 to 2472MHz (General Europe)

WIRELESS EMISSION SCHEMES

- + DSSS, OFDM

WIRELESS DATA MODULATION SCHEMES

- + DBPSK, DQPSK, CCK and OFDM (BPSK/QPSK/16-QAM/64-QAM)

WIRELESS TRANSMIT POWER²

- + DSL-2740B: 17dBm +/- 2dBm
- + DWA-140: 14dBm +/- 2dBm

ANTENNAS

- + DSL-2740B: 3 detachable dipole antennas with reverse SMA plugs
- + DWA-140: integrated internal antenna

INTERNET/FIREWALL PROTECTION

- + Built-in NAT firewall
- + Stateful Packet Inspection (SPI)
- + DoS attacks prevention
- + Packet filtering (IP/ICMP/TCP/UDP)
- + Intrusion Detection System (IDS)
- + DMZ
- + URL filtering/domain blocking/scheduling parental control

OTHER SECURITY

- + 64/128-bit WEP data encryption (wireless LAN)
- + Wi-Fi Protected Access (WPA, WPA2) (wireless LAN)
- + Multiple SSID (wireless LAN)
- + MAC address-based access control (wireless LAN)
- + MAC/IP address filtering user access control (wired LAN)
- + IGMP Snooping with 32 Multicast groups
- + PVC/VLAN port mapping (bridge mode)

ROUTER FEATURES

- + NAT (maximum 1024 NAT sessions)
- + DHCP server/client/relay
- + Static Routing, RIP v.1, v.2
- + Universal Plug and Play (UPnP) Compliant
- + Dynamic Domain Name System (DDNS)
- + Virtual Server
- + SNTP, DNS proxy and IGMP proxy

VIRTUAL PRIVATE NETWORK (VPN)

- + Multiple PPTP/PSec/L2TP pass-through

QUALITY OF SERVICE

- + LAN to WAN traffic prioritization/Classification
- + 802.1p (0 to 7) traffic prioritization
- + Traffic Shaping
- + 802.11e Wireless QoS (WMM/WME)

DEVICE CONFIGURATION/MANAGEMENT^{*}

- + Installation Wizard
- + Web-based GUI for configuration, firmware upgrade

- + Code lock to prevent improper firmware upgrade
- + Telnet with SSH support
- + Syslog monitoring
- + SNMP v1, v2c support with built-in MIB-II (RFC 1213)
- + TR-069 Client
- * DSL-2740B only

Power Input

- + DSL-2740B: through 12VAC 1.5A external power adapter
- + DWA-140: USB bus power, no external power adapter required

POWER CONSUMPTION

- + DSL-2740B: Transmission: 750mA (max), Reception: 700mA (max)
- + DWA-140: Transmission: 460mA, Reception: 240mA

DIAGNOSTIC LEDs

- DSL-2740B:
 - + Power + LAN (1 to 4)
 - + WLAN + DSL
 - + Internet
- DWA-140:
 - + Activity

DIMENSIONS

- + DSL-2740B: 220 x 150 x 32 mm (8.66 x 5.90 x 1.26 inches)
- + DWA-140: 87 x 128 x 12 mm (3.43 x 5.04 x 0.47 inches)

WEIGHT

- + DSL-2740B: 474 grams (1.05 lb)
- + DWA-140: 18.9 grams (0.04 lb)

OPERATING TEMPERATURE

- 0° to 40° C (32° to 104° F)

STORAGE TEMPERATURE

- + DSL-2740B: -20° to 70° C (-4° to 158° F)
- + DWA-140: -20° to 65° C (-4° to 149° F)

OPERATING HUMIDITY

- 10% to 90% non-condensing

OPERATING HUMIDITY

- 10% to 90% non-condensing

OPERATING HUMIDITY

- 10% to 90% non-condensing

CERTIFICATION

- + FCC Class B * + CE
- + C-Tick * + IC *

* DWA-140 only

¹ Maximum wireless signal rate based on IEEE 802.11g standard and 802.11n draft specifications. Actual data throughput will vary. Network conditions and environmental factors, including volume of network traffic, building materials and construction and network overhead may lower actual data throughput rate and adversely affect the range.
² Typical transmit power; transmit power setting varies according to countries.

The devices described herein are in compliance with the essential requirements and other relevant provisions of Directive 1999/5/EC.

Product specifications, size and shape are subject to change without notice, and actual product appearance may differ from that depicted on the packaging.

D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries. All other trademarks are the property of their respective owners. Copyright 2007. All rights reserved.



D-Link Worldwide Offices

U.S.A	TEL: 1-800-326-1688	FAX: 1-866-743-4905	Spain	TEL: 34 93 409 0770	FAX: 34 93 491 0795	Pakistan	TEL: 92-21-454-8158	FAX: 92-21-453-6103
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223	Portugal	TEL: 351 21 9688493	FAX: 30 210 9914 512	Israel	TEL: 972-9-9715700	FAX: 972-9-9715601
Europe, UK & Ireland	TEL: 44-20-8955-9000	FAX: 44-20-8955-9002	Greece	TEL: 30 210 9914 512	FAX: 30 210 9916902	Latin America	TEL: 56-2-5638-950	FAX: 56-2-5638953
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300	Czech Republic	TEL: 420 224 247 500		Brazil	TEL: 55-11-2185-3300	FAX: 55-11-2185-3322
France	TEL: 33 1 30 23 86 88	FAX: 33 1 30 23 86 89	Hungary	TEL: 36 (0) 1 461 30 00	FAX: 36 (0) 1 461 30 09	South Africa	TEL: 27-12-665-2165	FAX: 27-12-665-2186
Netherlands	TEL: 31-10-282-1445	FAX: 31-10-282-1331	Poland	TEL: 48 (0) 22 583 92 7	FAX: 48 (0) 22 583 92 76	Russia	TEL: 7-495-744-0099	FAX: 7-495-744-0099
Belgium & Luxembourg	TEL: 32(0)2 517 7111	FAX: 32(0)2 517 6500	Singapore	TEL: 65-6774-6233	FAX: 65-6774-63225	Japan	TEL: 81-3-5781-0963	FAX: 81-3-5781-0965
Switzerland	TEL: 41 (0) 1 832 11 00	FAX: 41 (0) 1 832 11 01	Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868	Korea	TEL: 82-2-890-5491	FAX: 82-2-890-549
Sweden	TEL: 46-018564-61900	FAX: 46-018564-61901	India	TEL: 91-22-2652 6696	FAX: 91-22-2652 8914	China	TEL: 86-10-58635800	FAX: 86-10-58635799
Denmark	TEL: 45-43-969040	FAX: 45-43-424347	Middle East (Dubai)	TEL: 971-4-391-6480	FAX: 971-4-390-8881	Taiwan	TEL: 886-2-6600-0123	FAX: 886-2-6600-3389
Norway	TEL: 47 99 300 100	FAX: 47 22 30 95 80	Egypt	TEL: 202-291-9035	FAX: 202-291-9051	Headquarters	TEL: 886-2-6600-0123	FAX: 886-2-6600-9988
Finland	TEL: 358-10 309 8840	FAX: 358-10 309 8841	Turkey	TEL: 90-212-289-5659	FAX: 90-212-289-7606			
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723	Iran	TEL: 90-212-289-5659	FAX: 90-212-289-7606			