

Overview

Models

HP X125 1G SFP LC LH70 Transceiver

JD063B

HP X125 1G SFP RJ45 T Transceiver

JD089B

Key features

- SFP form factor
 - 1G Ethernet transmission speed
 - Up to 70km transmissions on single mode fiber
 - 1550nm wavelength
 - MSA compliant
-

Product overview

HP transceivers are designed and rigorously tested to meet the needs of critical network deployments. This product is a small form-factor pluggable SFP Gigabit LH70 transceiver that provides a full duplex Gigabit solution up to 70km on a single-mode fiber. Use only genuine HP transceivers in HP networking equipment.

Warranty and support

- **1-year warranty:** with advance replacement and 30-calendar-day delivery (available in most countries)
- **Electronic and telephone support:** limited electronic and telephone support is available from HP; to reach our support centers, refer to www.hp.com/networking/contact-support; for details on the duration of support provided with your product purchase, refer to www.hp.com/networking/warrantysummary
- **Software releases:** to find software for your product, refer to www.hp.com/networking/support; for details on the software releases available with your product purchase, refer to www.hp.com/networking/warrantysummary



Technical Specifications

HP X125 1G SFP LC LH70 Transceiver (JD063B)	Ports	1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)	
	Connectivity	Connector type	LC
Physical characteristics	Wavelength	1550 nm	
	Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)	
	Full configuration weight	0.04 lb. (0.02 kg)	
Environment	Transceiver form factor	SFP	
	Operating temperature	32°F to 158°F (0°C to 70°C)	
	Operating relative humidity	0% to 85%	
	Nonoperating/Storage temperature	-40°F to 185°F (-40°C to 85°C)	
	Nonoperating/Storage relative humidity	0% to 85%	
Electrical characteristics	Altitude	up to 10,000 ft. (3 km)	
	Power consumption typical	0.8 W	
	Power consumption maximum	1.0 W	
Cabling	Cable type:	Single-mode fiber optic, complying with ITU-T G.652;	
	Maximum distance:	• 70km	
Services	Fiber type	Single Mode	
		Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	



Technical Specifications

HP X125 1G SFP RJ45 T Transceiver (JD089B) A small form factor pluggable (SFP) Gigabit 1000Base-T transceiver that provides a full duplex Gigabit solution up to 100m on a Cat-5+ cable.	Ports	1 RJ-45 1000BASE-T port (IEEE 802.3ab Type 1000BASE-T)	
	Connectivity	Connector type	RJ-45
	Physical characteristics	Dimensions	2.71 (d) x 0.54 (w) x 0.55 (h) in. (6.88 x 1.37 x 1.4 cm)
	Electrical characteristics	Full configuration weight	0.07 lb. (0.03 kg)
		Power consumption typical	0.8 W
		Power consumption maximum	1.0 W
	Cabling	Cable type:	1000BASE-T: Category 5 (5E or better recommended), 100 Ω differential 4-pair unshielded twisted pair (UTP) or shielded twisted pair (STP) balanced, complying with IEEE 802.3ab 1000BASE-T;
		Maximum distance:	<ul style="list-style-type: none">• 100m
	Services		Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

To learn more, visit www.hp.com/networking

© Copyright 2012 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

