



Epson C9200 Series

High performance A3 colour laser printer for business and graphic art needs

Add quality, versatility and value to your A3 printing with the Epson AcuLaser C9200 Series. Create superb prints in colour and black & white at up to 26 ppm and share high performance printing across a network.

Take your business printing to new levels with the Epson AcuLaser C9200 Series. Maximise speed and quality on everything from A4 office print outs to A3 rich colour graphics with Epson ASIC and Epson Resolution Improvement Technologies.

The ideal A3 colour laser: one of the highest print quality and colour accurate printers on the market thanks to Epson Resolution Improvement Technology

Speed without compromising quality: print up to 26 ppm with fast processing from Epson ASIC technology

Comprehensive connectivity: standard Ethernet 10/100 Base Tx, Hi-Speed USB, Parallel and optional Type B interfaces

Extensive language support: genuine Adobe® PostScript 3™, PCL6, PCL5C, PDF1.6 and ESC/Page as standard

Flexible paper handling: print on a range of media up to A3F, with a paper capacity from 350 to 1,850 sheets

Upgrade to suit your needs: with optional duplex* and up to 3 x 500 sheet paper cassette units**

Standard RAM: 256MB expandable to 768MB. Extra memory and advanced functions thanks to CompactFlash™ support

Handles jobs of any size: faster ripping and first page out with latest Epson technologies including MIT Memory management technology

- * Standard on the Epson AcuLaser C9200DN and Epson AcuLaser C9200D3TNC
- ** Standard on the Epson AcuLaser C9200D3TNC

Key benefits:

- Superb quality at high-speed, up to 26 ppm in colour and black & white
- Comprehensive connectivity and printer languages including genuine Adobe® PostScript 3
- Versatile paper handling on a range of media from 350 up to 1,850 sheets
- Preconfigured models include Epson AcuLaser C9200N,
 Epson AcuLaser C9200DN,
 Epson AcuLaser C9200DTN,
 Epson AcuLaser C9200D3TNC



Epson AcuLaser C9200 Series

Print features Resolution 2400RIT (Epson Resolution Improvement Technology) 26 ppm in A4 Mono and Colour, 13 ppm in A3 Mono and Colour Print speed

First page out A4 Colour: 11.4 seconds, Mono: 8.1 seconds

Warm up time 109 sec or less Maximum monthly volume 150,000 pages Controller specifications

600 Mhz Processor speed

Memory (standard/max) 256MB / 768MB

Genuine Adobe Postscript 3, PCL5c, PCL6, PDF1.6, ESC/Page-Color, Printer control language emulations

ESC/Page, FX, ESCP2, I239X

Resident typefaces Scalable: 84 ESC/Page, 95 PCL5c, 80 PCL6, 136 PS3

Bitmap: 7 ESC/Page, 5 PCL5c, 1 PCL6 Typeface: 10 ESC/P2, 8 FX, 8 I239X

Interfaces and connectivity

Ethernet interface (100Base-TX/10Base-T) Standard interfaces

USB 2.0HS interface

Parallel interface (IEEE 1284 compliant) Optional interfaces Type-B, CompactFlash interface

TCP/IP: LPR. FTP. IPP. PORT2501, PORT9100, WSD Network printing protocols

Microsoft Network: Net BIOS over TCP/IP, Net BIOS over NetBEUI

NetWare: Standby, NDS Print Server, Bindery Print Server, Remote Printer

AppleTalk

Network management protocols TCP/IP: SNMP, HTTP, TELNET, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SNTP, SSDP, ENPC, SLP, WSD, LLTD

Microsoft Network: Auto-IP, SSDP MS Network (NetBEUI): SNMP, ENPC

NetWare: SNMP AppleTalk: SNMP

LCD 22 digits x 5 lines Control panel

Media handling 350 sheets (250 sheet Standard Cassette, 100 sheet MP Tray) Standard paper input Maximum paper input 1850 sheets (250 sheet Standard Cassette, 100 sheet MP Tray,

3x500 sheet Optional Paper Cassette) Paper size

A3, A4, A5, B4, B5, Letter, HLT, Legal, B, GLG, GLT, EXE, F4, A3F, custom (width: 90-311.2 mm, length: 139.7-1200 mm), Envelopes (Monarch, Com #10,

DL, IB5, C5, C6), Transparency, Labels

Paper weight 64-256 a/m²

Optional paper handling Duplex Unit, 500 sheet paper cassette (up to 3 can be fittted)

Paper output 500 sheet Power requirements

Rated voltage/frequency/current AC 220-240 V: 50 Hz/60 Hz, Max: 8.0A

Power consumption Printing: 576Wh, Standby: 146Wh, Sleep: 11Wh, Off: 0Wh

System requirement and OS support

Hardware languages

PC: Ethernet, USB or Parallel Port, MAC: EtherTalk or USB Port System requirement Windows support Microsoft Windows 2000 / XP / Server 2003 / Microsoft Windows Vista /

XP x64 Edition / Server 2003 x64 Edition / Vista x64 Edition

Mac support Mac OS 10.3.9 and higher Linux/Unix/Citrix/SAP/Novell support For compatibility please refer to

http://www.business-solutions.epson.co.uk/Compatible.htm

Additional software

Drivers and manuals Printer Driver, Epson Status Monitor, Reference Guide Network Utilities. Network Guide

Software Dimensions and weight (WxDxH mm, Kg)

Epson AcuLaser C9200N: 823x608x477 mm, 49.5 Kg Hardware **Options**

C12C802502 500 sheet Paper Cassette Unit: 577x548x168 mm, 14.8 Kg

C12C802512 Duplex Unit: 100x440x336 mm, 2.8 Kg

C12C847202 Printer stand: 535x508x96 mm, 8.5 Kg

Environmental conditions

Operation: 10 to 35° C / Storage: 0 to 35 °C Temperature Humidity Operation: 15 to 85% RH / Storage: 10 to 80% RH Operating: 7.25B (A); Standby: 5.3 B (A) Sound power

Sound pressure Safety and regulations

Safety standards Low Voltage Directive 2006/95/EC EN60950-1, EN60825-1

GOST-R (IEC60950-1, IEC60825-1) EMC Directive 2004/108/EC, EN 55022 Class B, EN 55024, EN 61000-3-2, EMC/EMI

Operating: 52dB (A); Standby: 40dB (A)

EN 61000-3-3, GOST-R (CISPR 22) Warranty

Standard warranty 1 year on-site

Extension to 3 years (ECPGRP100) Optional warranty






















Telephone 0871 222 6702 (UK) 01 436 7742 (Republic of Ireland) enquiries@epson.co.uk etalk.epson-europe.com 0871 222 6740

Web:



Model configurations

C11CA15011BZ Epson AcuLaser C9200N

823 mm

Main model

Epson AcuLaser C9200DN C11CA15011BY

Main model + Duplex unit

Epson AcuLaser C9200DTN C11CA15011BX

. Main model + Duplex Unit + 500 sheet paper cassette unit

Epson AcuLaser C9200D3TNC C11CA15011BW

Main model + Duplex Unit + 3 x 500 sheet paper cassette unit + printer stand



Supplies	
Toner Cartridge (Yellow)	
14,000 pages*	C13S050474
Toner Cartridge (Magenta)	
14,000 pages*	C13S050475
Toner Cartridge (Cyan)	
14,000 pages*	C13S050476
Toner Cartridge (Black)	
21,000 pages*	C13S050477
Photoconductor Unit (Yellow)	
30,000 pages*	C13S051175
Photoconductor Unit (Magenta)	
30,000 pages*	C13S051176
Photoconductor Unit (Cyan)	
30,000 pages*	C13S051177
Photoconductor Unit (Black)	
50,000 pages*	C13S501178
Waste Toner Collector	



Options

21,000 pages*

500-Sheet Paper cassette unit C12C802502 Duplex unit C12C802512 Printer Stand C12C847202 128MB additional Memory 7012051 256MB additional Memory 7012079 512MB additional Memory 7104195

* Figures are approximate and are based on the number of A4 sheets printed at 5% coverage under conditions of continuous printing. Intermittent use may reduce page yield.



C13S050478