

DVI to USB-C Video Capture Device

Product ID: USBC2DVCAPRO



This DVI to USB-C video capture device records high-definition DVI video to your USB-C, USB-A or Thunderbolt 3 computer. With an aluminum enclosure, this device is built strong for fixed-location or on-the-go capture. It offers a separate 3.5 mm audio input for accompanying audio or voice-overs, and a DVI pass-through port for connecting a monitor to review the video as it's captured.

Capture HD video at 1080p 60fps

Record 1080p video at 60fps (frames per second), to save your content so it can be shared, stored, or edited. Capture from security equipment, control rooms, medical, or other industrial DVI devices, directly to your computer.

Easy video recording on Windows and Mac

The included software makes recording easy. Using a widely adopted codec, videos saved in StreamCatcher™ work with almost any video player and require no converting or editing.

Live stream on Windows

On Windows, you can live broadcast your video over the internet, using Twitch™ or other third-party video streaming platforms, with the included software.

DirectShow compatibility on Windows

With this capture device, you're not tied to the included software. You can record raw/lossless video using any third-party DirectShow™ compatible software, such as Open Broadcaster Software (OBS).

Capture video from HDMI®, VGA or DVI devices

This versatile DVI capture device works with HDMI to DVI and VGA to DVI adapters, so you can record video from an HDMI or VGA source.

The USBC2DVCAPRO is backed by a 2-year StarTech.com warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Record video for training and tutorial purposes from devices that output DVI
- Capture raw video using your preferred DirectShow compatible software
- Great for recording the output from your PC, server, or POS station, when creating software training and tutorial videos
- Add your own independent audio source for voice-over commentary

Features

- Includes a USB-A and USB-C cable for connection to any Mac or PC host
- Great picture quality with USB 3.0 bandwidth enabling you to capture 1080p video at 60fps
- Wide device playback support with universally encoded video files
- Raw/lossless video capture ensuring DirectShow™ compatibility on Windows devices
- Separate 3.5 mm audio input for added voice commentary or audio track
- Includes a DVI pass-through port for a monitor to watch your video as it is captured

Hardware	Warranty	2 Years																	
	Audio	Yes																	
	Chipset ID	Mstar - MST3363CNK-170																	
	Converter Type	Format Converter																	
	Industry Standards	MPEG4 (H.264)																	
Performance	Audio Specifications	2-channel stereo audio																	
	Maximum Analog Resolutions	1920 x 1080 60 FPS																	
	Maximum Digital Resolutions	1920 x 1080 60 FPS																	
	Supported Resolutions	1920 x 1080, 1280 x 720, 1024 x 768, 800 x 600																	
	Wide Screen Supported	Yes																	
Software	OS Compatibility	Windows® 7, 8, 8.1, 10 MacOS® 10.11 to 10.13																	
		<table border="1"> <thead> <tr> <th></th> <th>Windows</th> <th>macOS</th> </tr> </thead> <tbody> <tr> <td>AVI</td> <td>Video - H.264</td> <td>N/A</td> </tr> <tr> <td>MP4</td> <td>Video - H.264 Audio - aac</td> <td>Video - H.264 Audio - aac</td> </tr> <tr> <td>TS</td> <td>Video - H.264 Audio - aac</td> <td>MPEG TS Video: MPEG-1, MPEG-2-video Audio: MPEG Audio layer 1, 2</td> </tr> <tr> <td>FLV</td> <td>Video - H.264 Audio - aac</td> <td>N/A</td> </tr> <tr> <td>MPG</td> <td>N/A</td> <td>MPEG program stream MPEG-1, MPEG-2-video Audio: MPEG Audio layer 1, 2</td> </tr> </tbody> </table>		Windows	macOS	AVI	Video - H.264	N/A	MP4	Video - H.264 Audio - aac	Video - H.264 Audio - aac	TS	Video - H.264 Audio - aac	MPEG TS Video: MPEG-1, MPEG-2-video Audio: MPEG Audio layer 1, 2	FLV	Video - H.264 Audio - aac	N/A	MPG	N/A
	Windows	macOS																	
AVI	Video - H.264	N/A																	
MP4	Video - H.264 Audio - aac	Video - H.264 Audio - aac																	
TS	Video - H.264 Audio - aac	MPEG TS Video: MPEG-1, MPEG-2-video Audio: MPEG Audio layer 1, 2																	
FLV	Video - H.264 Audio - aac	N/A																	
MPG	N/A	MPEG program stream MPEG-1, MPEG-2-video Audio: MPEG Audio layer 1, 2																	
Special Notes / Requirements	Note	This video capture device requires a USB 3.0 port (or higher). The video capture device does not work with USB 2.0 ports (or lower).																	
Power	Power Source	USB-Powered																	
Environmental	Humidity	20% to 80% (non-condensing)																	

	Operating Temperature	0°C to 40°C (32°F to 104°F)
	Storage Temperature	-5°C to 40°C (23°F to 105°F)
Physical Characteristics	Product Height	1 in [24.3 mm]
	Product Length	3.6 in [92.2 mm]
	Product Weight	3.6 oz [102 g]
	Product Width	2.4 in [61.1 mm]
Packaging Information	Shipping (Package) Weight	1 lb [0.5 kg]
What's in the Box	Included in Package	1 - USB 3.0 capture device for DVI video
		1 - 6ft [2m] USB-C to USB-B Cable
		1 - 3.3 ft [1 m] USB-A to USB-B cable
		1 - 3.3 ft [1 m] DVI cable

Product appearance and specifications are subject to change without notice.