



CSP600WSURC5 | PROFESSIONAL SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The CyberPower CSP600WSURC5 is ideal for Home/Office protection with 900 joules, 6 swivel outlets, 2 USB charge ports (3.6 Amps shared), and a convenient wall-tap design. The CSP600WSURC5 has outlets that swivel 90 degrees left or right to make it easy to manage, organize, and assure cords are low profile - great for tight plug-in locations.

As a surge protector, the CSP600WSURC5 prevents damage to computers, phones, printers, and other electronics by diverting excess voltage during a power spike. Plus, it's all backed by a One-Year Limited Warranty and a \$75,000 Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Personal Computers

FEATURES

- Surge suppression: 900 J
- Volts: 125 V
- Plug type: NEMA 5-15P
- Outlet type: 6 NEMA 5-15R
- USB charge ports: 2 (3.6-Amp)
- USB charge type: 1 USB Type C / 1 USB Type A
- EMI/RFI Filtration: Yes
- Warranty: One-Year Limited
- Connected Equipment Guarantee: \$75,000



SPECIFICATIONS

INPUT	
Circuit Breaker	None
Cord Length	Wall-tap
Input Plug Type	NEMA 5-15P
Input Voltage	125 VAC
Maximum Input Current	15 A
Plug Style	Wall-tap

OUTPUT	
Outlet Type	6 - NEMA 5-15R
Outlets - Total	6
USB Charge Port	Yes
USB Charge Port Amperage	3.6 A (Shared)
USB Charge Port Quantity	2
USB Charge Port Type	1 Type A 1 Type C
USB Charge Port Voltage	5 VDC
USB Charge Port Watts	18 W

CSP600WSURC5

PROFESSIONAL SURGE PROTECTOR

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING

Attenuation	32 dB
Clamping Voltage	500V (H-N, H-G, N-G)
Coax Protection RG6	None
EMI/RFI Filtration	Yes
Maximum Surge Current	45,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	15,000 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	900 J

PHYSICAL

Color	White
Form Factors Supported	Direct Plug
Material of Construction	Plastic

PHYSICAL DIMENSIONS

Physical Dimensions - WxHxD (cm)	10.16 x 17.46 x 3.49 cm
Physical Dimensions - WxHxD (mm)	102 x 175 x 35 mm
Physical Dimensions - WxHxD (in.)	4 x 6.875 x 1.375 in.
Weight (kg)	0.33 kg
Weight (lb)	0.72 lbs.

SHIPPING DIMENSIONS

Shipping Dimensions - WxHxD (cm)	10.8 x 6.35 x 19.69 cm
Shipping Dimensions - WxHxD (mm)	107.95 x 63.5 x 196.85 mm
Shipping Dimensions - WxHxD (in)	4.25 x 2.5 x 7.75 in.
Weight (kg)	0.44 kg
Weight (lb)	0.97 lbs.

CERTIFICATIONS

Environmental	RoHS Compliant
Safety	UL498a UL1310 UL1449 FCC DOE VI

WARRANTY

CEG Amount	\$75,000
Connected Equipment Guarantee	Lifetime
Product Warranty	One-Year Limited Warranty