

H190X

Big screen entertainment, bright HD ready projector





- Lights on viewing 3,900 ANSI lumens
- Easy connectivity HDMI, VGA, USB Power
- Clear, powerful audio 10W speaker
- Lightweight and portable

Project stunning images at any time of the day with the bright, 3,900 lumens, HD compatible, Optoma H190X. Feel the action and experience every moment on the big screen for immersive live sports, gaming and movies.



Specifications

Net weight	6.61 lbs
Gross weight	9.7 lbs
Dimensions (W x D x H) Gross weight	12.44" x 9.61" x 4.25"
Weight and dimensions	
Power consumption (max)	225W
Power consumption (min)	187W
(standby)	10718/
Power consumption	0.5W
Power supply	100 ~ 240V, 50 ~ 60Hz
Power	
Optional wireless models	WHD200
	Basic user manual
	Battery
In the box	AC power cord Remote control
Watts per speaker	10W
Speaker count	1
Remote control	Card style
Domoto control	humidity 85%
Operating conditions	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max
	Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
	Italian, Japanese, Norwegian, Polish, Portuguese, Romanian,
	Finnish, French, German, Greek, Hungarian, Indonesian,
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,
Security	Security bar, Kensington Lock, Password protected interface
3D	Full 3D
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
	576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
	4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p,
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N,
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Noise level (max)	29dB
Noise level (typical)	27dB
General	
	Control 1 x RS232
	Outputs 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1A
Connections	Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm
Connectivity Connections	
Connectivity	11670
Native offset	112%
Focal length (mm)	21.85 mm~24mm/0.86"~0.945"
Zoom type	Manual
Zoom	1.1
Projection distance	39.37" - 472.44"
Throw ratio	1.55:1 ~ 1.73:1
Optical	
Lamp life hours (up to)	6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)
Lamp watts	203
Light source type	Lamp
Lamp info	02.27 - 200.00 ulayonar
Screen size	75% 32.24" ~ 299.53" diagonal
Vertical scan rate Uniformity	50 ~ 85(120 for 3D)Hz 75%
Horizontal scan rate	15.38 ~ 91.15Khz
vertical	
Keystone correction -	+/-40°
Aspect ratio - compatible	4:3,16:9
Native aspect ratio	16:10
Contrast ratio	30,000:1
Brightness	3,900 lumens
Resolution	WXGA (1280x800)
Display technology	DLP





Copyright © 2021 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments™. All other trademarks are the property of their respective owners. All specifications subject to change at any time. 06022021032722