

SP5500 OptimusS

Mobile Computer

Honeywell's SP5500 OptimusS™ is a compact portable data terminal designed for retail and light warehouse data collection applications, including inventory, stocking, order-picking and shipping/receiving.

The SP5535 OptimusSBT™ incorporates Bluetooth® connectivity for real-time data transfer and easy integration with any Class 2 Bluetooth® (up to 10 m) peripheral.

OptimusS and OptimusSBT feature navigation and software development tools that make customizing applications for even the toughest data-collection challenges a snap.

Each OptimusS comes with the Optimizer software package to facilitate application development. This graphically-oriented program allows even computer beginners to quickly and easily set up the applications they wish to run on their terminal. There are also several simple utilities for uploading and downloading of data. The entire software suite is designed to make application development a painless process.

Both devices come with software for quick configuration to any mobile computing program or database. Their 2MB of memory accommodate large inventories and rechargeable batteries provide hours of scanning operation (OptimusS: 100 hours; OptimusSBT: 36 hours).



Features

- **LCD Display with Backlight and Adjustable Font:** Easy to view screen to accommodate different users and environments
- **Small Form Factor:** Same feature set as bulkier units in a lighter, easier to handle package
- **Cradle Communicates RS232 and USB:** One cradle does both, so a simple cable swap gives users quick-change ability
- **Fully Charged Battery Lasts Approximately 100 Hours:** Minimizes down time; speeds up the inventory process
- **Several Programming Options (Optimizer, BASIC, C):** Accommodates different levels of programming skills from beginner to advanced (SP5500 only)
- **Class 2 Bluetooth Technology (up to 10 m):** Allows real-time data transfer up to 10 meters to a variety of devices

SP5500 OptimusS Technical Specifications

Mechanical/Environmental

Dimensions	Terminal: 137 mm x 55 mm x 28 mm (5.4" x 2.2" x 1.1") Cradle: 58 mm x 92 mm x 110 mm (2.3" x 3.6" x 4.3")
Weight	4.9 oz (140g) including batteries
Operating Temperature	0°C to 55°C (32°F to 131°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Humidity	5% to 95% relative humidity, non-condensing
Drop	Designed to withstand 1.2 m (4') drops

System Architecture

Processor	16-bit CMOS, low power consumption
Memory	Program memory: 2 MB flash ROM Data memory: 2 MB SRAM
Display	LCD - 100 x 64 pixels, back-lit
Keypad	21 rubber keys; alpha/numeric, function, scanner
Audio	Programmable buzzer 1 kHz – 4 kHz
I/O Ports	Unit: Cradle IR, Class 2 Bluetooth (optional); Cradle: USB, RS232, Modem cradle (56k)
Battery	Main: 3.7 V, 700 mAh Li-ion rechargeable; Back-up: 3.0 V, 7 mAh Li-ion rechargeable
Decode Capability	Reads standard 1D symbologies
Imager/Scanner	Laser Scanner Visible Laser Diode 650 nm ± 10 nm
Development Environment	Windows-based Optimizer; optional C & BASIC compilers
Warranty	1 year factory warranty

Wireless Connectivity

WPAN	Class 2 Bluetooth (up to 10 m)
-------------	--------------------------------

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance
For a complete listing of all supported bar code symbologies, please visit www.honeywellaidc.com/symbologies



For more information:
www.honeywellaidc.com

Honeywell Scanning & Mobility

9680 Old Bailes Road
Fort Mill, SC 29707
800.582.4263
www.honeywell.com

Typical Performance*	
Narrow Width	Depth of Field
5.2 mil	70 mm - 95 mm (2.8" - 3.8")
7.5 mil	57 mm - 171 mm (2.3" - 6.8")
10.4 mil	50 mm - 210 mm (2.0" - 8.3")
13 mil	50 mm - 254 mm (2.0" - 10.0")
19.5 mil	75 mm - 300 mm (3.0" - 11.8")

*Resolution: 5 mil (0.127 mm)
*Performance may be impacted by bar code quality and environmental conditions

Honeywell