

24"(23.8" viewable) LED Monitor with SuperClear® AH-IPS type Panel Technology

VA2459-smh



The ViewSonic® VA2459-smh is a 24" (23.8" viewable) Full HD LED monitor with SuperClear® IPS Panel technology, offering clearly sharp color representation and outstanding screen performance at wide viewing angles. It is modernized with a minimalistic, borderless design which provides exceptional viewing experience for home entertainment or office work. It also carries eye-care technology, including Flicker-Free and Blue Light Filter, helping to eliminate eye strain from viewing for extended periods of time. Furthermore, Viewsonic's exclusive ViewMode™ provides intuitive presets to deliver optimized screen performance in different applications, with an energy-saving Eco-mode that enables users to do documental processing or internet surfing while saving. Built in with HDMI and VGA inputs,.

Key Features:

SuperClear IPS Technology
Sleek Frameless Design
flexible connectivity
Dual Integrated Stereo Speakers
VESA-Compatible Mount

Designed for:

Entertainment

24"(23.8" viewable) LED Monitor with SuperClear® AH-IPS type Panel Technology

VA2459-smh

Specifications

LCD Panel	Monitor Size	24" (23.8" viewable)
	Panel Technology	AH-IPS type
	Resolution	Full HD 1920 x 1080
	Display Area	527.04mm (H) x 296.46mm (V)
	Aspect Ratio	16:9
	Brightness	250 cd/m2 (Typ)
	Contrast Ratio	1000:1 (Typ)
	Dynamic Contrast Ratio	80,000,000:1
	Viewing Angles	178 degrees / 178 degrees (Typ)
	Refresh Rate	Recommended: 1920 x 1080 @60Hz
	Response Time	GTG: 4ms (Typ)
	Backlight	1 WLED light bar
	Backlight Life	30,000 Hrs (Min)
	Colours	16.7M colors (6-bit+A-FRC)
	Colour Gamut	72% (Typ) CIE 1931
	Panel Surface	Anti-Glare type, Hard-coating (3H)
	Pixel Size	0.2745mm (H) x 0.2745mm (V)
INPUT SIGNAL	Frequency	Fh = 24 ~ 83KHz ; Fv = 50~ 76Hz
	Sync	Separate Sync, Composite Sync, Sync on Green
COMPATIBILITY	PC	Windows 7, Windows 8, Windows 8.1, Windows 10 certified
	Mac	Power Mac tested
CONNECTOR	Digital	HDMI x 1 (v1.4 compatible)
	Analog	VGA x 1
	Auido Out	Earphone out x 1 (3.5mm plug)
	Audio In	Audio in x 1 (3.5mm plug)
AUDIO	Speaker	2W x2
POWER	Power	3-pin plug (CEE22) x 1
	Voltage	AC 100-240V (Universal); 50/60Hz
	Consumption	21W
	Optimize	18W
	Conserve	14W
ERGONOMICS	Tilt	23° ~ -5°
WALL MOUNT	VESA	100mm x 100mm
OPERATING CONDITIONS	Temperature	32°F to 104°F (0°C to 40°C)
	Humidity	20% to 90% (no condensation)
DIMENSIONS	Physical With Stand (mm)	540.4mm (W) x389.9mm (H) x 200mm (D)
WEIGHT	Net With Stand (kg)	3.26kg
REGULATIONS		BSMI, PSB, RCM, MEPS, SASO, KC, e-Standby, VCCI, PSE
PACKAGE CONTENTS		LCD Display/Power Cable (1.5m)/VGA Cable (1.5m)/Audio Cable (1.5m)/Quick Start Guide