



ProLite X2775HDS

The ProLite X2775HDS is the latest addition to the range of monitors featuring VA Panel technology which offers superb colour performance and viewing angles. This sophisticated technology provides 24 bit 'True Colour' and superior black and white display performance. A 3000:1 Native Contrast Ratio means the ProLite X2775HDS is ideal for Photographic Design and Web-design. Featuring a fast response time, full HD 1920 x 1080 resolution with VGA, DVI and HDMI connectivity, this screen is compatible with a wide range of systems and applications and is also a Low Power LED Panel, making it an excellent choice for Universities, Corporate, Financial and Design Markets.

DISPLAY CHARACTERISTICS

Diagonal	27"
Panel	VA
Display area h x w	336.2 x 597.6 mm; 13.2" x 23.5"
Response time	8 ms
Contrast	3000 : 1 typical
Contrast	5 000 000 : 1 ACR
Brightness	300 cd/m ² typical
Viewing zone	horizontal/vertical: 178° / 178°; right/left: 89° / 89°; up/down: 89° / 89°
Display colour	16.7 million
Pixel pitch h x v	0.3113 x 0.3113 mm
Native resolution	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
Horizontal sync	24 - 80 KHz
Vertical sync	55 - 75 Hz
Synchronization	Separate Sync
Aspect ratio	16 : 9

POWER MANAGEMENT

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	42 W typical; max. 1 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®

DIMENSIONS & WEIGHT

Dimensions w x h x d	642 x 438.5 x 210 mm
Weight	6 kg

INTERFACES & CONNECTORS

Analog input connector	VGA (D-Sub)
Digital input connector	DVI-D, HDMI
HDCP	yes
Headphone connector	Yes
Output connector	headphone socket
Inputs	USB (4x)

SPECIAL FEATURES

Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Plug & Play	VESA DDC2BT™
Controls	Via OSD in 9 languages (EN, DE, FR, ES, IT, PT, Chinese, RU, JP) and 5 front controls (Power, Menu/ Select, +/ Volume, -/ ECO, Auto)
User controls	luminance (contrast, brightness, ECO, i-style Colour, ACR), image setup (clock, phase, H. position, V. position, aspect), colour adjust (colour temperature, gamma), OSD setup (H. position, V. position, time out, language), others (reset, signal select, HDMI audio, OD, information), volume, auto adjust
Speakers	2 x 2 W (Stereo)
Anti-theft-device	Kensington-lock™ prepared
Ergonomics	CE, TCO 5.1
Safety	TÜV-Bauart
Tilt angle	20° up; 5° down
VESA mounting	100 x 100 mm
Colour	Black

ACCESSORIES

Driver	Windows 95 / 98 / 2000 / ME / XP / Vista / 7
Included accessories	power cable, D-Sub cable, DVI-D cable, audio cable, USB cable, stand, quick start guide