

4XEM's 4XEM's 4-in-1 HDMI, VGA, Power Delivery USB-C Dock

4XEM Part- 4XUSBCHUB05



Expand your desktop to multiple displays with higher resolutions for an increased experience when entertaining, gaming, and when at work. 4XEM's 4-in-1 USB-C Docking Station connects to a multitude of devices through its HDMI port and VGA port. Additionally, the docking station comes with a USB-C port and a USB-A port which comes with Power Delivery; both ideal for charging and transferring data. Increase your displays either at work or at leisure with 4XEM's 4-in-1 USB-C Docking Station.

**Problem it Solves:** The 4XEM's 4-in-1 USB-C Docking Station allows you to expand your desktop monitor to other screens, either through an HDMI connection or a VGA one. Get higher resolution simply with 4XEM's 4-in-1 Docking Station.

**4XEM Products Are Available At Your Favorite Online Retailers**

**WWW.4XEM.COM**

Contact Todd Schaus 4XEM sales Rep  
1-866-999-4936 Ext.104    [tschaus@4xem.com](mailto:tschaus@4xem.com)



## Features

- USB-C connector for charging and transferring
- USB-A with Power Delivery
- HDMI port
- VGA port
- Supports 4K video resolution
- PC Compatibility: MacBook Pro 15"/13"/2018/17/16, MacBook 2018/17/16/15, iMac/iMac Pro 2017, Dell XPS 13 9350/9360, HUAWEI MateBook X
- Mobile Compatibility: Huawei mate 10/P20, Samsung Galaxy S8/S8+/S9/S9+

## Application

- Home
- Office
- Networks
- Charging
- Transferring

**4XEM Products Are Available At Your Favorite Online Retailers**





**DATA SHEET**

Warranty Information	Warranty	3 Years
Hardware	4K Support	Yes
	Fast-Charge Port(s)	No
Connector(s)	Displays Supported	2 *see Notes*
	Interface	USB 3.0
	Bus Type	USB-C
	Industry Standards	HDMI 1.4
	Chipset ID	Power Delivery - DP 2.0 Explore Microelectronics - EP9632
Performance	Host Connector	USB Type-C
	Host Connector Type	Fixed Attached Cable
	Connector Type(s)/Rate(s)	1x HDMI 1.4 (10.2 Gbps) 1x VGA 1x USB 3.0 Type-A (5 Gbps) 1x USB Type-C (used for PD only)
	Maximum Digital Resolutions	Single Display: 3840 x 2160 @ 30Hz Dual Display: 1920 x 1080 @ 60Hz
	Maximum Digital Resolutions	1920 x 1080 @ 60Hz
Software	OS Compatibility	Windows® 10 Mac OS® 11
Power	Power Source	Bus Powered
	Power Delivery	PD Pass-Through - Max 100W
Physical Characteristics	Weight of Product	1.62 oz [46 g]
	Color	Grey, Black
	Material	Aluminum, Plastic, PVC
	Cable Length	5.31 in [135.0 mm]
	Product Height	0.60 in [15.3 mm]
	Product Width	2.45 in [62.3 mm]
	Product Length	1.59 in [40.3 mm] (incl cable - 8.64 in [219.5 mm])
Environmental	Operating Temperature	0°C to 55°C (32°F to 131°F)
	Storage Temperature	-10°C to 70°C (14°F to 158°F)
	Humidity	40~50% RH
Packaging Information	Shipping (Package) Weight	2.19 oz [62 g]
	Package Height	6.63 in [168.4 mm]
	Package Width	3.00 in [76.2 mm]
	Package Length	0.73 in [18.5 mm]
What's in the Box	Included in Package	1x USB-C Hub

**Notes**  
 Although this adapter supports 2 concurrently connected displays, the host OS only recognizes a single display resulting in the same image on both displays (mirror effect).  
 A host laptop with an available USB-C port (to ensure full adapter functionality, the host USB-C port must support DP alt mode and Power Delivery 2.0)  
 A 4K-capable display is required to achieve 3840 x 2160p resolution (4K is also known as 4K x 2K)  
 Uses 2 data lanes for DP alt mode @ HBR2 for video output and 2 data lanes for other functions

\* Product appearance and specifications are subject to change without notice.  
 \* Same day shipping is only available for orders shipping within the United States.

**4XEM Products Are Available At Your Favorite Online Retailers**

**WWW.4XEM.COM**

**Contact Todd Schaus 4XEM sales Rep  
 1-866-999-4936 Ext.104    tschaus@4xem.com**

