

# CITIZEN

## Print - Stick - Done

Market-leading, Eco-friendly POS printing solution



### The upgraded CT-S601IIR

A new and special version of the popular CT-S601II printer, the new CT-S601IIR arrives as a Re-Stick Liner-Free Model that prints top exit, self-adhesive labels and has been designed to serve across multiple applications.

### Eco-friendly POS printing solutions

Producing cost-effective, continuous roll label output, the CT-S601IIR also highlights mark-leading eco-friendly capabilities. Offering users significant waste reduction, the new printer produces entirely Liner-Free labels and is compatible with MAXStick® media. Also, due to its ability to adjust the print length to suit the required content, CT-S601IIR reduces waste further still.

### Internal power supply

All 80mm POS printers from Citizen offer an internal power supply.

## CT-S601IIR

POS, Receipt printer (thermal 3 inch / 80mm)

### Applications

---



Available in either sleek black or classic ivory

TOMORROW'S PRINTING TODAY



Supported by an adaptable range of optional interfaces including USB, LAN, WiFi, Bluetooth and others.

## Specifications

## CT-S601IIR

**POS, Receipt printer (thermal 3 inch / 80mm)**

### Features & Benefits

- Low space requirement - integrated power supply enables clean work station
- Mobile-POS ready



Producing super-fast, liner-free labels up to 83 mm wide, at a speed of 175 mm per second and at 203 dpi

# CITIZEN

## CT-S601IIR

POS, Receipt printer (thermal 3 inch / 80mm)

<b>Model</b>	<b>CT-S601IIR</b>
<b>Printing Technology</b>	Direct Thermal
<b>Resolution</b>	203 dpi
<b>Print Speed (maximum)</b>	175mm/sec
<b>Roll Size (max), Core Size</b>	83 mm outside diameter
<b>Media Thickness (min to max)</b>	65µm to 90µm
<b>Media Sensor</b>	Paper end
<b>Main Interface</b>	None: interface card slot for optional card
<b>Interface</b>	Parallel (IEEE 1284 compliant), Serial (RS-232C compliant), USB, Premium Wireless LAN, Ethernet (SEH), Bluetooth with Apple™ MFi compatibility, Compact Wireless LAN, Ethernet, Ethernet + USB host, USB 2.0, Powered USB
<b>Power supply</b>	100 – 240V, 50-60 Hz, external power supply (supplied) or 24V DC
<b>Reliability</b>	100 million pulses, 75km
<b>Control panel</b>	Feed button, 3 LEDs
<b>Emulations (Languages)</b>	ESC/POS™
<b>Drivers and software</b>	Free-of-charge from website, including support for various platforms
<b>Size (W x D x H) and Weight</b>	145x192x148 mm, 2 Kg, DC version 145x192x120, 1.6 Kg
<b>Cutter</b>	Guillotine type, partial
<b>EMC and safety standards</b>	CE, UL, TUV, C-UL, FCC class A, VCCI

# CITIZEN

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

CT-S601IIR

**POS, Receipt printer (thermal 3 inch / 80mm)**