

## 4500 Series Thin Clients

*4K Value & Security Class*

Model Numbers: 4572, 4510

### Industry Leading VDI Performance

The 4500 Series is a new, highly secure model to the 10ZiG product lineup. The 4500 Series is small in size yet surprisingly powerful, supporting a 4K dual monitor setup at a value price point. Featuring a 1 x DisplayPort and 1 x HDMI combination along with a rare industry find of a Fiber option, the 4500 Series is an ideal choice for Federal and Military as well as Enterprise Organizations in verticals such as Finance and Healthcare needing the absolute highest levels of security in their VDI environment.

The 10ZiG 4500 Thin Client is available with 10ZiG PeakOS™ (Linux), Windows 10 IoT (W10 IoT) and is VMware, Citrix and Microsoft Ready.



- ▶ Intel Dual Core N3060 1.6 GHz (2.48 GHz Burst Frequency)
- ▶ Optional Fiber
- ▶ 1 x DisplayPort and 1 x HDMI combination
- ▶ 5 x USB (2 x USB 3.0)
- ▶ Optional Wireless (External Antenna)
- ▶ Optional VESA and ARM Mount
- ▶ Optional TPM 2.0 (Windows Only)
- ▶ Optional TAA Compliance
- ▶ 4K UHD with Dual Monitor Support\*
- ▶ 802.1x Network Authentication
- ▶ FREE Centralized Management via 10ZiG Manager

# 4500 Series Thin Clients



System	
Management	10ZiG Manager
Form Factor	Ultra Mini
Processor	Intel Dual Core N3060 1.6 GHz (2.48 GHz Burst Frequency)
Processor Graphics	Intel HD Graphics
Dimensions	
Device	5.5"(D) x 2.4"(W) x 6.6"(H) - 140mm x 61mm x 168mm
Weight	1.39 lbs (630g)
Connections	
Ports	1 x DisplayPort, 1 x HDMI, 2 x USB 3.0, 3 x USB 2.0, 1 x Mic In, 1 x Line Out, 1 x LAN (RJ45 or Fiber option), DC Jack
Video/Resolution	3840 x 2160 @ 30Hz / 2560 x 1600 @ 60Hz (2 monitors at 4K UHD)
Networking	
Wireless	Optional (802.11 a/b/g/n/ac External Antenna)
Fiber OR Ethernet	Fiber option OR standard RJ45 LAN (10/100/1000 Base-T)
Environmental	
Operating Temp.	32°-95°F (0°-35°C), 20-80% non-condensing humidity
Power	3-4 Average Watt Consumption, DC-12V/2A External Power Adapter

## SPECIFICATIONS

1. Power Button
2. USB 3.0 (2)
3. Mic In
4. Line Out
5. Reserve hole for external antenna
6. USB 2.0 (3)
7. HDMI Port
8. DisplayPort
9. RJ45 LAN or Fiber LAN Port
10. DC Jack
11. Kensington Lock

4572

4510

## Operating System

PeakOS™ (Linux)

Windows 10 IoT

## Memory

RAM	Std: 2GB Max: 8GB	Std: 4GB Max: 8GB
Storage	Std: 4GB Max: 256GB	Std: 16GB Max: 256GB

## Software

Software Applications	Firefox, Google Chrome**, Adobe Reader, Putty, Citrix Receiver, VMware Horizon Client, FreeRDP Client, Parallels Client, VNC (Shadowing), GStreamer, OpenOffice**, iSeries/5250 Emulation**, JRE (Java Runtime Engine)	Internet Explorer, Citrix Receiver, RDP, VMware Horizon Client, VNC (Shadowing), Windows Media Player, Amazon WorkSpaces, Parallels RAS Client, Spice Client, JRE (Java Runtime Engine), Microsoft Silverlight, Workspot Client
-----------------------	--	---

VDI Connection Brokers Supported	VMware Horizon (Blast Extreme, PCoIP, RDP), Citrix XenApp & XenDesktop, RDP, Parallels RAS	VMware Horizon (Blast Extreme, PCoIP, RDP), Citrix XenApp & XenDesktop, RDP, Parallels RAS, Amazon WorkSpaces, Workspot VDI
----------------------------------	--	---

\*4K performance dependent upon your current VDI Infrastructure and the necessary minimum requirements to support it.

\*\*Optional Application may require alternative model; please speak to a sales representative to confirm.



Americas P: +1 (866) 865-5250  
 EMEA P: +44 (0) 116 214 8650  
 APAC P: +61 2 80027421  
 DE P: +49(0) 6724 9304 45

E: info@10ZiG.com  
 E: info@10ZiG.eu  
 E: info@10ZiG.com.au  
 E: vertrieb@10zig.de

W: www.10ZiG.com

