

## SCENICVIEW P26W-5 ECO

### Premium Line wide TFT display

### With 0-watt power save mode

Issue August 2008

Pages 2

Enjoy perfect picture quality, outstanding ergonomics and usability as well as comfortable energy saving solutions of the new SCENICVIEW Premium Line displays.

#### Unique energy saving solutions

- 0-watt power save mode - 0.0 watt power consumption in standby
- ECO button - direct access to power saving operation mode
- Auto brightness control – protects your eyes and the environment

#### Premium 26-inch 16:10 wide format with ultra wide viewing angle

- In Plane Switching (IPS) for 178° typical viewing angle
- Brilliant color reproduction with more than 2,300,000 pixels
- 16.7 Mio colors (8-bit panel)
- Enhanced Color Gamut
- Overdrive technology for 5 ms gtg response time

#### Enhanced ergonomics stand

- Optimized ergonomic position close to desk adjustable
- 120 mm Height adjust
- +25° enhanced tilt
- +/-90° swivel

#### Representative Design

- Space saving front frame
- Optimized cable guide and elegant connector cover
- Integrated speakers




#### Flexible Connectivity

- HDMI interface, HDCP (via DVI-D and HDMI)
- 4x USB
- Analog and DVI interface

#### Comfortable usability and ready for Manageability

- DisplayView™ Auto Bright (adjustable Auto Brightness Control)
- DisplayView™ Bright (optimized picture performance for every application)
- DisplayView™ IT Suite
- Ready for remote inventory gathering
- Ready for remote execution of configuration tasks



<b>Visible screen diagonal</b>	26-inch (65 cm)
<b>Graphics display</b> (dependent on graphics processor)	
Pixels	1920 x 1200 (recommended)
Pixels *)	1680 x 1050
Pixels *)	1440 x 900, 1280 x 800
Pixels *)	1600 x 1200
Pixels *)	1280 x 1024
Pixels *)	1024 x 768
Pixels *)	800 x 600, 640 x 480
*) interpolated	
<b>HD standards</b>	1080i/p, 720p, 576i*/p, 480i*/p (* via HDMI only)
<b>Text display</b> (dependent on graphics processor)	
Pixels (max. 75 Hz)	720 x 400
<b>Picture size</b>	550 x 344 mm
<b>Pixel pitch</b>	0.287 mm
<b>Frequencies</b>	
Horizontal analog	28 – 94 kHz
Horizontal digital	28 – 82 kHz
Vertical	50 - 76 Hz
<b>Brightness typical</b>	400 cd/m <sup>2</sup>
<b>Contrast typical</b>	1000:1
<b>Ultra wide viewing angle</b> typical with CR>10:1	
Horizontal	178°
Vertical	178°
<b>Color performance</b> typical	16.7 Mio colors (8-bit panel) 102% color gamut (NTSC)
<b>Response time typical</b>	
Black to black typical	12 ms
Gray to gray	5 ms
<b>Plug &amp; Play</b>	VESA DDC CI
<b>Ease-of-use menu</b>	
Brightness/ Contrast	Brightness, Contrast, Black level, Auto Brightness, Auto level
Mode	Optimal, Office, Photo, Video
Image adjust	Phase, Clock, H-Position, V-Position, Sharpness, Saturation, Expansion
Audio	Volume, Mute
Color	sRGB, 6500K, 7500K, 9300K,
Setup	Native, Custom Color(R,G,B) Input Select, Language, DDC-CI, OSD-Position, OSD Timeout, Factory Recall
Information	Model name, S/N, Resolution/mode, Signal input
<b>Inclined support management</b>	
Height-adjust range	120 mm
Tilt angle up to	-5° / + 25°
Swivel	+/-90°
<b>Audio characteristics</b>	
Volume control	digital
Audio signal input (from PC)	3.5 mm stereo phone jack
Sound output	2.0 W (L) + 2.0 W (R)

<b>Electrical values</b>	
Rated voltage	100 – 240 V
Frequency	50 - 60 Hz
Power draw typical	
Operation (w/o sound & USB)	
max. Brightness	110W
with EPA settings	55W
0 watt power save mode	0.0 W
Protection class	1
<b>Temperatures / dimensions / weight</b>	
Ambient temperature (to IEC721)	
Recommended range	15°C to 32°C
Limit	5°C to 35°C
Dimensions (landscape, lowest position)	
(H x W x D)	462 x 610 x 217 mm
Dimensions without base	
(H x W x D)	409 x 610 x 93 mm
Weight unpacked / packed	10.5 kg / 12.5 kg
without base unpacked	8.3 kg
<b>Reliability typical</b>	
MTBF (demonstrated)	70,000 h
Lifetime of LCD	50,000 h
(brightness > 50 % of original brightness)	
<b>Compliance with standards</b>	
Product safety	EN60950
Ergonomics	GS mark ISO13406-2 (Pixel fault class II)
Radiation immunity and RFI suppression	CE certification according to EC Directive 2004/108/EEC (EN55022/B, EN55024 EN61000-3-2/-3); TCO'03 , TCO'06
Ecology	RoHS, WEEE, IT-Eco-declaration Energy Star (EPA 4.1)
<b>Video input</b>	1 x D-SUB analog 1 x DVI-D (24-pin) digital 1 x HDMI HDCP on DVI and HDMI
<b>USB</b>	4 x USB 2.0 downstream 1 x USB upstream
<b>Data cable (1.8 m)</b> detachable on display	D-SUB (15-pin) analog DVI-D (24-pin) digital Audio cable , USB cable (upstream)
<b>Power cable (1.8 m)</b>	for wall socket Euro-Schuko-Type CEE7
Integrated power supply	
Plug type on display side	IEC-320-C13
<b>Special features</b>	0-watt power save mode, ECO button, Auto brightness control, DisplayView™ IT Suite, Kensington Lock prepared, standardized mounting interface according VESA FPMPI (100 mm)
<b>Order code</b>	S26361-K1253-V150