IN2138HD



Bright, long-life business projector designed to work with the devices you already use Part #: IN2138HD

Superior lens performance, brighter-than-ever images, comprehensive networking capabilities, and room-filling internal audio -- all in a projector designed to work seamlessly with the devices you're already using.

Key Features

- ♦ 1080p (1920 x 1080) native resolution
- ♦ 4500 lumens and 28,500:1 contrast ratio for depth of image and life-like colors
- TechStation lets you customize your projector with the devices you already use
- Powered HDMI for mobile charging and device power
- Long life lamp of up to 15,000 hours
- 10-watt speaker and unique design for powerful sound
- Class-leading, whisper-quiet design
- Supports all HDMI 1.4a 3D formats

















Customize your projector using TechStation

With an HDMI port and multiple ways to connect your devices, the TechStation superpowers your projector and enables more effective learning by working seamlessly with the tools you already use. After connecting your device, close up the TechStation's lid to create a streamlined, all-in-one solution for streaming audio and video.

IN2130 Series projectors work with:

- Google ChromeCast Ultra
- Intel Computer Stick
- Asus Chromebit
- Amazon Fire TV Stick
- Android stick
- And more HDMI-supported devices to enable casting, streaming, and wireless



Exceptional Sound Quality

IN2130 Series projectors were designed to provide better-thanever sound quality through a 10W speaker. Whisper-quiet operating technology means you'll never have to compete against your projector to be heard during meetings or presentations. The IN2138HD projector offers high quality optics with 1.3x zoom ratio, clear focus, and full HD resolution. The projector delivers a longer throw so you have more flexibility on where to mount.

Brighter, Sharper Images in Any Light

With 4,500 lumens, amazing 28,500:1 contrast ratio, and 1080p HD, the IN2138HD projects sharper, clearer images no matter the lighting in your office or conference room. Plus BrilliantColor™ DLP imaging technology ensures images shine with over 1 billion colors that ensure life-like color accuracy and eye-catching presentations.

More Ways to Connect and Control

InFocus <u>ProjectorNet 4.1 software</u> lets you remotely manage and support your projector from a single computer via your existing network. Or quickly connect the IN2138HD projector to your internal network for easy remote management. You can also simply sync with Crestron Roomview or AMX Device Discovery.



Superior Lens Performance

Specifications*

esolution – Native Full HD (1920 x 1080) isplay Technology DLP ideo Standard Compatibility NTSC, NTSC 4.43, PAL, PAL-M, PAL-M, SECAM, 480i, 480p, 576i, 576p, 720p, 1080i, 1080p peakers Mono 10W x 1 amp Brightness 4,500 lumens amp Brightness – Eco Mode 3,360 lumens amp Life 5,000 hours amp Life – Dynamic Mode 15,000 hours amp Power 245W amp Power – Eco Mode 170W ontrast Ratio 28,500:1 olor Wheel High Speed 6 Segment RYGCWB umber of Colors 1.07 billion ynch Scan Frequency – Horizontal 31.5 ~ 97.6 KHz ynch Scan Frequency – Vertical 56 - 120 KHz spect Ratio 16:9 spect Ratio Compatibility 43, 16:10 ens Type Manual focus		
isplay TechnologyDLPideo Standard CompatibilityNTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, 480i, 480p, 576i, 576p, 720p, 1080i, 1080ppeakersMono 10W x 1amp Brightness4,500 lumensamp Brightness – Eco Mode3,360 lumensamp Life5,000 hoursamp Life – Low Power10,000 hoursamp Life – Dynamic Mode15,000 hoursamp Power245Wamp Power – Eco Mode170Woutrast Ratio28,500:1olor WheelHigh Speed 6 Segment RYGCWBumber of Colors1.07 billionynch Scan Frequency – Horizontal31.5 ~ 97.6 KHzspect Ratio16:9spect Ratio Compatibility4:3, 16:10ens TypeManual focusrojection Offset15%	Projector	IN2138HD
ideo Standard Compatibility NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, 480i, 480p, 576i, 576p, 720p, 1080i, 1080p peakers Mono 10W x 1 4,500 lumens amp Brightness — Eco Mode 3,360 lumens amp Life 5,000 hours amp Life — Low Power 10,000 hours amp Life — Dynamic Mode 15,000 hours amp Power 245W amp Power — Eco Mode 170W ootrast Ratio 28,500:1 oolor Wheel High Speed 6 Segment RYGCWB umber of Colors ynch Scan Frequency — Horizontal 31,5° 976 KHz spect Ratio 56 - 120 KHz spect Ratio Compatibility 4:3, 16:10 ens Type Manual focus rojection Offset 15%	Resolution – Native	Full HD (1920 x 1080)
meskers Mono 10W x 1 amp Brightness 4,500 lumens amp Brightness – Eco Mode 3,360 lumens amp Life 5,000 hours amp Life – Low Power 10,000 hours amp Life – Dynamic Mode 15,000 hours amp Power 245W amp Power – Eco Mode 170W ontrast Ratio 28,500:1 olor Wheel High Speed 6 Segment RYGCWB umber of Colors 1.07 billion ynch Scan Frequency – Horizontal 31.5 ~ 97.6 KHz ynch Scan Frequency – Vertical 56 - 120 KHz speet Ratio Compatibility 4:3, 16:10 ens Type Manual focus rojection Offset 15%	Display Technology	DLP
App Brightness 4,500 lumens amp Brightness – Eco Mode 3,360 lumens amp Life 5,000 hours amp Life – Low Power 10,000 hours amp Life – Dynamic Mode 15,000 hours amp Power 245W amp Power – Eco Mode 170W ontrast Ratio 28,500:1 olor Wheel High Speed 6 Segment RYGCWB umber of Colors 1.07 billion ynch Scan Frequency – Horizontal 31.5 ~ 97.6 KHz ynch Scan Frequency – Vertical 56 - 120 KHz spect Ratio Compatibility 4:3, 16:10 ens Type Manual focus rojection Offset 15%	Video Standard Compatibility	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
amp Brightness – Eco Mode 3,360 lumens amp Life 5,000 hours amp Life – Low Power 10,000 hours amp Life – Dynamic Mode 15,000 hours amp Power 245W amp Power – Eco Mode 170W ontrast Ratio 28,500:1 olor Wheel High Speed 6 Segment RYGCWB umber of Colors 1.07 billion ynch Scan Frequency – Horizontal 31.5 ~ 97.6 KHz ynch Scan Frequency – Vertical 56 - 120 KHz spect Ratio 16:9 spect Ratio Compatibility 4:3, 16:10 ens Type Manual focus rojection Offset 15%	Speakers	Mono 10W x 1
amp Life 5,000 hours amp Life - Low Power 10,000 hours amp Life - Dynamic Mode 15,000 hours amp Power 245W amp Power - Eco Mode 170W ontrast Ratio 28,500:1 olor Wheel High Speed 6 Segment RYGCWB umber of Colors 1.07 billion ynch Scan Frequency - Horizontal 31.5 ~ 97.6 KHz ynch Scan Frequency - Vertical 56 - 120 KHz spect Ratio Compatibility 4:3, 16:10 ens Type Manual focus rojection Offset 15%	Lamp Brightness	4,500 lumens
amp Life – Low Power amp Life – Dynamic Mode amp Life – Dynamic Mode amp Power 245W amp Power – Eco Mode 170W ontrast Ratio 28,500:1 olor Wheel High Speed 6 Segment RYGCWB umber of Colors 1.07 billion ynch Scan Frequency – Horizontal 31.5 ~ 97.6 KHz ynch Scan Frequency – Vertical spect Ratio spect Ratio 69 spect Ratio Compatibility 4:3, 16:10 ens Type Manual focus rojection Offset 15%	Lamp Brightness – Eco Mode	3,360 lumens
amp Life – Dynamic Mode amp Power 245W amp Power – Eco Mode 170W ontrast Ratio 28,500:1 olor Wheel High Speed 6 Segment RYGCWB umber of Colors 1.07 billion ynch Scan Frequency – Horizontal 31.5 ~ 97.6 KHz ynch Scan Frequency – Vertical spect Ratio spect Ratio spect Ratio Compatibility 4:3, 16:10 many Difference of the segment RYGCWB many Difference	Lamp Life	5,000 hours
245W amp Power – Eco Mode 170W contrast Ratio 28,500:1 color Wheel High Speed 6 Segment RYGCWB umber of Colors 1.07 billion ynch Scan Frequency – Horizontal ynch Scan Frequency – Vertical spect Ratio spect Ratio spect Ratio Compatibility ens Type Manual focus rojection Offset 15%	Lamp Life – Low Power	10,000 hours
amp Power – Eco Mode ontrast Ratio 28,500:1 olor Wheel High Speed 6 Segment RYGCWB umber of Colors 1.07 billion ynch Scan Frequency – Horizontal ynch Scan Frequency – Vertical Spect Ratio spect Ratio spect Ratio Compatibility ens Type Manual focus rojection Offset 15%	Lamp Life — Dynamic Mode	15,000 hours
28,500:1 olor Wheel High Speed 6 Segment RYGCWB umber of Colors 1.07 billion ynch Scan Frequency – Horizontal 31.5 ~ 97.6 KHz ynch Scan Frequency – Vertical 56 - 120 KHz spect Ratio Spect Ratio Compatibility 4:3, 16:10 ens Type Manual focus rojection Offset 15%	Lamp Power	245W
olor Wheel High Speed 6 Segment RYGCWB umber of Colors 1.07 billion ynch Scan Frequency – Horizontal 31.5 ~ 97.6 KHz ynch Scan Frequency – Vertical 56 - 120 KHz spect Ratio 16:9 spect Ratio Compatibility 4:3, 16:10 ens Type Manual focus rojection Offset 15%	Lamp Power – Eco Mode	170W
umber of Colors 1.07 billion 31.5 ~ 97.6 KHz ynch Scan Frequency – Vertical 56 - 120 KHz spect Ratio 16:9 spect Ratio Compatibility 4:3, 16:10 ens Type Manual focus rojection Offset 15%	Contrast Ratio	28,500:1
ynch Scan Frequency – Horizontal 31.5 ~ 97.6 KHz ynch Scan Frequency – Vertical 56 - 120 KHz spect Ratio 16:9 spect Ratio Compatibility 4:3, 16:10 ens Type Manual focus rojection Offset 15%	Color Wheel	High Speed 6 Segment RYGCWB
ynch Scan Frequency – Vertical 56 - 120 KHz spect Ratio 16:9 spect Ratio Compatibility 4:3, 16:10 ens Type Manual focus rojection Offset 15%	Number of Colors	1.07 billion
spect Ratio 16:9 spect Ratio Compatibility 4:3, 16:10 ens Type Manual focus rojection Offset 15%	Synch Scan Frequency — Horizontal	31.5 ~ 97.6 KHz
4:3, 16:10 ens Type Manual focus rojection Offset 15%	Synch Scan Frequency – Vertical	56 - 120 KHz
Manual focus rojection Offset 15%	Aspect Ratio	16:9
rojection Offset 15%	Aspect Ratio Compatibility	4:3, 16:10
	Lens Type	Manual focus
eystone Correction ± 40° / ±5°	Projection Offset	15%
	Keystone Correction	± 40°/±5°

Projector	IN2138HD
Connectors – Inputs	3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection)
Connectors – Outputs	3.5mm audio output, Monitor out (VGA)
Control	RS232, IR Remote, Network (RJ45, Telnet, ProjectorNet, Crestron Roomview, AMX Device Discovery, Browser)
Audible Noise – Eco Mode	< 21 dBA at 0°F / -17.8°C
Included Accessories	Power cord, Remote, HDMI Cable, Documentation, User Manual (CD)
3D Support	1080p @ 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required
Power Consumption	300.0W max
Power Consumption – Standby Mode	1.8W max
Power Consumption – Low Power Standby	0.5W max
Power Consumption – Eco Mode	220.0W max
Power Standard	AC 100 to 240V, 50/60
Operating Conditions	41 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m
Documentation Languages	English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese
Menu Languages	English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai
Security Features	Kensington lock port
TechStation	Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices
Throw and Zoom	
Throw Ratio – Minimum	1.12:1
Throw Ratio – Maximum	1.47:1
Zoom Ratio	1.3:1
Shipping	
Product Dimensions	4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm
Product Weight	7.1 lbs / 3.2 kg
Shipping Dimensions	7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm
Shipping Weight	9.9 lbs / 4.5 kg

^{*} Product specifications, terms, and offerings are subject to change at any time without notice.

Accessories

SimpleShare Presentation System (INA-SIMPS1)

Universal Projector Ceiling Mount (PRJ-MNT-UNIV)

 $1\ Year\ Extended\ Warranty\ for\ IN1XXX,\ IN2XXX,\ IN3XXX\ Projectors\ (EPW-PJM1)$

SimpleShare Touch Presentation System (INA-SIMINT1)

SimpleShare (INA-SIMS1)

LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+)

Soft Carry Case for Value Projectors (CA-SOFTVAL-2)

DLP Link 3D Glasses by XPAND (X103-EDUX3-R1)

 ${\it 2 Year Extended Warranty for IN1XXX, IN2XXX, IN3XXX Projectors (EPW-PJM2)}\\$