

1 Port USB to RS232 DB9 Serial Adapter Cable - M/M

StarTech ID: ICUSB232V2



The ICUSB232V2 1 Port USB to Serial Adapter converts a USB port into an RS232 DB9 serial port to connect to, monitor, and control a serial device.

Supporting data transfer rates up to 921.6 Kbps, the USB to serial cable is a convenient and cost-saving solution for providing serial connectivity to devices such as point-of-sale terminals, serial modems, industrial equipment, and a wide variety of other RS232 peripherals.

The USB to RS232 converter is easy to install and offers broad operating system compatibility, including Windows® 8, Linux and Mac OS®, for easy integration into mixed environments.

Backed by a StarTech.com 3-year warranty and free lifetime technical support.

Applications

- IT Administrators looking to add legacy functionality to newer notebooks, PCs and servers that lack an integrated RS232 port
- Connect bar code scanners, receipt printers and other point of sale devices
- Connect, monitor and control industrial/automotive sensors and other sensitive equipment
- Connect and program LED and digital signage boards

Features

- USB to Straight-Through RS232 DB9 Serial Adapter
- High-speed 921.6Kbps Baud Rate
- Compatible with Windows® 8, Mac OS X® and Linux
- Compatible with USB 1.1 or higher ports
- USB-powered - no external power adapter required
- Single cable, small footprint design for portability

Technical Specifications

Warranty	3 Years
Bus Type	USB 2.0
Chipset ID	Prolific - PL2303-HXD
Industry Standards	USB 1.1/2.0 RS232
Interface	Serial
Port Style	Cable Adapter
Ports	1
Connector Type(s)	1 - DB-9 (9 pin; D-Sub) Male
Connector Type(s)	1 - USB A (4 pin) Male
Data Bits	5, 6, 7, 8
FIFO	512 Bytes
Flow Control	None, Xon/Xoff, RTS/CTS, DTR/DSR
Max Baud Rate	921.6 Kbps
Parity	Odd, Even, Mark, Ace, or None Parity Modes
Serial Protocol	RS-232
Stop Bits	1, 1.5, 2
Microsoft WHQL Certified	Yes
OS Compatibility	Windows® 8 (32/64bit), 7 (32/64), Vista(32/64), XP(32/64), 2000 Windows® Server 2012, 2008 R2, 2008, 2003(32/64) Mac OS 10.x (Tested up to 10.8), 9.x, 8.x Linux kernel 2.4.31 and later
System and Cable Requirements	One available USB 1.1 (or above) port
Enclosure Type	Plastic
Product Height	0.8 in [20 mm]
Product Length	16.9 in [430 mm]
Product Weight	1.9 oz [52.5 g]
Product Width	1.4 in [35 mm]
Humidity	0~65% RH
Operating Temperature	0°C to 60°C (32°F to 140°F)
Storage Temperature	-20°C to 80°C (-4°F to 176°F)
Shipping (Package) Weight	2.2 oz [62.5 g]
Included in Package	1 - USB to RS232 Adapter
Included in Package	1 - Instruction Manual

Certifications, Reports and Compatibility

