






MKE Essential Omni

Quick Guide | Kurzanleitung | Guide rapide | Guida rapida | Guía de inicio rápido | Guia rápido | Beknopte handleiding | Krótka instrukcja obsługi | Snabbguide | Kort vejledning | Pikaohje | Γρήγορος οδηγός | Kısa Kılavuz | Краткая инструкция | 快速指南 | 快速使用指南 | クイックガイド | 요약 설명서

In the box





Foam windscreen
SL MZW 1




MZQ 02

Frequency response




capsule
only







Technical Data

Pick-up pattern	omni-directional
Frequency response	20 - 20.000 Hz
Sensitivity in free field, no load (1 kHz)	5 mV, Pa +- 3,5 dB
Nominal impedance	1 kΩ
Min. terminating impedance	4,7 kΩ
Equivalent noise level:	
A-weighted (DIN IEC 651)	28 dB
CCIR-weighted (CCIR 468-1)	41 dB
Max. sound pressure level	140 dB
Plug	3,5 mm or 3-Pin
Cable length	1,6 m
Diameter of mic capsule	4,8 mm
Weight	16 g



Sennheiser electronic GmbH & Co. KG

Am Labor 1, 30900 Wedemark, Germany, www.sennheiser.com
Printed in Germany, Publ. 05/18, 578672/A01




Wind screen






Instrument

Clip

Magnetic mount



Pin mount



* Accessory | Zubehör | Accessoires | Accesorios | Accesorios | Acessórios |
 Toebehoren | Części akcesoria | Tillbehör | Tilbehør | Lisäosia | Αξεσουάρ
 ανταλλακτικά | Aksesuar | Аксессуары | 附件 | 付属品 | 액세서리부품