

MIP480 In-Vehicle Printer

Fixed Vehicle Printer for Heavy Duty Workload



- Rugged construction
- Easy paper loading
- Simple to change long life ribbon
- Can handle fan fold and cut sheet forms
- Print speed up to 480 cps
- Backlit control panel
- Bluetooth and 802.11 b/g connectivity available
- Intermec 6820 Compatible

High speed, easy to use vehicle printer

Ideally suited to route delivery and other Mobile Applications. Ease of use starting with paper loading, done without opening covers, and paper stabilizer guides provide a solid backing for easy location (tractor cover included for harsh environments).

Ribbon Changing and Forms Flexibility

The MIP480 uses a long life 4 mil character ribbon - in typical usage, this means you only have to change ribbons once every three or four months. The MIP480 can handle up to four part continuous forms - it can also print on single top glued forms giving you flexibility for future requirements.

Excellent Print Quality

The 24-wire print head produces clear, crisp output of text and graphics. There's support for IBM® Proprinter® X24e and Epson® ESC/P2 emulations. A variety of resident typefaces ensure fast, high-quality text.

Optional Accessories

Ruggedized brackets, paper input trays and vehicle power cords are also available for the MIP480. Custom hardware can be designed for your fleet if required.

Available Configuration:

MIP48000-AA Standard Model - includes RS232, USB, and Bluetooth

MIP48001-AA Optional Model - includes 802.11b/g plus connectivity of the standard model.

| | |
|------------------------------|--|
| Print Speed | AT 10 cpi: 400 draft, 133 LQ; At 12 cpi: 480 draft, 160 LQ |
| Print Method | Serial impact dot matrix |
| Resolution | 180 x 120 dpi Draft, 180 x 360 dpi LQ, 1 / 360" All-point-addressable |
| Character Density | 10, 12, 15, 17.1, 20, 24 |
| Line Density | 3, 4, 5, 6, 8 |
| Character Modes | Double width , Double height ,Double strike, Italic |
| Character Sets | Code pages 437, 850, 860, 862, 863, 865, 851, 852853, 855, 857, 866, 869, USSR Gost, 864, 437G 920 (Latin-5), 858, 923(Latin-9) |
| Printhead Life | 250 million characters |
| Printhead Type | 24 wire |
| Memory | 64kB |
| Standard Connectivity | RS232, USB 2.0, Bluetooth Ver 1.2 |
| Optional Connectivity | 802.11 b/g wireless ethernet |
| Standard Emulation | IBM 2390+ (includes Pro printer XL24E), ESC/P2, Intermec 6820 |
| Fonts | Draft, Roman, Sans Serif, Courier, Bold, Prestige, Script, Orator, Gothic, OCR-A, OCR-B, Sans Serif H, Roman T; Barcodes: UPC/A, UPC/E, EAN8, EAN13, Code 39, Code 128, Codabar, Interleaved 2 of 5, Industrial 2 of 5 |
| Consumables | 4 million character, re-inking ribbon |
| STD Paper Handling | continuous forms: park, manual paper thickness adjustment; cut sheets: auto-load |
| Number of Copies | original plus three |
| Paper Type | continuous forms, cut sheets |
| Paper Size | Continuous Forms: Width 4" - 10.5" (102-267 mm); Length 4" or more (102+ mm). Cut Sheet: Width 4-10.5" (102-267 mm); Length 3-14.3" (76-364 mm) |
| Physical Weight | 15.4 lbs (6.5 kg) |
| PhysicalSize | 14.2"w x 10.2"h x 4.7"d (36.0cm x 26.0cm x 12.0cm) |
| Power Voltage | AC Adapter: 110 VAC +/- 10%, 240 VAC +/- 10%; Auto Ranging;12-24 VDC |
| Power Frequency | AC Adapter: 47- 63 Hz |
| Compliance | CA C22.2 No. 950; EN60950; GS Mark; UL 746C; CE EMC Directive; E-Mark; ASTM, EC Directives, EU Directives, RoHS |
| Reliability MTBF | 15000 Hours |
| Drivers | Windows XP, 2000 or any operating system containing ESC/P2 |
| Temperature | -4°F to 140°F (-20°C to 60°C); Storage: -22°F to 158°F (-30°C to 70°C) |
| Acoustic | 57 dB(A) |
| Warranty | One Year Return To Depot |



Tally and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice. Copyright © 2009 TallyGenicom, L.P.

Printed Date: 08/07/2009



4500 Daly Drive, Suite 100
Chantilly, VA 20151
T 800.436.4266
www.tallygenicom.com