



FCS-5212 Version: 1

! Power supply unit is to be ordered separately.

GEMINI Fixed IP Network Camera, 6-Megapixel, H.265, 4.3X Optical Zoom, IR LEDs, Indoor/Outdoor

The LevelOne FCS-5212 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP67 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 6-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-5212 should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

Key Features

- 6-Megapixel high-definition resolution
 - Video compression: H.264, H.265, MJPEG
 - Supports 3 video streams simultaneously
 - Supports 4.3X optical zoom
 - Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
 - Weatherproof IP67-rated housing
 - Vandal-proof IK10-rated housing
 - Built-in infrared LEDs for night viewing up to 50m
 - Supports iPhone/Android phone remote viewing over the Internet
-

Specifications

System Specifications

Standards:

TCP(IPv6/v4), UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, SAMBA UPnP, SNMP, Bonjour
IEEE 802.3 10-BASE-T, Ethernet
IEEE 802.3u 100-BASE-TX, Fast Ethernet
IEEE 802.3af Power over Ethernet (PoE)
IEEE 802.1X Network Access Control

Image Sensor:

1/2.9" Progressive Scan CMOS

Lens:

Aut Focus @F1.6, 2.8~12mm Motorized VF LENS

**Port:**

1 x RJ-45 10/100 Mbps PoE port
Power Connector DC JACK
Audio:In/Out
I/O terminal block (1 DI/1 DO)
1 x MicroSDHC/ MicroSDXC card slot

Button/Knob:

Reset

Indicator:

Power

IR Cut Filter:

Removable infrared-cut filter for day & night function

IR LED:

Up to 50 Meter, Wavelength @ 850 nm

Shutter Time:

1/3 s to 1/100,000 s

Angle of View:

Horizontal field of view: 88° to 27°
Vertical field of view: 56° to 18°
Diagonal field of view: 110° to 33°

Pan/Tilt/Zoom:

4.3X Zoom

Video Format:

Main stream: H.265/H.264
Sub-stream: H.265/H.264/MJPEG
Third stream: H.265/H.264

Resolution:

50Hz: 20 fps (3072 × 2048, 3072 × 1728, 2944 × 1656), 25 fps (2560 × 1440, 1920 × 1080, 1280 × 720)
60Hz: 20 fps (3072 × 2048, 3072 × 1728, 2944 × 1656), 30fps (2560 × 1440, 1920 × 1080, 1280 × 720)

Output Video Format:

MPEG4

Audio Compression:

G.711/G.722.1/G.726/MP2L2/PCM

Power Input:

12 VDC ± 25%, PoE (802.3at, class 4), ? 5.5 mm coaxial power plug

Power Consumption:

12 VDC, 1.2A, max. 14.5W
PoE (802.3at, 42.5V to 57V), 0.5A to 0.3A, max. 18W

Data Rate:

Video Bit Rate: 256 Kbps to 16 Mbps
Audio Bit Rate: 64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-192Kbps(MP2L2)

Storage Capacity:

Built-in micro SD/SDHC/SDXC card slot, up to 128 GB

Digital Zoom:

8X

Operating Temperature (°C):

-30 °C to +60 °C (-22 °F to +140 °F)

Operating Humidity (Non-condensing):

95% or less (non-condensing)

Mount:

Working with Mounting accessory:
Ceiling Wall,Corner,Vertical Pole

Features**General:**

Motion Detection, Rotated Mode, Mirror, Color Adjustment (Brightness, Contrast, Saturation), Sharpness Adjustment, Anti-Flicker

PoE:

PoE (802.3af, class 3)

Security:

One-key reset, anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark, IP address filter, File Management,Object Removal Detection

Management:

Event Triggers (Network Disconnected, IP address Conflict, Illegal Login, HDD Full, HDD Error, Alarm Input, Alarm Output, Line Crossing Detection, Intrusion Detection, Face detection)

Video:

Three streams,BLC/3D DNR,120dB WDR

Audio:

1 input (line in/mic.in), 1 output (line out), terminal block, mono sound

Performance**Number of Clients:**

Up to 32 users, 3 levels: Administrator, Operator and User
Simultaneous Live View:Up to 6 channels

Frame Rate (fps):**Main Stream:**

50Hz: 20 fps (3072 × 2048, 3072 × 1728, 2944 × 1656), 25 fps (2560 × 1440, 1920 × 1080, 1280 × 720)

60Hz: 20 fps (3072 × 2048, 3072 × 1728, 2944 × 1656), 30fps (2560 × 1440, 1920 × 1080, 1280 × 720)

Sub-Stream:

50Hz: 25fps (640 × 480, 640 × 360, 320 × 240)

60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)

Third Stream:

50Hz: 25fps (1280 × 720, 640 × 360, 352 × 288)

60Hz: 30fps (1280 × 720, 640 × 360, 352 × 240)

Minimum illumination:

Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR

Physical Specifications**Dimensions (W x D x H mm):**

?144.1 × 332.7 mm (?5.7" × 13.1")

Weight (g):

1893 g (4.2 lb.)

Color:

White

Approval and Compliance



EMI/EMS:

CE/FCC

Environmental Test:

IP67, IK10

Others:

ONVIF (PROFILE S, PROFILE G), ISAPI

Others

Supported Browsers:

IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+

Compatibility:

Windows 7/8/10

Order Information

Package Contents

FCS-5212

Screw Kit

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

Optional Accessory



CAS-7344

Pole Mount Bracket, Clamping Range 2.6"-5"



CAS-7345

Corner Mount Bracket

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.