

## 17" LCD Combo Console

GCL1800



- Integrated KVM console featuring a 17" TFT LCD active matrix monitor , keyboard and touchpad
- 1280 x 1024 resolution on 19" rack mount LCD provides a sharp video display
- Adjustable depth to fit different sizes of racks
- Multi platform OS support - Windows®, Mac, Sun Solaris™ , and Linux®
- Rack mountable in a 19" (1U) system rack
- Custom ASIC provides an auto-sensing function that recognizes the position of each station on the installation
- Fully Supports DDC2B

IOGEAR's new 17" LCD Combo Console offers a space-saving, streamlined approach to IT environments by integrating a keyboard, 17" TFT LCD active matrix monitor, and touchpad in one unit.

The LCD display is built into the cover; the keyboard and touchpad are built into the base. Setup is fast and easy. There is no software to configure, no installation routines and no incompatibility problems. Slide the console module section out; flip the cover up; and you are ready to go to work. When finished, flip the cover down and slide the console module back into the rack.

For further convenience and flexibility, the LCD drawer also supports an external USB mouse port, and an external console ports (keyboard, monitor, and mouse), which allows a second user to take control of the KVM either remotely or locally. (Remote operation requires additional equipment).



## 17" LCD Combo Console



### Product Requirements

#### Computers:

- VGA, SVGA, or MultiSync video graphics card with an HDB-15 port
- PS/2 mouse and keyboard ports (6-pin mini DIN) or 1 USB port

### Package Contents

- 1 x 17" LCD Console
- 1 x USB KVM Cable
- 1 x Firmware Upgrade Cable
- 1 x Rack Mount Kit (Short and Long L Brackets)
- 1 x Grounding Wire
- 1 x Power Cord
- 1 x Installation Guide
- 1 x Warranty Card

# 17" LCD Combo Console

## Specifications

Function	GCL1800	Dimensions	GCL1800
Computer Connections		Unit Dimensions	
Direct	1	Width	19in.
Daisy Chain or Cascading	256	Height	1.75in.
Connectors		Depth	21in.
Second Console Video	1 x HDB-15 Female	Unit Package Dimensions	
Second Console Keyboard	PS/2 or USB	Width	26.75in.
Second Console Mouse	PS/2 or USB	Height	5.5in.
Mouse	1 x USB (External USB Mouse Port)	Depth	28.5in.
Power	1 x 3-Prong AC Socket	Weight	
Console Connectors		Unit Pack Wt.	40.1lb
Flash ROM Upgrade	1 x RJ-11 Female	Unit Wt. w/accessories	30.27lb
CPU Connectors		Unit Wt.	25.94lb
Keyboard, Mouse, and Monitor	1 x SPHD-15 Female		
Switches			
Power	1 x Rocker Switch		
Reset	1 x Semi-recessed Pushbutton		
F/W Upgrade	1 x Switch		
LCD Power	1 x LED Pushbutton (Orange)		
LCD Adjustment	4 x Pushbutton		
LEDs			
Power On	Dark Green		
Emulation			
Keyboard	PS/2, USB		
Mouse	PS/2, USB		
Video Resolution	1280 x 1024 @ 75Hz; DDC2B		
Power Input Rating			
Per AC Power Inlet, 50/60Hz	100~240VAC. 50/60Hz, 1A		
Power Consumption	120V, 29.6W		
Environment			
Operation Temperature	0~40°C		
Storage Temperature	-20~60°C		
Humidity	0~80% RH; Non-condensing		
Housing			
Case	Metal and Plastic		