

### Overview

### HPE OfficeConnect 1910 Switch Series

#### Models

HPE OfficeConnect 1910 24 Switch	JG538A
HPE OfficeConnect 1910 8 Switch	JG536A
HPE OfficeConnect 1910 48 Switch	JG540A
HPE OfficeConnect 1910 8 PoE+ Switch	JG537A
HPE OfficeConnect 1910 24 PoE+ Switch	JG539A

#### Key features

- Customized operation using intuitive Web interface
- Layer 3 static routing with 32 network segments and expansion routes.
- Access control lists for granular security control
- Spanning Tree: STP, RSTP, and MSTP
- Limited Lifetime Warranty

#### Product overview

HPE OfficeConnect 1910 Switch Series consists of advanced smart-managed fixed-configuration Fast Ethernet switches designed for small businesses in an easy-to-administer solution. By utilizing the latest design in silicon technology, this series is one of the most power efficient in the market. The series is part of the OfficeConnect portfolio of Hewlett Packard Enterprise small business networking products.

The series consists of five Fast Ethernet models. The 8- and 24- port models include two dual-personality SFP ports to support fiber connectivity. The 48 port model has 2 dedicated SFP ports plus two 10/100/1000 Ethernet ports. The 8- and 24-port Fast Ethernet models are available with or without PoE.

All models support rack mounting or desktop operation. Customizable features include basic Layer 2 features like VLANs and link aggregation, as well as advanced features such as Layer 3 static routing, IPv6, ACLs, and Spanning Tree Protocols. HPE OfficeConnect 1910 Switch Series includes a Limited Lifetime Warranty. This warranty provides advance hardware replacement with next business day shipment in most countries, limited 24x7 telephone support available from Hewlett Packard Enterprise for the first 90 days, and limited electronic and business hours telephone support is available from HPE for the entire warranty period.

#### Features and benefits

##### Management

- **Simple Web management**  
allows for easy management of the switch- even by nontechnical users- through an intuitive Web GUI; http and secure http (https) is supported
- **Single IP management**  
enables management of up to four HPE OfficeConnect 1910 devices using a single Web interface; simplifies management of multiple devices
- **Secure Web GUI**  
provides a secure, easy-to-use graphical interface for configuring the module via HTTPS
- **SNMPv1, v2c, and v3**  
facilitates management of the switch, as the device can be discovered and monitored from an SNMP management station
- **Complete session logging**  
provides detailed information for problem identification and resolution

## Overview

- **Dual flash images**  
provides independent primary and secondary operating system files for backup while upgrading
- **Port mirroring**  
enables traffic on a port to be simultaneously sent to a network analyzer for monitoring
- **Management security**  
restricts access to critical configuration commands; offers multiple privilege levels with password protection; ACLs provide Telnet and SNMP access; local and remote syslog capabilities allow logging of all access
- **Network Time Protocol (NTP)**  
synchronizes timekeeping among distributed time servers and clients; keeps timekeeping consistent among all clock-dependent devices within the network so that the devices can provide diverse applications based on the consistent time
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP)**  
advertises and receives management information from adjacent devices on a network, facilitating easy mapping by network management applications
- **Limited CLI**  
enables users to quickly deploy and troubleshoot devices in the network
- **RMON**  
provides advanced monitoring and reporting capabilities for statistics, history, alarms, and events
- **Default DHCP client mode**  
allows the switch to be directly connected to a network, enabling plug-and-play operation; in absence of DHCP server on the network, the switch will fallback to a unique static address determined by the MAC address of the switch

## Quality of Service (QoS)

- **Broadcast control**  
allows limitation of broadcast traffic rate to cut down on unwanted network broadcast traffic
- **Rate limiting**  
sets per-port ingress enforced maximums and per-port, per-queue minimums
- **Traffic prioritization**  
provides time-sensitive packets (like VoIP and video) with priority over other traffic based on DSCP or IEEE 802.1p classification; packets are mapped to four hardware queues for more effective throughput

## Connectivity

- **IPv6**
  - **IPv6 host**  
enables switches to be managed and deployed at the IPv6 network's edge
  - **IPv6 routing**  
supports IPv6 static routes
  - **MLD snooping**  
forwards IPv6 multicast traffic to the appropriate interface, preventing traffic flooding
  - **IPv6 ACL/QoS**  
supports ACL and QoS for IPv6 network traffic
- **Auto-MDI/MDIX**  
adjusts automatically for straight-through or crossover cables on all 10/100/1000 ports
- **IEEE 802.3X flow control**  
provides a flow throttling mechanism propagated through the network to prevent packet loss at a congested node
- **IEEE 802.3af Power over Ethernet (PoE) ready**  
provides up to 15.4 W per port to power standards-compliant IP phones, wireless LAN access points, Web cameras, and more (all PoE models)
- **IEEE 802.3at Power over Ethernet (PoE+)**  
provides up to 30 W per port, which allows support of the latest PoE+-capable devices such as IP phones, wireless access points, and security cameras, as well as any IEEE 802.3af-compliant end device; eliminates the cost of additional electrical cabling and circuits that would otherwise be necessary in IP phone and WLAN deployments.
- **Packet storm protection**

## Overview

protects against broadcast, multicast, or unicast storms with user-defined thresholds

- **Cable diagnostics**  
detects cable issues remotely, using a browser-based tool

## Security

- **Advanced access control lists (ACLs)**  
enables network traffic filtering and enhances network control using MAC- and IP-based ACLs; time-based ACLs allow for greater flexibility with managing network access
- **Secure Sockets Layer (SSL)**  
encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch
- **IEEE 802.1X and RADIUS network logins**  
controls port-based access for authentication and accountability
- **Automatic VLAN assignment**  
assigns users automatically to the appropriate VLAN based on their identity, location and time of day
- **STP BPDU port protection**  
blocks Bridge Protocol Data Units (BPDUs) on ports that do not require BPDUs, preventing forged BPDU attacks
- **STP root guard**  
protects the root bridge from malicious attacks or configuration mistake
- **Automatic denial-of-service protection**  
monitors for malicious attacks and protects the network by blocking the attacks
- **Management password**  
provides security so that only authorized access to the Web browser interface is allowed

## Performance

- **Half-/full-duplex auto-negotiating capability on every port**  
doubles the throughput of every port
- **Selectable queue configurations**  
allows for increased performance by selecting the number of queues and associated memory buffering that best meet the requirements of the network applications
- **IGMP snooping**  
improves network performance through multicast filtering, instead of flooding traffic to all ports
- **Fiber uplink**  
provides greater distance connectivity using Gigabit fiber uplinks

## Layer 2 switching

- **VLAN support and tagging**  
supports IEEE 802.1Q (4,094 VLAN IDs) and 256 VLANs simultaneously
- **Spanning Tree Protocol (STP)**  
supports standard IEEE 802.1D STP, IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) for faster convergence, and IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
- **BPDU filtering**  
drops BPDU packets when STP is enabled globally but disabled on a specific port
- **Jumbo frame support**  
supports up to 10 kilobyte frame size to improve the performance of large data transfers

## Layer 3 services

- **Address Resolution Protocol (ARP)**  
determines the MAC address of another IP host in the same subnet; supports static ARPs; gratuitous ARP allows detection of duplicate IP addresses; proxy ARP allows normal ARP operation between subnets or when subnets are separated by a Layer 2 network

## Overview

- **DHCP relay**  
simplifies management of DHCP addresses in networks with multiple subnets

## Layer 3 routing

- **Static IPv4/IPv6 routing**  
provides basic routing (supporting up to 32 static routes and 8 virtual VLAN interfaces); allows manual configuration of routing

## Resiliency and high availability

- **Link aggregation**  
Brings together groups of ports automatically using Link Aggregation Control Protocol (LACP) or, manually, to form an ultra-high-bandwidth connection to the network backbone; helps prevent traffic bottlenecks; (8-port, 24-port and 48-port models support a maximum of 8 ports per trunk; the 8-port models supports 4 trunks; the 24-port model supports 8 trunks; the 48-port model support supports 16 trunks)

## Convergence

- **LLDP-MED (Media Endpoint Discovery)**  
defines a standard extension of LLDP that stores values for parameters such as QoS and VLAN to configure automatically network devices such as IP phones
- **PoE allocations**  
supports multiple methods (automatic, IEEE 802.3af class, LLDP-MED, or user-specified) to allocate PoE power for more efficient energy savings
- **Auto voice VLAN**  
recognizes IP phones and automatically assigns voice traffic to dedicated VLAN for IP phones

## Additional information

- **Green initiative support**  
provides support for RoHS and WEEE regulation
- **Green IT and power**  
improves energy efficiency through the use of the latest advances in silicon development; shuts off unused ports and utilizes variable-speed fans, reducing energy costs

## Warranty and support

- **Limited Lifetime Warranty**  
This series comes with a Limited Lifetime Warranty providing advance hardware replacement with next business day shipment in most countries, 24x7 phone support available for the first 90 days, and electronic and business hours phone support for the entire warranty period. See <http://www.hpe.com/networking/warrantysummary> for full warranty and support information included with your product purchase.

## Configuration

**Build To Order:** BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.

### HPE OfficeConnect 1910 8 Switch

- 8 RJ-45 autosensing 10/100 ports
- 2 SFP dual-personality 1000 Mbps ports
- min=0 \ max=2 SFP Transceivers
- 1U - Height

JG536A  
See Configuration  
**NOTE: 2, 3**

### No Power Cord

- No Localized Power Cord Selected

JG536A#AC3

### HPE OfficeConnect 1910 8 PoE+ Switch

- 8 RJ-45 auto-negotiating 10/100 ports
- 2 SFP dual-personality 1000 Mbps ports
- min=0 \ max=2 SFP Transceivers
- 1U - Height

JG537A  
See Configuration  
**NOTE: 2, 3**

### No Power Cord

- No Localized Power Cord Selected

JG537A#AC3

### HP 1910-8G-PoE+ (65W) Switch

- 8 RJ-45 auto-negotiating 10/100/1000 ports
- 1 SFP 1000 Mbps port
- min=0 \ max=1 SFP Transceiver
- 1U - Height

JG349A  
See Configuration  
**NOTE: 4, 5**

### PDU Cable NA/MEX/TW/JP

- C15 PDU Jumper Cord (NA/MX/TW/JP)

JG349A#B2B

### PDU Cable ROW

- C15 PDU Jumper Cord (ROW)

JG349A#B2C

### HP 1910-8G-PoE+ (180W) Switch

- 8 RJ-45 auto-negotiating 10/100/1000 ports
- 1 SFP 1000 Mbps port
- min=0 \ max=1 SFP Transceiver
- 1U - Height

JG350A  
See Configuration  
**NOTE: 4, 5**

### PDU Cable NA/MEX/TW/JP

- C15 PDU Jumper Cord (NA/MX/TW/JP)

JG350A#B2B

### PDU Cable ROW

- C15 PDU Jumper Cord (ROW)

JG350A#B2C

## Configuration

HP 1910-16G Switch <ul style="list-style-type: none"><li>16 RJ-45 auto-negotiating 10/100/1000 ports</li><li>4 SFP 1000 Mbps ports</li><li>min=0 \ max=4 SFP Transceivers</li><li>1U - Height</li></ul>	JE005A See Configuration <b>NOTE: 1, 5</b>
PDU Cable NA/MEX/TW/JP <ul style="list-style-type: none"><li>C15 PDU Jumper Cord (NA/MX/TW/JP)</li></ul>	JG350A#B2B
PDU Cable ROW <ul style="list-style-type: none"><li>C15 PDU Jumper Cord (ROW)</li></ul>	JG350A#B2C
HP 1910-24G-PoE(170W) Switch <ul style="list-style-type: none"><li>24 RJ-45 auto-negotiating 10/100/1000 ports</li><li>4 SFP 1000 Mbps ports</li><li>min=0 \ max=4 SFP Transceivers</li><li>1U - Height</li></ul>	JE008A See Configuration <b>NOTE: 1, 5</b>
PDU Cable NA/MEX/TW/JP <ul style="list-style-type: none"><li>C15 PDU Jumper Cord (NA/MX/TW/JP)</li></ul>	JE008A#B2B
PDU Cable ROW <ul style="list-style-type: none"><li>C15 PDU Jumper Cord (ROW)</li></ul>	JE008A#B2C
HPE OfficeConnect 1910 24 Switch <ul style="list-style-type: none"><li>24 RJ-45 autosensing 10/100 ports</li><li>2 SFP dual-personality 1000 Mbps ports</li><li>min=0 \ max=2 SFP Transceivers</li><li>1U - Height</li></ul>	JG538A See Configuration <b>NOTE: 2, 3</b>
No Power Cord <ul style="list-style-type: none"><li>No Localized Power Cord Selected</li></ul>	JG538A#AC3
HPE OfficeConnect 1910 24 PoE+ Switch <ul style="list-style-type: none"><li>24 RJ-45 auto-negotiating 10/100 ports</li><li>2 SFP dual-personality 1000 Mbps ports</li><li>min=0 \ max=2 SFP Transceivers</li><li>1U - Height</li></ul>	JG539A See Configuration <b>NOTE: 2, 3, 6</b>
No Power Cord <ul style="list-style-type: none"><li>No Localized Power Cord Selected</li></ul>	JG539A#AC3
HPE OfficeConnect 1910 48 Switch <ul style="list-style-type: none"><li>48 RJ-45 autosensing 10/100 ports</li><li>2 RJ-45 autosensing 10/100/1000 ports</li><li>2 SFP 1000 Mbps ports</li></ul>	JG540A See Configuration <b>NOTE: 2, 3</b>

## Configuration

- min=0 \ max=2 SFP Transceivers
- 1U - Height

No Power Cord

JG540A#AC3

- No Localized Power Cord Selected

### Configuration Rules:

#### Note 1

The following Transceivers install into this switch:

HPE X121 1G SFP LC SX Transceiver	J4858C
HPE X121 1G SFP LC LX Transceiver	J4859C
HPE X121 1G SFP RJ45 T Transceiver	J8177C
HPE X120 1G SFP LC SX Transceiver	JD118B
HPE X120 1G SFP LC LX Transceiver	JD119B
HPE X120 1G SFP RJ45 T Transceiver	JD089B
HPE X125 1G SFP LC LH40 1310nm Transceiver	JD061A
HPE X120 1G SFP LC LH40 1550nm Transceiver	JD062A
HPE X125 1G SFP LC LH70 Transceiver	JD063B
HPE X120 1G SFP LC BX 10-U Transceiver	JD098B
HPE X120 1G SFP LC BX 10-D Transceiver	JD099B

#### Note 2

Localization required. (See Localization Menu for list.)

#### Note 3

The following Transceivers install into this switch:

HPE X121 1G SFP LC SX Transceiver	J4858C
HPE X121 1G SFP LC LX Transceiver	J4859C
HPE X120 1G SFP LC LX Transceiver	JD119B

#### Note 4

The following Transceivers install into this switch:

HPE X121 1G SFP LC SX Transceiver	J4858C
HPE X121 1G SFP LC LX Transceiver	J4859C
HPE X121 1G SFP RJ45 T Transceiver	J8177C
HPE X120 1G SFP LC SX Transceiver	JD118B
HPE X120 1G SFP LC LX Transceiver	JD119B
HPE X120 1G SFP RJ45 T Transceiver	JD089B
HPE X125 1G SFP LC LH40 1310nm Transceiver	JD061A
HPE X120 1G SFP LC LH40 1550nm Transceiver	JD062A
HPE X125 1G SFP LC LH70 Transceiver	JD063B

#### Note 5

Localization (Wall Power Cord) required on orders without #B2B or #B2C (PDU Power Cord). (See Localization Menu)

#### Note 6

CLIC RULE ONLY: #0D1 is not supported on JG538A and JG539A.

## Rack Level Integration CTO Models

## Configuration

HPE OfficeConnect 1910 48 Switch

JG540A

See Configuration

**NOTE: 1, 2**

- 48 RJ-45 autosensing 10/100 ports
- 2 RJ-45 autosensing 10/100/1000 ports
- 2 SFP 1000 Mbps ports
- min=0 \ max=2 SFP Transceivers
- 1U - Height

### Configuration Rules:

**Note 1** CLIC RULE ONLY: #0D1 on JG540A for use with ZU715A only.

**Note 2** #ABA Localization required.

**Remarks:** The Rack Level Integration CTO section above and it's rules are for CLIC Setup at this time. No setup in Watson or QuickSpecs is required at this time.

## Transceivers

### SFP Transceivers

HPE X121 1G SFP LC SX Transceiver	J4858C
HPE X121 1G SFP LC LX Transceiver	J4859C
HPE X121 1G SFP RJ45 T Transceiver	J8177C
HPE X120 1G SFP LC SX Transceiver	JD118B
HPE X120 1G SFP LC LX Transceiver	JD119B
HPE X120 1G SFP RJ45 T Transceiver	JD089B
HPE X120 1G SFP LC BX 10-U Transceiver	JD098B
HPE X120 1G SFP LC BX 10-D Transceiver	JD099B
HPE X125 1G SFP LC LH40 1310nm Transceiver	JD061A
HPE X120 1G SFP LC LH40 1550nm Transceiver	JD062A
HPE X125 1G SFP LC LH70 Transceiver	JD063B

## Internal or External Power Supplies(Model Dependant)

Internal Power supplies Included

### External Redundant Power Supplies

HPE RPS1600 Redundant Power System

JG136A

See Configuration

**NOTE: 2, 3**

- Height = 1U
- includes 1 x c13, 1600w and Power Supply port

HPE RPS1600 1600W AC Power Supply

JG137A

See Configuration

**NOTE: 1, 3**

- Installs into JG136A only



## Configuration

### Configuration Rules:

- Note 1** If this power supply is selected, The JG136A - HPE A-RPS1600 Redundant Power System must be on order or onsite.
- Note 2** Localization required.
- Note 3** Each switch will only support 1 JG136A and 1 JG137A Power supply systems.

### Options for the HPE 1600 External RPS Power Supply

HPE X290 1000 A JD5 2m RPS Cable JD187A

**Remark:** These cables are used to connect the External Power System to Switch.

## Cables

### Multi-Mode Cables

HPE LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable	AJ833A
HPE LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable	AJ834A
HPE LC to LC Multi-mode OM3 2-Fiber 2.0m 1-Pack Fiber Optic Cable	AJ835A
HPE LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable	AJ836A
HPE LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable	AJ837A
HPE LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable	AJ838A
HPE LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable	AJ839A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable	QK732A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable	QK733A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable	QK734A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable	QK735A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable	QK736A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable	QK737A

## Technical Specifications

### HPE OfficeConnect 1910 24 Switch (JG538A)

Ports	24 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full 2 dual-personality ports; each port can be used as a RJ 45 10/100/1000 Mbps port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) or as a SFP 100/1000 Mbps slot (IEEE 802.3u Type 100BASE-FX, IEEE 802.3z Type 1000BASE-X) 1 RJ-45 console port to access limited CLI port Supports a maximum of 24 autosensing 10/100 ports plus 2 dual-personality ports either RJ-45 10/100/1000 port or SFP 100/1000 slot	
Physical characteristics	Dimensions	17.32(w) x 6.81(d) x 1.73(h) in (44 x 17.3 x 4.4 cm) (1U height)
	Weight	4.85 lb (2.2 kg)
Memory and processor	Module	MIPS @ 500 MHz, 32 MB flash, 128 MB RAM; packet buffer size: 512 KB
Mounting and enclosure	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)	
Performance	100 Mb Latency	< 5 μs
	1000 Mb Latency	< 5 μs
	Throughput	up to 6.6 Mpps (64-byte packets)
	Routing/Switching capacity	8.8 Gb/s
	Routing table size	32 entries (IPv4), 32 entries (IPv6)
	MAC address table size	8192 entries
Environment	Operating temperature	32°F to 104°F (0°C to 40°C)
	Operating relative humidity	10% to 90%, noncondensing
	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Non-operating/Storage relative humidity	10% to 95%, noncondensing
Electrical characteristics	Frequency	50/60 Hz
	Voltage	100 - 240 VAC, rated
	Maximum power rating	12 W
	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	
Safety	IEC 60950-1; EN 60950-1; UL 60950-1 2nd Edition; CSA C22.2 No. 60950-1-07 2nd Edition	
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A	
Management	IMC - Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB	
Notes	SFP ports and copper ports can work simultaneously, independent of each other to give a total of 28 Gigabit-capable ports.	
Services	Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office	

### HPE OfficeConnect 1910 8 Switch (JG536A)

<b>Ports</b>	8 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type
--------------	--

## Technical Specifications

	100BASE-TX); Duplex: half or full 2 dual-personality ports; each port can be used as a RJ 45 10/100/1000 Mbps port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) or as a SFP 100/1000 Mbps slot (IEEE 802.3u Type 100BASE-FX, IEEE 802.3z Type 1000BASE-X) 1 RJ-45 console port to access limited CLI port Supports a maximum of 8 autosensing 10/100 ports plus 2 dual-personality ports either RJ-45 10/100/1000 port or SFP 100/1000 slot	
<b>Physical characteristics</b>	<b>Dimensions</b>	10.47(w) x 6.38(d) x 1.73(h) in (26.6 x 16.2 x 4.4 cm) (1U height)
	<b>Weight</b>	2.2 lb (1 kg)
<b>Memory and processor</b>	<b>Module</b>	MIPS @ 500 MHz, 32 MB flash, 128 MB RAM; packet buffer size: 512 KB
<b>Mounting and enclosure</b>	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)	
<b>Performance</b>	<b>100 Mb Latency</b>	< 5 $\mu$ s
	<b>1000 Mb Latency</b>	< 5 $\mu$ s
	<b>Throughput</b>	up to 4.2 Mpps (64-byte packets)
	<b>Routing/Switching capacity</b>	5.6 Gb/s
	<b>Routing table size</b>	32 entries (IPv4), 32 entries (IPv6)
	<b>MAC address table size</b>	8192 entries
	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)
<b>Environment</b>	<b>Operating relative humidity</b>	10% to 90%, noncondensing
	<b>Non-operating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Non-operating/Storage relative humidity</b>	10% to 95%, noncondensing
<b>Electrical characteristics</b>	<b>Frequency</b>	50/60 Hz
	<b>Voltage</b>	100 - 240 VAC, rated
	<b>Maximum power rating</b>	8 W
	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	
<b>Safety</b>	IEC 60950-1; EN 60950-1; UL 60950-1 2nd Edition; CSA C22.2 No. 60950-1-07 2nd Edition	
<b>Emissions</b>	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A	
<b>Management</b>	IMC - Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB	
<b>Notes</b>	SFP ports and copper ports can work simultaneously, independent of each other to give a total of 28 Gigabit-capable ports.	
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office	

### HPE OfficeConnect 1910 48 Switch (JG540A)

<b>Ports</b>	48 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
	2 SFP 100/1000 Mbps slots (IEEE 802.3u Type 100BASE-FX, IEEE 802.3z Type 1000BASE-X)
	2 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full;

## Technical Specifications

	1000BASE-T: full only 1 RJ-45 console port to access limited CLI port Supports a maximum of 48 autosensing 10/100 ports plus 2 autosensing 10/100/1000 ports plus 2 SFP 100/1000 slots	
<b>Physical characteristics</b>	<b>Dimensions</b>	17.32(w) x 6.81(d) x 1.73(h) in (44 x 17.3 x 4.4 cm) (1U height)
	<b>Weight</b>	5.07 lb (2.3 kg)
<b>Memory and processor</b>	<b>Module</b>	MIPS @ 500 MHz, 32 MB flash, 128 MB RAM; packet buffer size: 1.5 MB
<b>Mounting and enclosure</b>	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)	
<b>Performance</b>	<b>100 Mb Latency</b>	< 5 $\mu$ s
	<b>1000 Mb Latency</b>	< 5 $\mu$ s
	<b>Throughput</b>	up to 13.1 Mpps (64-byte packets)
	<b>Routing/Switching capacity</b>	17.6 Gb/s
	<b>Routing table size</b>	32 entries (IPv4), 32 entries (IPv6)
	<b>MAC address table size</b>	8192 entries
	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)
<b>Environment</b>	<b>Operating relative humidity</b>	10% to 90%, noncondensing
	<b>Non-operating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Non-operating/Storage relative humidity</b>	10% to 95%, noncondensing
<b>Electrical characteristics</b>	<b>Frequency</b>	50/60 Hz
	<b>Voltage</b>	100 - 240 VAC, rated
	<b>Maximum power rating</b>	22 W
	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	
<b>Safety</b>	IEC 60950-1; EN 60950-1; UL 60950-1 2nd Edition; CSA C22.2 No. 60950-1-07 2nd Edition	
<b>Emissions</b>	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A	
<b>Management</b>	IMC - Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB	
<b>Notes</b>	SFP ports and copper ports can work simultaneously, independent of each other to give a total of 28 Gigabit-capable ports.	
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office	

### HPE OfficeConnect 1910 8 PoE+ Switch (JG537A)

<b>Ports</b>	8 RJ-45 autosensing 10/100 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3at PoE+); Duplex: half or full	
	2 dual-personality ports; each port can be used as a RJ 45 10/100/1000 Mbps port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) or as a SFP 100/1000 Mbps slot (IEEE 802.3u Type 100BASE-FX, IEEE 802.3z Type 1000BASE-X)	
	1 RJ-45 console port to access limited CLI port	
	Supports a maximum of 8 autosensing 10/100 ports plus 2 dual-personality ports either RJ-45 10/100/1000 port or SFP 100/1000 slot	

## Technical Specifications

<b>Physical characteristics</b>	<b>Dimensions</b>	12.99(w) x 9.06(d) x 1.73(h) in (33 x 23 x 4.4 cm) (1U height)
	<b>Weight</b>	4.63 lb (2.1 kg)
<b>Memory and processor</b>	<b>Module</b>	MIPS @ 500 MHz, 32 MB flash, 128 MB RAM; packet buffer size: 512 KB
<b>Mounting and enclosure</b>	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)	
<b>Performance</b>	<b>100 Mb Latency</b>	< 5 $\mu$ s
	<b>1000 Mb Latency</b>	< 5 $\mu$ s
	<b>Throughput</b>	up to 4.2 Mpps (64-byte packets)
	<b>Routing/Switching capacity</b>	5.6 Gb/s
	<b>Routing table size</b>	32 entries (IPv4), 32 entries (IPv6)
	<b>MAC address table size</b>	8192 entries
	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)
<b>Environment</b>	<b>Operating relative humidity</b>	10% to 90%, noncondensing
	<b>Non-operating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Non-operating/Storage relative humidity</b>	10% to 95%, noncondensing
<b>Electrical characteristics</b>	<b>Frequency</b>	50/60 Hz
	<b>Voltage</b>	100 - 240 VAC, rated
	<b>Maximum power rating</b>	90 W
	<b>PoE power</b>	62 W
<b>Safety</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	
	PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of an External Power Supply (EPS).	
	IEC 60950-1; EN 60950-1; UL 60950-1 2nd Edition; CSA C22.2 No. 60950-1-07 2nd Edition	
<b>Emissions</b>	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A	
<b>Management</b>	IMC - Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB	
<b>Notes</b>	SFP ports and copper ports can work simultaneously, independent of each other to give a total of 28 Gigabit-capable ports.	
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office	

### HPE OfficeConnect 1910 24 PoE+ Switch (JG539A)

<b>Ports</b>	24 RJ-45 autosensing 10/100 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3at PoE+); Duplex: half or full	
	2 dual-personality ports; each port can be used as a RJ 45 10/100/1000 Mbps port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) or as a SFP 100/1000 Mbps slot (IEEE 802.3u Type 100BASE-FX, IEEE 802.3z Type 1000BASE-X)	
	1 RJ-45 console port to access limited CLI port	
	Supports a maximum of 24 autosensing 10/100 ports plus 2 dual-personality ports either RJ-45 10/100/1000 port or SFP 100/1000 slot	
	<b>Physical characteristics</b>	<b>Dimensions</b> 17.32(w) x 9.37(d) x 1.73(h) in (44 x 23.8 x 4.4 cm) (1U height)

## Technical Specifications

	<b>Weight</b>	7.28 lb (3.3 kg)
<b>Memory and processor</b>	<b>Module</b>	MIPS @ 500 MHz, 32 MB flash, 128 MB RAM; packet buffer size: 512 KB
<b>Mounting and enclosure</b>	Mounts in an EIA-standard	19 in. telco rack or equipment cabinet (hardware included)
<b>Performance</b>	<b>100 Mb Latency</b>	< 5 $\mu$ s
	<b>1000 Mb Latency</b>	< 5 $\mu$ s
	<b>Throughput</b>	up to 6.6 Mpps (64-byte packets)
	<b>Routing/Switching capacity</b>	8.8 Gb/s
	<b>Routing table size</b>	32 entries (IPv4), 32 entries (IPv6)
	<b>MAC address table size</b>	8192 entries
<b>Environment</b>	<b>Operating temperature</b>	32°F to 104°F (0°C to 40°C)
	<b>Operating relative humidity</b>	10% to 90%, non-condensing
	<b>Non-operating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Non-operating/Storage relative humidity</b>	10% to 95%, noncondensing
<b>Electrical characteristics</b>	<b>Frequency</b>	50/60 Hz
	<b>Voltage</b>	100 - 240 VAC, rated
	<b>Maximum power rating</b>	220 W
	<b>PoE power</b>	180 W
	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	
	PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of an External Power Supply (EPS).	
<b>Safety</b>	IEC 60950-1; EN 60950-1; UL 60950-1 2nd Edition; CSA C22.2 No. 60950-1-07 2nd Edition	
<b>Emissions</b>	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A	
<b>Management</b>	IMC - Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB	
<b>Notes</b>	SFP ports and copper ports can work simultaneously, independent of each other to give a total of 28 Gigabit-capable ports.	
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office	

### Standards and protocols Device management

(applies to all products in series)

RFC 2819 RMON

#### General protocols

IEEE 802.1D MAC Bridges  
 IEEE 802.1p Priority  
 IEEE 802.1Q VLANs  
 IEEE 802.1s (MSTP)  
 IEEE 802.1w Rapid Reconfiguration of Spanning Tree  
 IEEE 802.3 Type 10BASE-T  
 IEEE 802.3ab 1000BASE-T  
 IEEE 802.3ad Link Aggregation Control Protocol (LACP)

## Technical Specifications

IEEE 802.3i 10BASE-T  
IEEE 802.3x Flow Control  
IEEE 802.3z 1000BASE-X

### MIBs

RFC 1213 MIB II  
RFC 1493 Bridge MIB  
RFC 2021 RMONv2 MIB  
RFC 2233 Interface MIB  
RFC 2233 Interfaces MIB  
RFC 2571 SNMP Framework MIB  
RFC 2572 SNMP-MPD MIB  
RFC 2573 SNMP-Notification MIB  
RFC 2573 SNMP-Target MIB  
RFC 2613 SMON MIB  
RFC 2618 RADIUS Client MIB  
RFC 2620 RADIUS Accounting MIB  
RFC 2665 Ethernet-Like-MIB  
RFC 2667 IP Tunnel MIB  
RFC 2668 802.3 MAU MIB  
RFC 2674 802.1p and IEEE 802.1Q Bridge MIB  
RFC 2737 Entity MIB (Version 2)  
RFC 3414 SNMP-User based-SM MIB  
RFC 3415 SNMP-View based-ACM MIB  
RFC 3418 MIB for SNMPv3

### Network management

IEEE 802.1AB Link Layer Discovery Protocol (LLDP)  
IEEE 802.1D (STP)  
RFC 1215 SNMP Generic traps

### QoS/Cos

IEEE 802.1p (CoS)

### Security

IEEE 802.1X Port Based Network Access Control

## Accessories

### HPE OfficeConnect 1910 Transceivers

<b>Switch Series accessories</b>	HPE X121 1G SFP LC SX Transceiver	J4858C
	HPE X121 1G SFP LC LX Transceiver	J4859C
	HPE X121 1G SFP RJ45 T Transceiver	J8177C
	HPE X120 1G SFP LC SX Transceiver	JD118B
	HPE X120 1G SFP LC LX Transceiver	JD119B
	HPE X110 100M SFP LC LX Transceiver	JD120B
	HPE X120 1G SFP RJ45 T Transceiver	JD089B

### Cables

HPE LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable	AJ833A
HPE LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable	AJ834A
HPE LC to LC Multi-mode OM3 2-Fiber 2.0m 1-Pack Fiber Optic Cable	AJ835A
HPE LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable	AJ836A
HPE LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable	AJ837A
HPE LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable	AJ838A
HPE LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable	AJ839A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable	QK732A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable	QK733A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable	QK734A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable	QK735A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable	QK736A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable	QK737A



## Accessory Product Details

**NOTE:** Details are not available for all accessories. The following specifications were available at the time of publication.

<b>HPE X121 1G SFP LC SX Transceiver</b> (J4858C)  A small form-factor pluggable (SFP) Gigabit SX transceiver that provides a full-duplex Gigabit solution up to 550 m on multimode fiber.	<b>Ports</b>	1 LC 1000BASE-SX port; Duplex: full only
	<b>Physical characteristics</b>	Dimensions: 2.24(d) x 0.54(w) x 0.48(h) in. (5.69 x 1.37 x 1.22 cm) Weight: 0.04 lb. (0.02 kg) Transceiver form factor: SFP
	<b>Environment</b>	Operating temperature: 32°F to 158°F (0°C to 70°C) Operating relative humidity: 5% to 85%, noncondensing Nonoperating/Storage temperature: -40°F to 203°F (-40°C to 85°C) Altitude: up to 10,000 ft. (3 km)
	<b>Electrical characteristics</b>	Power consumption typical: 0.4 W Power consumption maximum: 0.7 W
	<b>Cabling</b>	Type: <ul style="list-style-type: none"> <li>62.5/125 <math>\mu</math>m or 50/125 <math>\mu</math>m (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively;</li> </ul> Maximum distance: <ul style="list-style-type: none"> <li>2-220 m (62.5 <math>\mu</math>m core diameter, 160 MHz*km bandwidth)</li> <li>2-275 m (62.5 <math>\mu</math>m core diameter, 200 MHz*km bandwidth)</li> <li>2-500 m (50 <math>\mu</math>m core diameter, 400 MHz*km bandwidth)</li> <li>2-550 m (50 <math>\mu</math>m core diameter, 500 MHz*km bandwidth)</li> </ul> Cable length: 2-550m Fiber type: Multi Mode
	<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office
<b>HPE X121 1G SFP LC LX Transceiver</b> (J4859C)  HP X121 1G SFP LC LX Transceiver: An SFP format gigabit transceiver with LC connectors using LX technology.	<b>Ports</b>	1 LC 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX); Duplex: full only
	<b>Physical characteristics</b>	Dimensions: 2.24(d) x 0.54(w) x 0.486(h) in. (5.69 x 1.37 x 1.23 cm) Weight: 0.04 lb. (0.02 kg)
	<b>Environment</b>	Operating temperature: 32°F to 158°F (0°C to 70°C) Operating relative humidity: 0% to 85%, noncondensing Nonoperating/Storage temperature: -40°F to 212°F (-40°C to 100°C) Altitude: up to 10,000 ft. (3 km)
	<b>Cabling</b>	Type: <ul style="list-style-type: none"> <li>Either single mode or multimode; 62.5/125 <math>\mu</math>m or 50/125 <math>\mu</math>m (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively; Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2</li> </ul>

## Accessory Product Details

Type B1;

Maximum distance:

- 2-550 m (multimode 62.5  $\mu$ m core diameter, 500 MHz\*km bandwidth)
- 2-550 m (multimode 50  $\mu$ m core diameter, 400 MHz\*km bandwidth)
- 2-550 m (multimode 50  $\mu$ m core diameter, 500 MHz\*km bandwidth)
- 2-10,000 m (single-mode fiber)

### Notes

A mode conditioning patch cord may be needed in some multimode fiber installations.

Wavelength: 1310nm

Power Consumption: < 500mW Typical

### Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

### HPE X121 1G SFP RJ45 T Transceiver (J8177C)

HP X121 1G SFP RJ45 T Transceiver: An SFP format gigabit transceiver with RJ45 connectors using 1000BaseT technology.

### Ports

1 RJ-45 1000BASE-T port (IEEE 802.3ab Type 1000BASE-T); Duplex: full only

### Physical characteristics

Dimensions: 2.71(d) x 0.54(w) x 0.55(h) in. (6.88 x 1.37 x 1.4 cm)  
Weight: 0.06 lb. (0.03 kg)

### Environment

Operating temperature: 32°F to 158°F (0°C to 70°C); with 100 LFM airflow over the SFP module  
Operating relative humidity: 0% to 95% @ 75°F (25°C), noncondensing  
Nonoperating/Storage temperature: -40°F to 185°F (-40°C to 85°C)  
Nonoperating/Storage relative humidity: 0% to 95% @ 77°F (25°C), noncondensing  
Altitude: up to 10,000 ft. (3000 km)

### Cabling

Cable type:  
1000BASE-T: Category 5 (5E or better recommended), 100  $\Omega$  differential 4-pair unshielded twisted pair (UTP) or shielded twisted pair (STP) balanced, complying with IEEE 802.3ab 1000BASE-T;

Maximum distance:

- 100 m

### Notes

Power consumption is nominally 1 watt.

For supported platforms and minimum software requirements to support this product, see the document titled "Support for the J8177C 1000Base-T Mini-GBIC" on the "HP Mini-GBICs and SFPs" Manuals Web page. The J8177C Gigabit copper mini-GBIC is not supported on dual-personality ports.

The J8177C is capable of 100 Mb operation. This is supported on only the HP E8200zl, E5400zl, and HP E6200-24G-mGBIC yl Switches using

## Accessory Product Details

software version K.12.21 or later. Use the "auto-100" port setting to enable 100 Mb operation.

Important: The earlier J8177B does not support 100 Mb operation. When used in the Switch gl 20-Port 10/100/1000 Module (J4908A), the J8177C mini-GBIC can be installed in either the upper or lower mini-GBIC port, but will block access to the other port.

### Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

<b>HPE X120 1G SFP LC SX Transceiver (JD118B)</b>  A small form-factor pluggable (SFP) Gigabit SX transceiver that provides a full-duplex Gigabit solution up to 550m on a Multimode fiber.	<b>Ports</b>	1 LC 1000BASE-SX port	
	<b>Connectivity</b>	<b>Connector type</b>	LC
	<b>Physical characteristics</b>	<b>Wavelength</b>	850 nm
		<b>Dimensions</b>	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
	<b>Electrical characteristics</b>	<b>Full configuration weight</b>	0.04 lb. (0.02 kg)
		<b>Power consumption typical</b>	0.8 W
		<b>Power consumption maximum</b>	1.0 W
	<b>Cabling</b>	Maximum distance: <ul style="list-style-type: none"> <li>• FDDI Grade distance = 220m</li> <li>• OM1 = 275m</li> <li>• OM2 = 500m</li> <li>• OM3 = Not Specified by standard</li> </ul> Cable length up to 550m Fiber type Multi Mode	
	<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office	

<b>HPE X120 1G SFP LC LX Transceiver (JD119B)</b>  A small form-factor pluggable (SFP) Gigabit LX transceiver that provides a full duplex Gigabit solution up to 550m on MMF or 10Km on SMF	<b>Ports</b>	1 SFP 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX)	
	<b>Connectivity</b>	<b>Connector type</b>	LC
	<b>Physical characteristics</b>	<b>Wavelength</b>	1300 nm
		<b>Dimensions</b>	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
	<b>Electrical characteristics</b>	<b>Full configuration weight</b>	0.04 lb. (0.02 kg)
		<b>Power consumption typical</b>	0.8 W
		<b>Power consumption maximum</b>	1.0 W
	<b>Cabling</b>	Cable type: Either single mode or multimode;  Maximum distance: <ul style="list-style-type: none"> <li>• 550m for Multimode</li> </ul>	

## Accessory Product Details

		<ul style="list-style-type: none"> <li>• 10km for Singlemode</li> </ul>
		Fiber type Both
<b>Services</b>		Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office
<b>HPE X120 1G SFP RJ45 T Transceiver</b> (JD089B)	<b>Ports</b>	1 RJ-45 1000BASE-T port (IEEE 802.3ab Type 1000BASE-T)
	<b>Connectivity</b>	<b>Connector type</b> RJ-45
	<b>Physical characteristics</b>	<b>Dimensions</b> 2.71(d) x 0.54(w) x 0.55(h) in. (6.88 x 1.37 x 1.4 cm)
		<b>Full configuration weight</b> 0.07 lb. (0.03 kg)
		<b>Power consumption typical</b> 0.8 W
	<b>Electrical characteristics</b>	<b>Power consumption maximum</b> 1.0 W
	<b>Cabling</b>	Cable type: 1000BASE-T: Category 5 (5E or better recommended), 100 Ω differential 4-pair unshielded twisted pair (UTP) or shielded twisted pair (STP) balanced, complying with IEEE 802.3ab 1000BASE-T
		Maximum distance: <ul style="list-style-type: none"> <li>• 100m</li> </ul>
<b>Services</b>		Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office
<b>HPE LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable</b> (AJ833A)	<b>Cabling</b>	<b>Cable type:</b> 50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m
	<b>Notes</b>	<b>Maximum distance:</b> 10Gbps Transfer Rate (Ethernet): 300m  Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end. <ul style="list-style-type: none"> <li>• Dimensions: Core diameter: 50 ± 3.0μm Cladding diameter: 125 ± 2.0μm Coating diameter: 245 ± 10μm</li> <li>• Optical glass: Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.</li> <li>• Optical glass: Bandwidth: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.</li> <li>• CABLE: The cable is duplex zipcord graded index 50/125μm multimode optical fiber and designed to work in both the 850 and 1300 nm wavelength windows.</li> <li>• BULK CABLE &amp; CABLE ASSEMBLY CONFIGURATION:</li> <li>• Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.</li> <li>• Jacket Color: Aqua for OM3 multimode per TIA 598</li> <li>• Boot Color: White</li> </ul>

## Accessory Product Details

- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

### Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

**HPE LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable**  
(AJ834A)

### Cabling

#### Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m

#### Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

### Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0µm Cladding diameter: 125 ± 2.0µm Coating diameter: 245 ± 10µm
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125µm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

### Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

**HPE LC to LC Multi-mode OM3 2-Fiber 2.0m 1-Pack Fiber Optic Cable**

### Cabling

#### Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for

## Accessory Product Details

(AJ835A)

distances of up to 300 m;

### Notes

#### Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125  $\mu$ m fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50  $\pm$  3.0 $\mu$ m Cladding diameter: 125  $\pm$  2.0 $\mu$ m Coating diameter: 245  $\pm$  10 $\mu$ m
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 $\mu$ m multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

### Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

**HPE LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable**  
(AJ836A)

### Cabling

#### Cable type:

50/125  $\mu$ m core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

### Notes

#### Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Cable Specs: This specification defines the detail requirements for a tight buffered duplex fiber optic multimode OM3 50/125  $\mu$ m fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50  $\pm$  3.0 $\mu$ m Cladding diameter: 125  $\pm$  2.0 $\mu$ m Coating diameter: 245  $\pm$  10 $\mu$ m
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.

Accessory Product Details

- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

HPE LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable (AJ837A)

Cabling

**Cable type:**  
50/125 μm (core/cladding) diameter, mulitimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

**Maximum distance:**  
10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 um fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0um Cladding diameter: 125 ± 2.0um Coating diameter: 245 ± 10um
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level

## Accessory Product Details

descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

<b>HPE LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable (AJ838A)</b>	<b>Cabling</b>	<p><b>Cable type:</b> 50/125 <math>\mu</math>m (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;</p>
	<b>Notes</b>	<p><b>Maximum distance:</b> 10Gbps Transfer Rate (Ethernet): 300m</p> <p>Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 <math>\mu</math>m fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.</p> <ul style="list-style-type: none"> <li>• Dimensions: Core diameter: 50 <math>\pm</math> 3.0<math>\mu</math>m Cladding diameter: 125 <math>\pm</math> 2.0<math>\mu</math>m Coating diameter: 245 <math>\pm</math> 10<math>\mu</math>m</li> <li>• Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.</li> <li>• Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.</li> <li>• CABLE: The cable is duplex zipcord graded index 50/125<math>\mu</math>m multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.</li> <li>• BULK CABLE &amp; CABLE ASSEMBLY CONFIGURATION:</li> <li>• Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.</li> <li>• Jacket Color: Aqua for OM3 multimode per TIA 598</li> <li>• Boot Color: White</li> <li>• Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths &gt; 30 meters.</li> <li>• Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.</li> <li>• Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg</li> </ul>
	<b>Services</b>	<p>Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office</p>
<b>HPE LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable (AJ839A)</b>	<b>Cabling</b>	<p><b>Cable type:</b> 50/125 <math>\mu</math>m (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;</p>
	<b>Notes</b>	<p><b>Maximum distance:</b> 10Gbps Transfer Rate (Ethernet): 300m</p> <p>Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 <math>\mu</math>m fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.</p> <ul style="list-style-type: none"> <li>• Dimensions: Core diameter: 50 <math>\pm</math> 3.0<math>\mu</math>m Cladding diameter: 125 <math>\pm</math></li> </ul>



Accessory Product Details

- 2.0um Coating diameter: 245 ± 10um
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable (QK732A)Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core Diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the Hewlett Packard Enterprise website at <http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable (QK733A)Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating

## Accessory Product Details

diameter: 245 ± 10um

- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

### Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

### HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable (QK734A) Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

### Services

Refer to the Hewlett Packard Enterprise website at

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

### HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable (QK735A) Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um,

## Accessory Product Details

	<p>Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.</p> <ul style="list-style-type: none"> <li>• Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths &gt;30m</li> <li>• Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45</li> </ul> <p><b>Services</b></p> <p>Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office</p>
--	---

### HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable (QK736A) Notes

	<p>Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.</p> <ul style="list-style-type: none"> <li>• Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um</li> <li>• Bandwidth: 3000 MHz-km @ 850nm (Laser)</li> <li>• Jacket Color: Blue</li> <li>• Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic</li> <li>• Boot Color: White</li> <li>• Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.</li> <li>• Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths &gt;30m</li> <li>• Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45</li> </ul> <p><b>Services</b></p> <p>Refer to the Hewlett Packard Enterprise website at <a href="http://www.hpe.com/networking/services">http://www.hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office</p>
--	---

### HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable (QK737A) Notes

	<p>Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.</p> <ul style="list-style-type: none"> <li>• Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um</li> <li>• Bandwidth: 3000 MHz-km @ 850nm (Laser)</li> <li>• Jacket Color: Blue</li> <li>• Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic</li> <li>• Boot Color: White</li> <li>• Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.</li> <li>• Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths &gt;30m</li> <li>• Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45</li> </ul> <p><b>Services</b></p> <p>Refer to the Hewlett Packard Enterprise website at</p>
--	--

## Accessory Product Details

<http://www.hpe.com/networking/services> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office

---

## Summary of Changes

Date	Version History	Action	Description of Change:
23-Sep-2016	From Version 18 to 19	Added	SKU JD120B added to Accessories
01-Aug-2016	From Version 17 to 18	Changed	Adding #AC3 Option on Configuration section. Updates made on Overview and Technical Specifications
06-May-2016	From Version 16 to 17	Changed	Document name changed to HPE OfficeConnect Switch Series. Overview, Features and Benefits, Technical Specifications updated.
18-Mar-2016	From Version 15 to 16	Changed	Version updated to change Concentra ID from c03824531 to c05051651
01-Dec-2015	From Version 14 to 15	Changed	Overview, Features and Benefits and Technical Specifications updated.
01-Dec-2014	From Version 12 to 14	Changed	Updated Warranty and support and Product Overview
25-Feb-2014	From Version 11 to 12	Changed	Internal and External Power Supplies, Transceivers, and Cables were revised.
09-Dec-2013	From Version 10 to 11	Changed	Configuration was revised.
09-Oct-2013	From Version 9 to 10	Removed	HP X124 1G SFP LC SX and HP X124 1G SFP LC LX Transceivers were removed.
11-Sep-2013	From Version 8 to 9	Added	Configuration was added.
10-Jun-2013	From Version 7 to 8	Added	OM4 cables were added.
14-May-2012	From Version 6 to 7	Changed	Features and Benefits were updated. The product description and Key Features were also updated. 3 new models were added.
26-Sep-2011	From Version 4 to 6	Changed	The QuickSpecs was completely revised, including changing the title.
20-Jun-2011	From Version 2 to 4	Changed	Features and Benefits were updated. The product description and Key Features were also updated
20-Oct-2010	From Version 1 to 2	Changed	Features and Benefits were reorganized and updated Layer 3 routing. Ports, Notes, Services note and General Protocols were revised throughout Models PremierFlex Cables were added

## Summary of Changes



**Sign up for updates**



**Hewlett Packard  
Enterprise**

© Copyright 2016 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

To learn more, visit: <http://www.hpe.com/networking>

c05051651 - 13677 - Worldwide - V19 - 23-September-2016