

XDS-1078-A9

Advanced 10.1" Interactive Room Panel

Industry's First Android 9.0 Meeting Room Panel — Highly Responsive & Secure



Android 9
By Google

Latest OS from Google. Continuous security updates for reliability



PoE+ / PoE

Minimalist installation keeps workplaces simple & modern



2.8 cm Slim Design

Built-in zero-gap flush for secure, versatile mounting




High Visibility Status Light

Elegant light bars with soft illumination that is easy on the eyes



Orientation Aware

Easy to integrate into workplace design in portrait and landscape



High Performance Processor

Powers smooth, responsive, and vibrant user experience



10-Point Multi-Touch

Quick check-in/out or book room at-the-door. Zoom and scroll for easy browsing



Remote Device Management

Easily manage, monitor & troubleshoot all in-service room panels

Technical Specifications

Display

- 10.1" LCD panel
- 10 points capacitive multi-touch
- 300 nits maximum brightness
- 1280 x 800 panel resolution
- Viewing angle (H / V): 170 / 170
- 6 primary colors LED bar x 2

HTML5 Support

- Widgets for calendar, clock, news, and web page integration
- HTML5 technologies including CSS and Javascript
- Chromium-based browser engine, same as Google Chrome™

Optional Accessories

- PGM-001 Glass Mount Solution
- PTM-101 Tilt Wall Mount
- PVK-102 Pivot Table Stand
- PWM-011 & PWM-041 Premium Window Mount
- Table stand
- Adapter
- Power plug

Video Format Supported

- H.264/AVC up to 1080p (1920 x 1080)
- H.265/HEVC up to 1080p (1920 x 1080)
- MPEG-4 up to 1080p (1920 x 1080)
- MPEG-2 up to 1080p (1920 x 1080)
- MPEG-1 up to 1080p (1920 x 1080)
- VC-1 up to 1080p (1920 x 1080)

Advanced Signage Features

- Remote commissioning
- AlwaysOn, AppLock to prevent unauthorized access
- StrongCache for continuous playback even when network is not available
- Multi-zone screen layout, transparent PNG overlay, and graphical scrolling ticker
- Auto-play starts playing scheduled contents automatically when power is re-established
- Automatic error recovery with built-in WDT
- Real-time clock with backup clock battery

Power Requirement

- Input: 100 - 240 V, 50 - 60 Hz
- Output: 12 V, 1.5 A
- UL / CB certified power supplies
- Interchangeable connector system includes US plugs (optional for EU, UK, and AUS plugs)
- IEEE 802.3at Power-over-Ethernet (PoE+) / Eco mode on IEEE 802.3af Power-over-Ethernet (PoE)

Image Format Supported

- JPEG up to 1920 x 1080
- PNG up to 1920 x 1080

Environmental

- Operating temperature: 0 to 40 °C
- Humidity: 10 to 85 % @ 40 °C non-condensing

Audio Format Supported

- MP3 up to 320 kbps

Connectivity

- Wi-Fi: 802.11 b/g/n
- Micro USB for ADB
- Ethernet RJ45: 10/100 BASE-T
- USB 2.0 x 2
- Built-in 1 W stereo speakers x 2
- 3.5 mm analog stereo audio out
- Optional 3G / 4G mobile module via USB
- Micro SD card slot, memory expendable to 16 GB / 32 GB / 64 GB (card replaces internal storage)

Dimensions for Product & Package

- Display size: 269.88 mm x 170.77 mm x 28.5 mm (10.62" x 16.72" x 1.12")
- Display weight: 727 g (1.6 lbs)
- Individual package size: 336 mm x 100 mm x 227 mm (27.36" x 10.23" x 20.86")
- Outer carton size: 523(W)x356(D)x259(H)mm
- Units per outer carton: 5

Content Management

- SignApps Express Utility
- 3rd party solution (optional license)

Open Standards Supported

- HTML5, Javascript and CSS
- Android 9.0 API
- W3C SMIL for cross-platform management
- W3C HTML5 widgets
- Support multimedia content playback such as video and image

Mounting Options

- Built-in VESA compatible 75 mm x 75 mm posts
- Flush mount back cover

Supplied Accessories

- Zero-gap flush VESA mount
- DC in & micro SD stopper
- HW & SW QSG

Certifications

- CE / FCC / RoHS

Warranty

- 1-year limited parts & labor* (varies based on region, contact sales for more details)

XDS-1078 Comparison Table

	Android version	Touch	Light	RAM	Storage	PoE
XDS-1078-A9	Android 9	●	●	2 GB	16 GB	● (PoE+)
XDS-1078-A7	Android 7	●	●	1 GB	8 GB	●



America

20 Fairbanks,
Ste, 170 Irvine, CA 92618
California, U.S.A
Tel: +1-949-305-6489
Email: US-Sales@IAdea.com

Taiwan

114, 3F, No. 21
Ln. 168, Xingshan Rd.
Neihu Dist., Taipei, Taiwan
Tel: +886-2-2791-1110
Fax: +886-2-2791-1170
Email: Sales@IAdea.com

