Key **Features**

Large Images in Small Spaces | All-in-One Interactive Solution | vBoard interactive software | Optional Qwizdom Oktopus Software | SuperColor: **Amazing Color Accuracy**



Product **Description**

With out-of-the-box interactivity and an ultra-short throw lens, the ViewSonic® PS750W WXGA projector delivers a complete interactive solution perfect for any classroom. Featuring an embedded camera, along with an included laser curtain module and wall mount kit, the PS750W offers a low-cost, big picture alternative to interactive whiteboards and displays. An ultra-short throw lens enables the projector to be placed just inches away from a wall or screen, making it flexible enough to be ceiling-mounted or simply placed on the tabletop. ViewSonic's easy-to-use vBoard software lets users write, highlight, edit, and transform documents and images on-screen in real-time. PortAll™, a neatly designed and enclosed HDMI/MHL dongle compartment, features an integrated micro USB cable for easy charging – allowing teachers to present interesting lesson content via wireless dongles and PC sticks. For a complete, all-in-one interactive projection solution, the PS750W delivers everything you need for immersive and engaged learning in the classroom.



RESOLUTION



LUMENS



0.233 **THROW RATIO**

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:		Controls:	
Type: Resolution Type:	Ultra Short Throw DLP WXGA	Physical Controls:	Power, My Button, COMP1., COMP2., HDMI, Auto Sync, Source, 4 direction buttons, Enter, Menu, Laser, Exit, Mouse Left, Mouse Right, Pg Up, Pg Dn, Mouse, Pattern, Blank, Keypad Lock, Volume Mute, HELP, Presentation Timer, Volume, Magnify, Eco Mode, Audio Mode, Color Mode
Resolution:	1280 x 800		
Brightness (ANSI Lumens):	3,300		
Throw Distance:	1.43 – 1.97 ft. / 0.436 – 0.601 m		
Throw Ratio:	0.233		Display, Image, Power
Display Size (in.):	87 – 120 in.	On Screen Display:	Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
Keystone:	Vertical (± 30°) / Horizontal (± 30°)		
Lens:	Manual optical focus	Operating Conditions:	
Light Source (watt):	240	Temperature:	32-104° F (0-40° C)
Light Source Life, Normal (hours):	3000	Humidity (non-condensing):	0-90%
Light Source Life, Dynamic Eco-	6000	Weight (imperial):	
Mode (hours):	0000	Net (lbs):	13.38
Color Depth:	30 bits, 1.07B Color (10+10+10)	Gross (lbs):	18.71
Dynamic Contrast Ratio:	10,000:1	Weight (metric):	
Aspect Ratio:	16:10	Net (kg):	6.075
Video Signal:		Gross (kg):	8.5
Frequency Horizontal:	15-100kHz	Dimensions (metric) (WxHxD):	
Frequency Vertical:	24-120Hz	Packaging (mm):	590 x 500 x 275
Compatibility:		Physical (mm):	434 x 388 x 153
PC Resolution (max):	1920x1080	Dimensions (imperial) (WxHxD):	
Mac® Resolution (max):	1920x1080 (may require MAC adapter)	Packaging (in.):	23.23 x 19.69 x 10.83
Connector:	adaptery	Physical (in.):	17.09 x 15.28 x 6.02
USB 2.0 Type A(1), USB Type A (5V 2A) (1), Mini USB Type B(2), Audio Ouput (Mini Jack)(1), Ethernet LAN (RJ45)(1), 3.5mm Audio In(1), Control (RS232)(1), HDMI 1.4(1), HDMI 1.4/MHL 2.0(1), VGA Out(1), Composite RCA Video In(1), S-Video In(1), RCA Audio In (L/R)(1), RGB Input(2)		General:	
		Regulations: FCC (including ICES003), cTUVus, NOM, TUV-Rheinland S Mark	
Audio:		PACKAGE CONTENTS: PS750W Projector, PJ-WMK-303, Laser Curtain Module, 2 IR Pens, Power Cable, VGA Cable, Remote Control with AAA	
Internal Speakers:	10W (x2)	Batteries, Quick Start Guide, ViewSonic Wizard CD (with User Guide)	
Power:		Warranty: Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service**	
Voltage:	AC 100-240V (universal), 50-60Hz	Recycle/Disposal: Please dispose of in accordance with local, state or	
Consumption (max):	410W	federal laws.	
Stand-by:	<0.5W	UPC: 766907889413	
		Accessories:	