4XEM

Problem solved.

4XEM's Dual HDMI USB-C Dock

4XEM Part- 4XUSBCHUB07

4XEM's Dual HDMI USB-C Dock is a premier device if you need to upgrade the video output and resolution of your display set-ups. Fitted with two HDMI ports expand the range of your display monitor or laptop. Not only does this device add displays to your network it also is capable of improve the quality of your video through enabling 4K video resolution. Additionally, this dock comes with an USB-A and USB-C port, which enables charging and data transferring to enabled devices. Perform multiple functions with one plug and play device at the centre of your personal or workplace network.

Problem it solves: Spread your single monitor laptop or display to two HDMI enabled devices while simultaneously charging and transferring data with two different USB ports.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104   tschaus@4xem.com

Features

- USB-C connector and port
- 2x HDMI ports
- USB-A (USB 3.0) port
- Supports resolution up to 4K with USB-C and HDMI
- Transfers data at 5Gbps
- Supports Mac OS, Windows, and Linux
- Compatible with a variety of HDMI enabled products

Application

- Home
- Office
- Networks
- Charging
- Transferring

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104   tschaus@4xem.com

Warranty Information	Warranty	3 Years
Hardware	4K Support	Yes
	Fast-Charge Port(s)	No
	Displays Supported	2
	Interface	USB 3.0
	Bus Type	USB-C
	Industry Standards	HDMI 1.4
		Power Delivery - PD 2.0
	Chipset ID	Lontium Semiconductor - LT8712
Connector(s)	Host Connector	USB Type-C
	Host Connector Type	Fixed Attached Cable
	Connector Type(s)/Rate(s)	2x HDMI 1.4 (10.2 Gbps)
		1x USB 3.0 Type-A (5 Gbps)
		1x USB Type-C (used for PD only)
Performance	Maximum Digital Resolutions	Single Monitor: 3840 x 2160 @ 30Hz
		Dual Monitors: 1920 x 1080 @ 60Hz each
Software	OS Compatibility	Windows® 10
		Mac OS® 11
Power	Power Source	Bus Powered
	Power Delivery	PD Pass-Through - Max 100W
Physical Characteristics	Weight of Product	2.26 oz [64 g]
	Color	Grey, Black
	Material	Aluminum
	Cable Length	5.27 in [133.9 mm]
	Product Height	0.61 in [15.4 mm]
	Product Width	2.46 in [62.4 mm]
	Product Length	2.50 in [63.4 mm] (incl cable 9.45 in [240 mm])
Environmental	Operating Temperature	0ºC to 55ºC (32°F to 131°F)
	Storage Temperature	-10°C to 70°C (14°F to 158°F)
	Humidity	40~50% RH
Packaging Information	Shipping (Package) Weight	2.68 oz [76 g]
	Package Height	6.78 in [172.3 mm]
	Package Width	3.00 in [76.2 mm]
	Package Length	0.70 in [17.8 mm]
What's in the Box	Included in Package	1x USB-C Hub
Notes		A host laptop with an available USB-C port (to ensure full adapter functionality, the host USB-C port must support DP alt mode and Power Delivery 2.0)
		A 4K-capable display is required to achieve 3840 x 2160p resolution (4K is also known as 4K x 2K)
		Uses 2 data lanes for DP alt mode @ HBR2 for video output and 2 data lanes for other functions

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104   tschaus@4xem.com