

		IXUS 175
<b>IMAGE SENSOR</b>		
Type		1/2.3 type CCD
Effective Pixels		Approx. 20.0M [14]
Effective / Total Pixels		Approx. 20.5M
Colour Filter Type		Primary Colour
<b>IMAGE PROCESSOR</b>		
Type		DIGIC 4+ with iSAPS technology
<b>LENS</b>		
Focal Length		5.0 – 40.0 mm (35 mm equivalent: 28 – 224 mm)
Zoom		Optical 8x ZoomPlus 1.6x Digital approx. 4x Combined approx. 32x [1]
Maximum f/number		f/3.2 – f/6.9
Construction		8 elements in 7 groups (1 double-sided aspherical lens)
Image Stabilisation		Digital (Digital IS Mode)
<b>FOCUSING</b>		
Type		TTL
AF System/ Points		AiAF (Face Detection / 9-point), 1-point AF (fixed to centre)
AF Modes		Single, Continuous (Auto mode only), Servo AF/AE, Tracking AF [6]
AF Assist Beam		Yes
Closest Focusing Distance		1 cm (W) from front of lens in Macro
<b>EXPOSURE CONTROL</b>		
Metering modes		Evaluative (linked to Face Detection AF frame), Centre-weighted average, Spot (centre)
AE Lock		Yes
Exposure Compensation		+/- 2 EV in 1/3 stop increments. Enhanced i-Contrast for automatic dynamic range correction
ISO sensitivity		AUTO, 100, 200, 400, 800, 1600
<b>SHUTTER</b>		
Speed		1 – 1/2000 s (factory default) 15 – 1/2000 s (total range – varies by shooting mode)
<b>WHITE BALANCE</b>		
Type		TTL
Settings		Auto (including Face Detection WB), Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom
<b>COLOUR MATRIX</b>		
Type		sRGB
<b>LCD MONITOR</b>		
Monitor		6.8 cm (2.7") LCD (TFT), approx. 230,000 dots
Coverage		Approx. 100%
Brightness		Adjustable to one of five levels. Quick-bright LCD
<b>FLASH</b>		
Modes		Auto, Manual Flash On / Off, Slow Synchro
Slow Sync Speed		Yes. Fastest speed 1/2000 s
Red-Eye Reduction		Yes
Flash Exposure Compensation		Face Detection FE, Smart Flash Exposure
Built-in Flash Range		50 cm – 3.0 m (W) / 1.3 – 1.5 m (T)
External Flash		Canon High Power Flash HF-DC2
<b>SHOOTING</b>		
Modes		Smart Auto (32 scenes detected), P, Portrait, FaceSelf-Timer, Low Light (5.0 MP), Digital IS, Fish-eye Effect, Miniature Effect, Toy Camera Effect, Monochrome, Super Vivid, Poster Effect, Fireworks, Long Shutter
Modes in Movie		Smart Auto (21 scenes detected), P, Portrait, Miniature Effect, Monochrome, Super Vivid, Poster Effect, Fireworks
Drive modes		Single, Continuous, Self-Timer
Continuous Shooting		Approx. 0.8 shots/s Low Light Mode (5.0 MP): Approx. 2.2 shots/s (all speeds are until memory card becomes full) [3] [4]
<b>RECORDING PIXELS / COMPRESSION</b>		
Image Size		4:3 - (L) 5152 x 3864, (M1) 3648 x 2736, (M2) 2048 x 1536, (S) 640 x 480, (W) 5152 x 2896
Compression		Resize option available in playback
Movies		Fine (HD) 1280 x 720, 25 fps, (L) 640 x 480, 29.97 fps Miniature Effect (HD) 5 fps, 2.5 fps, 1.25 fps Miniature Effect (L) 6 fps, 3 fps, 1.5 fps
Movie Length		(HD) Up to 4 GB or 29 min 59 s [7] (L) up to 4 GB or 1 hour [4]
<b>FILE TYPES</b>		
Still Image Type		JPEG compression, (Exif 2.3 [Exif Print] compliant) / Design rule for Camera File system, Digital Print Order Format [DPOF] Version 1.1 compliant
Movies		MOV [Video: H.264, Audio: Linear PCM (monaural)]
<b>DIRECT PRINT</b>		
Canon Printers		Canon SELPHY Compact Photo Printers and Canon Inkjet Printers supporting PictBridge
PictBridge		Yes
<b>OTHER FEATURES</b>		
Red-Eye Correction		Yes
Intelligent Orientation Sensor		Yes, with Auto Rotate
Histogram		Yes, during playback
Playback zoom		Approx. 2x – 10x
Self Timer		Approx. 2, 10 s or Custom
Menu Languages		English, German, French, Dutch, Danish, Finnish, Italian, Greek, Norwegian, Portuguese, Russian, Swedish, Spanish, Ukrainian, Polish, Czech, Hungarian, Turkish, Simplified Chinese, Chinese (traditional), Japanese, Korean, Thai, Arabic, Romanian, Farsi, Hindi, Malay, Indonesian, Vietnamese, Hebrew
<b>INTERFACE</b>		
Computer		Hi-Speed USB composite connector (Mini-B compatible)
Other		A/V output, composite connector (PAL/NTSC)
<b>MEMORY CARD</b>		

Type	SD, SDHC, SDXC
<b>SUPPORTED OPERATING SYSTEM</b>	
PC & Macintosh	Windows 10 / 8.1 / 8 / 7 SP1 [18] Mac OS X 10.9 / 10.10 / 10.11
<b>SOFTWARE</b>	
Other	CameraWindow DC
<b>POWER SOURCE</b>	
Batteries	Rechargeable Li-ion Battery NB-11L / NB-11LH (NB-11L battery and charger supplied)
Battery life	Approx. 220 shots  Eco Mode: Approx. 300 shots Playback Mode: Approx. 240 min
<b>ACCESSORIES</b>	
Cases / Straps	Soft Case DCC-1320 Soft Case DCC-1350 Soft Case DCC-1370
Flash	Canon High Power Flash HF-DC2
Power Supply & Battery Chargers	Battery Charger CB-2LFE / CB-2LDE Rechargeable Li-ion Battery NB-11L / NB-11LH
Other	Canon AV Cable AVC-DC400 Interface cable IFC-400PCU
<b>PHYSICAL SPECIFICATIONS</b>	
Operating Environment	0 – 40 °C, 10 – 90% humidity
Dimensions (WxHxD)	95.2 x 54.3 x 22.1 mm
Weight	Approx. 126 g (including battery and memory card)
<p><b>All data is based on Canon standard testing methods (according to CIPA Standards) except where indicated. Subject to change without notice.</b></p> <p>[1] Depending on the image size selected. [3] Under conditions where the flash does not fire. [4] Depending on memory card speed / capacity / compression setting. [6] Some settings limit availability. [7] The following Speed Class memory cards are required for maximum record time: (HD) 1280 x 720 Speed Class 4 or above. (Full HD) 1920 x 1080 Speed Class 6 or above. (iFrame) 1280 x 720 Speed Class 6 or above. [14] Image processing may cause a decrease in the number of pixels.</p>	