


## Key Features

Ultra HD Resolution | Built-in Multi-Core Media Player with 8GB Storage | Embedded LAN, Optional Wi-Fi, Internet Browser | ViewBoard® Cast Content Sharing Software | Free Bundled vController™ Software




## Product Description

The ViewSonic® CDE5010 is a 50" (50" viewable) 4K Ultra HD commercial display purpose-built to deliver eye-catching imagery for hotels, restaurants, retail, business, and more. With stunning 3840x2160 resolution, 350-nit high brightness, wide viewing angles, and dual 10W speakers, this display provides immersive, high-impact messaging wherever needed. In addition to HDMI, DVI, and VGA inputs to connect with various high definition devices, this display utilizes an integrated multi-core processor and 8GB of internal memory, allowing customers to playback multimedia content via USB without the need for a PC. To make life even easier, the bundled vController software offers easy maintenance and intuitive interfaces for remote management via a PC server or laptop, and flicker-free and blue light filter technologies help provide a comfortable viewing environment.



50"  
**DISPLAY**



3840 x 2160  
**RESOLUTION**



350 cd/m2  
**BRIGHTNESS**

### Contact Sales

- call: 888.881.8781
- email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)
- visit: [viewsonic.com](http://viewsonic.com)

**Display:**

Display Size (in.):	50
Viewable Area (in.):	50
Light Source:	DLED
Resolution:	3840 x 2160
Aspect Ratio:	16:9
Static Contrast Ratio:	4,000:1
Backlight Life (Hours):	30,000
Brightness:	350 cd/m2
Response Time (Typical GTG):	8ms
Viewing Angles:	178° horizontal, 178° vertical
Panel Surface:	Anti-glare, Hard coating (3H)

**Embedded Player:**

CPU:	Quad Core - Cortex A53
Memory:	2GB
Storage:	8GB eMMC
Interface:	OSD / Remote Control

**Audio:**

Internal Speakers:	10W (x2)
--------------------	----------

**Connector:**

HDMI 2.0(2), DVI-D(1), VGA(1), RCA Audio Out(1), 3.5mm Audio In(1), USB 3.0(1), USB 2.0(1), Micro USB(1), RS232(1), RS232 Out(1), Ethernet LAN (RJ45)(1), IR in(1), IR out(1)
---

**Power:**

Voltage:	100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz
Consumption (max):	175W
Consumption (typical):	140W
Stand-by:	<0.5W

**Operating Conditions:**

Temperature:	41-104° F (5 - 40° C)
Humidity (non-condensing):	20-80%

**Weight (metric):**

Net (kg):	14.9
Net Without Stand (kg):	13.0
Gross (kg):	16.5

**Weight (imperial):**

Net (lbs):	32.9
Net Without Stand (lbs):	28.7
Gross (lbs):	36.4

**Dimensions (metric) (WxHxD):**

Packaging (mm):	1282.0 x 845.0 x 203.0
Physical (mm):	1123.6 x 685.9 x 329.6
Physical Without Stand (mm):	1123.6 x 646.7 x 67.8

**Dimensions (imperial) (WxHxD):**

Packaging (in.):	50.5 x 33.3 x 8.0
Physical (in.):	44.2 x 27.0 x 13.0
Physical Without Stand (in.):	44.2 x 25.5 x 2.7

**Mount:**

VESA Compatible:	400 x 400 mm
------------------	--------------

**General:**

Warranty: Three-year limited warranty on parts, labor and backlight
---

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

PACKAGE CONTENTS: CDE5010, Remote control, CD User Manual, Quick Start Guide, Power cables, VGA cable, RS232 cable, IR sensor cable, RS232 daisy chain cable

Regulations: cULus, FCC, Energy Star 7.0, UL-MX-CoC, Mexico Energy

UPC: 766907990416

**Accessories:**

NMP-302WX, NMP-302w, NMP580-W, NMP620-P10, NMP620-P10X, NMP660, SC-A25R, VC10, VCB10, WMK-014, WMK-047-2, WMK-051, sc-a25x