# JTouch Interactive Display



with Capacitive Touch Technology

The new 65-inch JTouch engages audiences with a design that fits your budget and your workspace. Foster collaboration and creativity and bring presentations to life with accurate and responsive edge-to-edge capacitive touch, a slim and bezel-less design, and a bright, vivid 1080p HD display.

#### **Key Features**

- Big, bright display at an affordable price that's right for your budget
- 1080p resolution for crisp, vivid images that can be seen from from the back of a conference room
- Display your notebook via HDMI or VGA & control it from the display via touch using a USB cable
- Run all your Windows, Mac or Chromebook apps, even older ones, with touch
- 10 point touchscreen for more real-time editing
- Sleek, bezel-less design
- No calibration or special stylus needed means it's quick and easy to use with just your fingertips
- Front-facing, 20-watt speakers for robust sound





- HDMI to quickly connect your notebook
- USB port for optional on-board PC
- Two-port USB hub syncs with your connected notebook
- USB to enable notebook touch control

### **Projected Capacitive Touch**

The ultra-responsive and sleek bezel-less technology found in tablets and smart phones is now in the JTouch Display model INF6500eAG. Get more touch points for fingers, styluses and even medical-grade gloves.



## Specifications\*

Resolution	DISPLAY	INF6500eAG
Mounting Orientation  Antiglare Refresh Rate Viewing Angle Technology Direct LED backlight Pixel Pitch Response Time Response Time Response Time Rountation Antiglare ROUNT STAN STAN STAN STAN STAN STAN STAN ST	Size	65" Diagonal
Antiglare         Yes           Refresh Rate         120 Hz           Viewing Angle         178"           Technology         Direct LED backlight           Pixel Pitch         0.40mm x 0.40mm           Response Time         8 ms           Contrast Ratio         4,000:1           Brightness         300 cd/m²           Imput Connections         HDMI x 5, VGA, USB x 4 (2 for hub, 1 for optional on-board PC, 1 for touch), 3.5mm line-in audio (mono), component, composite, RS232           Output Connections         RCA stereo audio out, 3.5mm stereo out           Touch Screen         10-point, projected capacitive           Speakers (Integrated)         2x10W (front facing)           Power         AC 100 to 240V, 50/60Hz           Mount         VESA standard 400 x 400mm, M6 screws           Product Dimensions (H x W x D)         972mm x 1521mm x 83mm           Product Weight         50 kg           Shipping Dimensions (H x W x D)         1141mm x 1687mm x 213mm           Shipping Weight         62 kg           Accessories Included***         VGA cable, USB cable, power cord, remote, quick setup guide           Warranty         2 year limited, extended warranties available           Operating Temperature         41 to 95"F at 0 to 10K ft / 5 to 35"C at 0 to 3,048 m	Resolution	1080p HD (1920x1080)
Refresh Rate    120 Hz	Mounting Orientation	Landscape
Viewing Angle Technology Direct LED backlight  Pixel Pitch 0.40mm x 0.40mm Response Time 8 ms Contrast Ratio 4,000:1  Brightness 300 cd/m² Input Connections HDMI x 5, VGA, USB x 4 (2 for hub, 1 for optional on-board PC, 1 for touch), 3.5mm line-in audio (mono), component, composite, RS232 Output Connections RCA stereo audio out, 3.5mm stereo out Touch Screen 10-point, projected capacitive Speakers (Integrated) Power AC 100 to 240V, 50/60Hz Mount VESA standard 400 x 400mm, M6 screws Product Dimensions (H x W x D) 972mm x 1521mm x 83mm Product Weight Shipping Dimensions (H x W x D) Shipping Dimensions (H x W x D) Shipping Weight Accessories Included*** VGA cable, USB cable, power cord, remote, quick setup guide Warranty 2 year limited, extended warranties available Operating Temperature 41 to 95°F at 0 to 10K ft / 5 to 35°C at 0 to 3,048 m Noise  *40dBA @ 77°F / 25°C	Antiglare	Yes
Technology Direct LED backlight  0.40mm x 0.40mm  Response Time 8 ms  Contrast Ratio 4,000:1  Brightness 10put Connections HDMI x 5, VGA, USB x 4 (2 for hub, 1 for optional on-board PC, 1 for touch), 3.5mm line-in audio (mono), component, composite, RS232  Output Connections RCA stereo audio out, 3.5mm stereo out  Touch Screen 10-point, projected capacitive  Speakers (Integrated) 2x10W (front facing)  Power AC 100 to 240V, 50/60Hz  Mount VESA standard 400 x 400mm, M6 screws  Product Dimensions (H x W x D) 972mm x 1521mm x 83mm  Product Weight 50 kg  Shipping Dimensions (H x W x D) 1141mm x 1687mm x 213mm  Shipping Weight 62 kg  Accessories Included*** VGA cable, USB cable, power cord, remote, quick setup guide  Warranty 2 year limited, extended warranties available  Operating Temperature 41 to 95°F at 0 to 10K ft / 5 to 35°C at 0 to 3,048 m  Noise <a href="https://doi.org/10.10mm/4.15">Noise</a>	Refresh Rate	120 Hz
Pixel Pitch  Response Time  8 ms  Contrast Ratio  4,000:1  Brightness  300 cd/m²  Input Connections  HDMI x 5, VGA, USB x 4 (2 for hub, 1 for optional on-board PC, 1 for touch), 3.5mm line-in audio (mono), component, composite, RS232  Output Connections  RCA stereo audio out, 3.5mm stereo out  Touch Screen  10-point, projected capacitive  Speakers (Integrated)  Power  AC 100 to 240V, 50/60Hz  Mount  VESA standard 400 x 400mm, M6 screws  Product Dimensions (H x W x D)  972mm x 1521mm x 83mm  Product Weight  50 kg  Shipping Dimensions (H x W x D)  1141mm x 1687mm x 213mm  Shipping Weight  62 kg  Accessories Included***  VGA cable, USB cable, power cord, remote, quick setup guide  Warranty  2 year limited, extended warranties available  Operating Temperature  41 to 95°F at 0 to 10K ft / 5 to 35°C at 0 to 3,048 m  Noise	Viewing Angle	178°
Response Time  Contrast Ratio  HDMI x 5, VGA, USB x 4 (2 for hub, 1 for optional on-board PC, 1 for touch), 3.5mm line-in audio (mono), component, composite, RS232  Output Connections  RCA stereo audio out, 3.5mm stereo out  Touch Screen  10-point, projected capacitive  Speakers (Integrated)  Power  AC 100 to 240V, 50/60Hz  Mount  VESA standard 400 x 400mm, M6 screws  Product Dimensions (H x W x D)  972mm x 1521mm x 83mm  Product Weight  Shipping Dimensions (H x W x D)  1141mm x 1687mm x 213mm  Shipping Weight  62 kg  Accessories Included***  VGA cable, USB cable, power cord, remote, quick setup guide  Warranty  2 year limited, extended warranties available  Operating Temperature  41 to 95°F at 0 to 10K ft / 5 to 35°C at 0 to 3,048 m  Noise	Technology	Direct LED backlight
Contrast Ratio Brightness Input Connections HDMI x 5, VGA, USB x 4 (2 for hub, 1 for optional on-board PC, 1 for touch), 3.5mm line-in audio (mono), component, composite, RS232 Output Connections RCA stereo audio out, 3.5mm stereo out Touch Screen 10-point, projected capacitive Speakers (Integrated) Power AC 100 to 240V, 50/60Hz Mount VESA standard 400 x 400mm, M6 screws Product Dimensions (H x W x D) 972mm x 1521mm x 83mm Product Weight 50 kg Shipping Dimensions (H x W x D) 1141mm x 1687mm x 213mm Shipping Weight 62 kg Accessories Included*** VGA cable, USB cable, power cord, remote, quick setup guide Warranty 2 year limited, extended warranties available Operating Temperature 41 to 95°F at 0 to 10K ft / 5 to 35°C at 0 to 3,048 m Noise	Pixel Pitch	0.40mm x 0.40mm
Brightness 300 cd/m²  Input Connections HDMI x 5, VGA, USB x 4 (2 for hub, 1 for optional on-board PC, 1 for touch), 3.5mm line-in audio (mono), component, composite, RS232  Output Connections RCA stereo audio out, 3.5mm stereo out  Touch Screen 10-point, projected capacitive  Speakers (Integrated) 2x10W (front facing)  Power AC 100 to 240V, 50/60Hz  Mount VESA standard 400 x 400mm, M6 screws  Product Dimensions (H x W x D) 972mm x 1521mm x 83mm  Product Weight 50 kg  Shipping Dimensions (H x W x D) 1141mm x 1687mm x 213mm  Shipping Weight 62 kg  Accessories Included*** VGA cable, USB cable, power cord, remote, quick setup guide  Warranty 2 year limited, extended warranties available  Operating Temperature 41 to 95°F at 0 to 10K ft / 5 to 35°C at 0 to 3,048 m  Noise	Response Time	8 ms
HDMI x 5, VGA, USB x 4 (2 for hub, 1 for optional on-board PC, 1 for touch), 3.5mm line-in audio (mono), component, composite, RS232  Dutput Connections  RCA stereo audio out, 3.5mm stereo out  Touch Screen  10-point, projected capacitive  Speakers (Integrated)  2x10W (front facing)  Power  AC 100 to 240V, 50/60Hz  Mount  VESA standard 400 x 400mm, M6 screws  Product Dimensions (H x W x D)  972mm x 1521mm x 83mm  Product Weight  50 kg  Shipping Dimensions (H x W x D)  1141mm x 1687mm x 213mm  Shipping Weight  Accessories Included***  VGA cable, USB cable, power cord, remote, quick setup guide  Warranty  2 year limited, extended warranties available  Operating Temperature  41 to 95°F at 0 to 10K ft / 5 to 35°C at 0 to 3,048 m  Noise	Contrast Ratio	4,000:1
Component, composite, RS232  RCA stereo audio out, 3.5mm stereo out  Touch Screen  10-point, projected capacitive  Speakers (Integrated)  Power  AC 100 to 240V, 50/60Hz  Mount  VESA standard 400 x 400mm, M6 screws  Product Dimensions (H x W x D)  972mm x 1521mm x 83mm  Product Weight  50 kg  Shipping Dimensions (H x W x D)  1141mm x 1687mm x 213mm  Shipping Weight  62 kg  Accessories Included***  VGA cable, USB cable, power cord, remote, quick setup guide  Warranty  2 year limited, extended warranties available  Operating Temperature  41 to 95°F at 0 to 10K ft / 5 to 35°C at 0 to 3,048 m  Noise	Brightness	$300 \text{ cd/m}^2$
Touch Screen  10-point, projected capacitive  2x10W (front facing)  Power  AC 100 to 240V, 50/60Hz  Mount  VESA standard 400 x 400mm, M6 screws  Product Dimensions (H x W x D)  972mm x 1521mm x 83mm  Product Weight  50 kg  Shipping Dimensions (H x W x D)  1141mm x 1687mm x 213mm  Shipping Weight  62 kg  Accessories Included****  VGA cable, USB cable, power cord, remote, quick setup guide  Warranty  2 year limited, extended warranties available  Operating Temperature  41 to 95°F at 0 to 10K ft / 5 to 35°C at 0 to 3,048 m  Noise <a href="https://www.noise.noise.com/"></a>	Input Connections	
Speakers (Integrated)  Power  AC 100 to 240V, 50/60Hz  Mount  VESA standard 400 x 400mm, M6 screws  Product Dimensions (H x W x D)  972mm x 1521mm x 83mm  Product Weight  50 kg  Shipping Dimensions (H x W x D)  1141mm x 1687mm x 213mm  Shipping Weight  62 kg  Accessories Included****  VGA cable, USB cable, power cord, remote, quick setup guide  Warranty  2 year limited, extended warranties available  Operating Temperature  41 to 95°F at 0 to 10K ft / 5 to 35°C at 0 to 3,048 m  Noise <a #"="" href="https://www.noise.&lt;/th&gt;&lt;th&gt;Output Connections&lt;/th&gt;&lt;th&gt;RCA stereo audio out, 3.5mm stereo out&lt;/th&gt;&lt;/tr&gt;&lt;tr&gt;&lt;th&gt;Power  AC 100 to 240V, 50/60Hz  Mount  VESA standard 400 x 400mm, M6 screws  Product Dimensions (H x W x D)  972mm x 1521mm x 83mm  50 kg  Shipping Dimensions (H x W x D)  Shipping Weight  62 kg  Accessories Included***  VGA cable, USB cable, power cord, remote, quick setup guide  Warranty  2 year limited, extended warranties available  Operating Temperature  41 to 95°F at 0 to 10K ft / 5 to 35°C at 0 to 3,048 m  Noise  AC 100 to 240V, 50/60Hz  VESA standard 400 x 400mm, M6 screws  972mm x 1521mm x 83mm  50 kg  Shipping Weight  62 kg  VGA cable, USB cable, power cord, remote, quick setup guide  41 to 95°F at 0 to 10K ft / 5 to 35°C at 0 to 3,048 m  Accessories Accessorie&lt;/th&gt;&lt;th&gt;Touch Screen&lt;/th&gt;&lt;th&gt;10-point, projected capacitive&lt;/th&gt;&lt;/tr&gt;&lt;tr&gt;&lt;th&gt;Mount  VESA standard 400 x 400mm, M6 screws  Product Dimensions (H x W x D)  972mm x 1521mm x 83mm  50 kg  Shipping Dimensions (H x W x D)  Shipping Weight  62 kg  Accessories Included***  VGA cable, USB cable, power cord, remote, quick setup guide  Warranty  2 year limited, extended warranties available  Operating Temperature  41 to 95°F at 0 to 10K ft / 5 to 35°C at 0 to 3,048 m  Noise  VESA standard 400 x 400mm, M6 screws  972mm x 1521mm x 83mm  50 kg  1141mm x 1687mm x 213mm  62 kg  VGA cable, USB cable, power cord, remote, quick setup guide  41 to 95°F at 0 to 10K ft / 5 to 35°C at 0 to 3,048 m  440dBA @ 77°F / 25°C&lt;/th&gt;&lt;th&gt;Speakers (Integrated)&lt;/th&gt;&lt;th&gt;2x10W (front facing)&lt;/th&gt;&lt;/tr&gt;&lt;tr&gt;&lt;th&gt;Product Dimensions (H x W x D)  Product Weight  Shipping Dimensions (H x W x D)  Shipping Weight  Accessories Included***  VGA cable, USB cable, power cord, remote, quick setup guide  Warranty  2 year limited, extended warranties available  Operating Temperature  41 to 95°F at 0 to 10K ft / 5 to 35°C at 0 to 3,048 m  Noise&lt;/th&gt;&lt;th&gt;Power&lt;/th&gt;&lt;th&gt;AC 100 to 240V, 50/60Hz&lt;/th&gt;&lt;/tr&gt;&lt;tr&gt;&lt;th&gt;Product Weight  Shipping Dimensions (H x W x D)  Shipping Weight  Accessories Included***  VGA cable, USB cable, power cord, remote, quick setup guide  Warranty  2 year limited, extended warranties available  Operating Temperature  41 to 95°F at 0 to 10K ft / 5 to 35°C at 0 to 3,048 m  &lt;a href=">&lt;40dBA @ 77°F / 25°C</a>	Mount	VESA standard 400 x 400mm, M6 screws
Shipping Dimensions (H x W x D)  Shipping Weight  62 kg  Accessories Included****  VGA cable, USB cable, power cord, remote, quick setup guide  Warranty  2 year limited, extended warranties available  Operating Temperature  41 to 95°F at 0 to 10K ft / 5 to 35°C at 0 to 3,048 m  Noise  <40dBA @ 77°F / 25°C	Product Dimensions (H x W x D)	972mm x 1521mm x 83mm
Shipping Weight 62 kg  Accessories Included*** VGA cable, USB cable, power cord, remote, quick setup guide  Warranty 2 year limited, extended warranties available  Operating Temperature 41 to 95°F at 0 to 10K ft / 5 to 35°C at 0 to 3,048 m <a href="#">&lt;40dBA @ 77°F / 25°C</a>	Product Weight	50 kg
Accessories Included***  VGA cable, USB cable, power cord, remote, quick setup guide  Warranty  2 year limited, extended warranties available  Operating Temperature  41 to 95°F at 0 to 10K ft / 5 to 35°C at 0 to 3,048 m  Voise  40dBA @ 77°F / 25°C	Shipping Dimensions (H x W x D)	1141mm x 1687mm x 213mm
Warranty 2 year limited, extended warranties available  Operating Temperature 41 to 95°F at 0 to 10K ft / 5 to 35°C at 0 to 3,048 m		

<sup>\*</sup> Product specifications, terms, and offerings are subject to change at any time without notice.

#### **Accessories**

LiteShow 4 Wireless Display Adapter (INLITESHOW4)
Android Whiteboard Module (INA-AWB)
Wall Mount for 57-70 Inch Display (INF-WALLMNT2)
Mobile Carts for 57-70 Inch Display (INF-MOBCART,
INF-MOBCARTPRO-B, INF-MOBCARTPRO-S)
Lift Assist Mount for 57-70 Inch Display (INA-MNTBB70)
Floor Support for Lift Assist Wall Mount (INA-SUPPORTBB)
Mobile Cart for Lift Assist Mount (INA-CARTBB)
VESA Interface Bracket for Lift Assist Mount (INA-VESABB)
Touchscreen Stylus (INA-STYLUS)
Extended Warranties (EPWHW65JT1, EPWHW65JT2,
EPWHW65JT3)

# Easily Upgrade to Whiteboard Functionality with Android Whiteboard:

With the Android Whiteboard (INA-AWB), your JTouch becomes a digital whiteboard that you can tailor to your organization's business, education or entertainment needs — including access to nearly endless applications in the Google Play store.

- Save notes electronically
- Create a multi-screen canvas, with room for free-form drawings, diagrams, and notes
- y wears
- Use it with fingers or a stylus
- Write or draw with complete collection of digital pens, highlighters, shapes, lines and colors
- Paste images