



INTERCHANGEABLE LENS LCOS PROJECTORS WUX6500 / WUX6500 D

MARKETS/APPLICATIONS
RECOMMENDED FOR:

- Education
- Corporate
- Large Conference Rooms/Auditoriums
- Houses of Worship
- Museums and Galleries
- Command Control Centers
- Digital Signage
- Simulation and Immersive Training
- Entertainment



REALiS



PROJECTORS.USA.CANON.COM

CAPTIVATING WITH COLOR, DETAIL, AND BRIGHTNESS.

The REALiS WUX6500 Pro AV LCOS Projector delivers bright, 6500 lumen high-resolution WUXGA (1920 x 1200) widescreen video and still images in a variety of environments. Equipped with Canon's LCOS Technology with AISYS-enhancement, and an advanced image processing engine, this projector displays vivid, seamless images with intricate detail, accurate color, high contrast, and deep blacks. Connection options include industry standards such as HDBaseT™, HDMI and DVI.

DELIVERS BRIGHT STUNNING IMAGES



A high resolution of WUXGA (1920 X 1200) with a high brightness (6500 lumens) along HDBaseT™ connectivity simplifies installation, facilitates long cable runs and makes sure your content engages your audience even in larger venue settings.

INTERCHANGEABLE LENSES



Five optional interchangeable Genuine Canon lens options provide a variety to suit your needs. These lenses were developed to be similar in size so that they do not protrude significantly from the projector's form.



KEY FEATURES

- 6500 Lumens
- WUXGA Resolution (1920 x 1200)
- LCOS Technology with AISYS-enhancement
- Optional Interchangeable Genuine Canon Lens Options
- Up to 2000:1 Contrast Ratio^{*1, *3}
- HDBaseT™
- Versatile Connectivity (HDMI, DVI)
- Motorized Horizontal/Vertical Lens Shift, Zoom, and Focus
- Network Management including Creston Connectivity & AMX Device Discovery
- DICOM® Simulation Mode* (*WUX6500 D only)


SPECIFICATIONS

PROJECTION SYSTEM	
Imaging Device	0.71" LCOS Reflective Panels x3
Aspect Ratio	16:10
Native Resolution	1920 x 1200 (WUXGA)
Brightness	6500 Lumens (Normal) / 5270 Lumens (Power Saver) ^{*1,2}
Contrast	2000:1 ^{*1,3}
Digital Keystone	V±20°, H±20° ^{*1}
Uniformity	88% ^{*1}
IMAGE ADJUSTMENTS	
Image Mode	Standard / Presentation / Dynamic / Video / Cinema / Photo / sRGB / Vivid Photo / DICOM SIM ^{*5} / User 1 / User 2 / User 3 / User 4 / User 5
Color Adjustment	Color Level, Color Balance, Color Temperature, Gain (R,G,B), Offset (R,G,B)
Wall Color Correction	Normal / Greenboard / Adjust (Custom)
Mounting	360° Projection (Vertical)
Tilt Angle	Bottom Front: 2 Places (Max. Angles: 6° Elevation)
INPUT SIGNALS	
Scanning Frequency	H: 27kHz - 75kHz, V: 24Hz - 60Hz
Analog PC Input	WUXGA / UXGA / WSXGA+ / SXGA+ / WXGA+ / FWXGA / WXGA / SXGA / XGA / SVGA / VGA
Digital PC Input	WUXGA / UXGA / WSXGA+ / SXGA+ / WXGA+ / FWXGA / WXGA / SXGA / XGA / SVGA / VGA
Digital Video Input	1080p / 1080i / 720p / 576p / 480p
Component Video Input	1080p / 1080i / 720p / 576p / 576i / 480p / 480i
Dot Clock	162MHz
LAMP	
Type	370-NSHA
Life	3000 Hours (Full Power) / 4000 Hours (Power Saver) ^{*2,4}
Power	370 / 300 W ^{*2,3}

DIMENSIONS



CONNECTABILITY



WHAT'S IN THE BOX

- Projector
- Lens Cap
- Power Cord
- VGA to VGA Connection Cable (Mini Dsub15-Mini Dsub15)
- Remote Controller RS-RC04 (includes two AAA batteries)
- Quick Start Guide (Book)
- User's Manual (CD-ROM)
- Warranty Card

^{*1}: When using the optional projection lens RS-IL01ST (projection lens sold separately). ^{*2}: When the Lamp Mode is in Full Power Mode/Power Saver Mode; value for Power Saver Mode is a calculated value thus cannot be guaranteed as specifications. ^{*3}: When the Lamp Control function is ON. ^{*4}: This time guarantee a 50% survival rate and a 50% brightness-maintenance rate. This value does not guarantee the service life of the lamp. ^{*5}: Only available on WUX6500 D model. ^{*6}: Calculated on 100" screen.

© 2017 Canon U.S.A., Inc. All rights reserved. Not responsible for typographical errors. Specifications subject to change without notice. Products not shown to scale. Certain images and effects are simulated. Canon and REALiS are registered trademarks of Canon Inc. in the United States and may also be trademarks or registered trademarks in other countries. DICOM is the registered trademark of the National Electrical Manufacturers Association for its standards publications relating to digital communications of medical information. The REALiS WUX6500 D is not cleared or approved for medical diagnosis and should not be used for these purposes. HDBaseT(TM) and the HDBaseT Alliance logo are trademarks of the HDBaseT Alliance. All other products and brand names may be registered trademarks, trademarks or service marks of their respective owners in the United States and/or other countries.

REALiS WUX6500	ITEM CODE: 1876C002	UPC CODE: 13803286618
REALiS WUX6500 D	ITEM CODE: 1876C005	UPC CODE: 660685168640

TERMINALS	
DVI-I	Digital PC/Analog PC Input
HDMI	Digital PC/Digital Video Input
Mini Dsub15	Analog PC/Component Video Input
Mini jack x3	Audio Input x2, Audio Output x1
Mini Jack x1	Connecting Wired Remote Controller
Dsub9	RS-232C Connection
USB type A	USB Connection / JPEG Still Images
RJ-45 (HDBaseT™)	HDBaseT Connection (Image, Audio, Control and Network)
RJ-45	Network Connection (1000BASE-T / 100BASE-TX / 10BASE-T)
BUILT-IN SOUND	
Internal Speaker	5W, Mono
REMOTE CONTROL	
Wireless Remote	Infrared (Supplied) or Wired (Optional)
RATINGS	
Fan Noise	43dB (Full Power) / 39dB (Power Saver) ^{*2}
Power Consumption	500W (Full Power) / 410W (Power Saver) ^{*2}
Standby Power	2.0 ~ 0.3W ^{*4}
Heat Dissipation	Up to 1,706 BTU/h
Power Voltage	AC 100 - 240V, 50/60 Hz
Operating Temperature	32°F - 104°F (0°C - 40°C) (20% RH - 85%RH)
Storage Temperature	-22°F - 140°F (-30°C - 60°C)
Dimensions (W x H x D)	W: 14.96" (380mm), H: 6.69" (170mm), D: 16.92" (430mm) (Including Protrusion)
Weight	18.73 lbs.
Projector Warranty	3 Years Parts and Labor
Lamp Warranty	120 Days

OPTIONAL LENSES

	THROW RATIO ^{*6}	LENS SHIFT	ZOOM RATIO	SCREEN SIZE	FOCAL LENGTH	F-NUMBER
STANDARD ZOOM LENS RS-IL01ST ITEM CODE: 4966B001	1.49 - 2.24:1	V: 15% - 55% H: ± 10%	1.5x	40"-600"	23.0 - 34.5mm	1.89 - 2.65
LONG FOCUS ZOOM LENS RS-IL02LZ ITEM CODE: 4967B001	2.19 - 3.74:1	V: 15% - 55% H: ± 10%	1.7x	40"-600"	34.0 - 57.7mm	1.99 - 2.83
ULTRA WIDE ANGLE LENS RS-IL03WF ITEM CODE: 4968B001	0.80:1	V: 5% - 5% H: ± 2%	Fixed	40"-300"	12.8mm	2.0
ULTRA LONG FOCUS ZOOM LENS RS-IL04UL ITEM CODE: 6064B001	3.55 - 6.94:1	V: 15% - 55% H: ± 10%	1.95x	60"-600"	53.6 - 105.6mm	2.34 - 2.81
SHORT FOCUS ZOOM LENS RS-IL05WZ ITEM CODE: 8168B001	1.00 - 1.50:1	V: 15% - 55% H: ± 10%	1.5x	40"-600"	15.56 - 23.34mm	2.09 - 2.34

ACCESSORIES

ITEM	ITEM CODE
Replacement Lamp RS-LP11	2141C001
Replacement Air Filter RS-FL01	4971B001
Remote Controller RS-RC04	4970B001
Remote Controller RS-RC05 (With Wired Connection Option)	5750B001
Ceiling Mount RS-CL11	4969B001
Ceiling Extension RS-CL08 (16" - 24")	3096B001
Ceiling Extension RS-CL09 (24" - 39")	3097B001
Top Cover RS-TC01 (Dark Grey)	5471B001