

## Features

- True-flat, bezel-free design
- 15.6in widescreen LCD
- Durable and sturdy base
- Built-in universal power supply
- Built-in speakers
- USB touch interface
- Supports integrated MSR and customer displays



# LE1015W

## True-flat 15.6in Widescreen Touch Monitor

The Bematech LE1015W wide screen touch monitor is designed and manufactured to meet Point-of-Sale requirements of both retail and restaurant operations. The highly durable touch monitor includes a solid base with an extra wide hinge for maximum stability. The LE1015W also facilitates quick and professional mounting of integrated magnetic stripe reader and VFD/LCD customer display.

# LE1015W SPECIFICATIONS

## LCD TOUCH PANEL

LCD size	15.6in (39.6cm)
Display active area	13.5in x 7.6in (34.5cm x 19.5cm)
Brightness	200 cd/m <sup>2</sup> typical
Response time	12ms typical
Contrast ratio	600:1 typical
Resolution	WXGA 1366 x 768 @60Hz (non-interlaced)
Viewing angle (CR>10)	Horizontal: 90°, Vertical: 60°, typical
Touch screen	USB interface, 5-wire resistive touch panel (Optional projected capacitive touch panel)

## MECHANICAL

Net weight	10.3 lbs (4.7 Kg)
Dimensions (W x H x D)	15.9in x 12.2in x 9.06in (40.4cm x 31.0cm x 23.0cm)
Color	Black

## ELECTRICAL

Power supply	Built-in universal power Input 100~240VAC, 50/60Hz
Power consumption	30W max Power saving mode 1W max Power off mode 0.5W max

## ENVIRONMENTAL

Operating temperature	5°C to 40°C (41°F to 104°F)
Relative humidity	20% to 80%, non-condensing

## MISCELLANEOUS

Plug & Play	DDC2B
VESA wall mount compatible	100mm x 100mm
Power management	VESA DPMS
Magnetic stripe reader (optional)	Track 1/2/3 USB interface
Customer display (optional)	8in (20.3cm) LCD or 2 x 20 VFD, USB interface