

CyberPower

CSB606W ESSENTIAL SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The Essential Surge Protector CSB606W from CyberPower offers vital surge protection for common home and office devices such as computers and electronics. It prevents spikes in energy caused by storms and electrical power surges from reaching your electronic equipment. The CSB606W provides 900 joules of protection with 6 outlets and a power cord (6 ft.).

Features of the CSB606W include automatic shutdown, metal oxide varistor (MOV) technology, an EMI/RFI noise filter, keyhole mounting slots, and impact-resistant casing. This surge suppressor comes with a Limited Lifetime Warranty and a Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Personal Computers
- Chargers
- Personal Electronics

FEATURES

- Surge suppression: 900 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P
- Plug style: Straight
- Outlet type: 6 NEMA 5-15R (surge-protected)
- Power cord: 6 ft
- Model color: White
- EMI/RFI Filtration: Yes
- Warranty: Limited Lifetime
- Connected Equipment Guarantee: \$50,000



SPECIFICATIONS

INPUT

Circuit Breaker	15 A
Cord Length	6 ft (1.8 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	Straight

OUTPUT

Outlet Type	6 - NEMA 5-15R
Outlets - Total	6

SURGE PROTECTION & FILTERING

Attenuation	32 dB
Clamping Voltage	500V (H-N, H-G, N-G)
Coax Protection RG6	None
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	45,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	15,000 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	900 J

CSB606W

ESSENTIAL SURGE PROTECTOR

SPECIFICATIONS CONT.

PHYSICAL

Color	White
Form Factor	Strip
Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)
Keyhole Mounting Slots	Yes
Material of Construction	Plastic
Safety Covers	No

PHYSICAL DIMENSIONS

Physical Dimensions - WxHxD (cm)	4.45 x 3.81 x 24.77 cm
Physical Dimensions - WxHxD (mm)	44 x 38 x 248 mm
Physical Dimensions - WxHxD (in.)	1.75 x 1.5 x 9.75 in.
Weight (kg)	0.57 kg
Weight (lb)	1.25 lbs.

SHIPPING DIMENSIONS

Shipping Dimensions - WxHxD (cm)	32.39 x 3.18 x 13.34 cm
Shipping Dimensions - WxHxD (mm)	323.85 x 31.75 x 133.35 mm
Shipping Dimensions - WxHxD (in)	12.75 x 1.25 x 5.25 in.
Weight (kg)	0.62 kg
Weight (lb)	1.37 lbs.

CERTIFICATIONS

Environmental	RoHS Compliant
Safety	UL1449 3rd Edition

WARRANTY

CEG Amount	\$50,000
Connected Equipment Guarantee	Lifetime
Product Warranty	Limited Lifetime Warranty