

USB 3.0 Multiport Adapter + USB-C to USB-A Cable - HDMI & VGA - 1xA

Product ID: BNDDKT30CAHV



This USB 3.0 multiport adapter comes with a USB-C to A adapter cable, so you can use it with either a USB-A or USB-C laptop. Use it as a portable docking station to expand the connectivity of your laptop, adding HDMI and VGA ports, one USB-A port and a Gigabit Ethernet port.

Two Great Products in One Versatile Solution

This USB-A and USB-C multiport adapter combo provides a cost-effective solution for wide-scale use in organizations currently using a mix of USB-A and USB-C laptops through a combination of two products:

A USB 3.0 multiport adapter (USB3SMDOCKHV) with hideaway cable that connects to your laptop's USB-A port

A 6" (152 mm) USB-C to USB-A adapter cable (USB31CAADP) that connects to newer USB-C port equipped laptops





Connect an HDMI or VGA Monitor

Enjoy flexible video output with this USB multiport adapter. You can extend your laptop's display by connecting to an HDMI (2048x1152p) or VGA (2048x1152p) monitor or projector, to give presentations or set up a workstation.

Enhance Productivity

Transform your USB-A or USB-C laptop into a full-scale workstation. Connect a flash drive, mouse or other peripheral to your laptop. The multiport adapter also adds wired network connectivity with the GbE port, making it ideal in areas without Wi-Fi.

Each item in the BNDDKT30CAHV bundle is backed by its own StarTech.com warranty, ranging from 2 years to 3 years, with the added benefit of free lifetime technical support.





Certifications, Reports and Compatibility











Applications

- Transform your USB-A or USB-C laptop into a portable workstation
- Connect your laptop to an external HDMI or VGA monitor to give presentations
- Use an HDMI TV in a hotel room as a second display when traveling
- Add wired Gigabit network access to your laptop

Features

- Connect your USB-A or USB-C laptop to an HDMI or VGA monitor
- USB 3.0 multiport adapter includes a USB-C to A adapter cable
- Built-in hideaway cable for enhanced cable management and portability
- Connect a flash drive, mouse or other device with the USB 3.0 Type-A port
- Add wired network connectivity with the Gigabit Ethernet RJ45 port



Data Sheet

	Warranty	3 Years
Hardware	4K Support	No
	Bus Type	USB 3.0
	Chipset ID	DisplayLink - DL-3700
	Displays Supported	1
	Fast-Charge Port(s)	No
	Industry Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab USB 3.0 - Hub port supports USB 2.0/1.1 backward-compatibility
Performance	Auto MDIX	Yes
	Compatible Networks	10/100/1000 Mbps
	Full Duplex Support	Yes
	Maximum Analog Resolutions	2048×1152 (VGA)
	Maximum Data Transfer Rate	5 Gbps (USB 3.0) 2 Gbps (Ethernet; Full-Duplex)
	Maximum Digital Resolutions	2048x1152 (HDMI)
	Type and Rate	USB 3.0 - 5 Gbit/s
	UASP Support	Yes
Connector(s)	Connector Type(s)	1 - USB Type-A (9 pin) USB 3.0 Male
		1 - HDMI (19 pin) Female
		1 - VGA (15 pin, High Density D-Sub) Female
		1 - VGA (15 pin, High Density D-Sub) Female 1 - RJ-45 Female
Software	OS Compatibility	1 - RJ-45 Female
Software Special Notes / Requirements	OS Compatibility Note	1 - RJ-45 Female 1 - USB Type-A (9 pin) USB 3.0 Female Windows® 7, 8, 8.1, 10 macOS 10.11 - 10.12, 10.14
Special Notes /		1 - RJ-45 Female 1 - USB Type-A (9 pin) USB 3.0 Female Windows® 7, 8, 8.1, 10 macOS 10.11 - 10.12, 10.14 Chrome OS™ v55+ Only a single video output can be used at one time, HDMI® or VGA. If a display is connected to each video output port
Special Notes /	Note	1 - RJ-45 Female 1 - USB Type-A (9 pin) USB 3.0 Female Windows® 7, 8, 8.1, 10 macOS 10.11 - 10.12, 10.14 Chrome OS™ v55+ Only a single video output can be used at one time, HDMI® or VGA. If a display is connected to each video output port at the same time, then the HDMI® port will take priority USB enabled computer system with available USB 3.0 port
Special Notes / Requirements	Note System and Cable Requirements	1 - RJ-45 Female 1 - USB Type-A (9 pin) USB 3.0 Female Windows® 7, 8, 8.1, 10 macOS 10.11 - 10.12, 10.14 Chrome OS™ v55+ Only a single video output can be used at one time, HDMI® or VGA. If a display is connected to each video output port at the same time, then the HDMI® port will take priority USB enabled computer system with available USB 3.0 port or USB-C port (using adapter).
Special Notes / Requirements	Note System and Cable Requirements	1 - RJ-45 Female 1 - USB Type-A (9 pin) USB 3.0 Female Windows® 7, 8, 8.1, 10 macOS 10.11 - 10.12, 10.14 Chrome OS™ v55+ Only a single video output can be used at one time, HDMI® or VGA. If a display is connected to each video output port at the same time, then the HDMI® port will take priority USB enabled computer system with available USB 3.0 port or USB-C port (using adapter). 1 - Link (Green)
Special Notes / Requirements Indicators	Note System and Cable Requirements LED Indicators	1 - RJ-45 Female 1 - USB Type-A (9 pin) USB 3.0 Female Windows® 7, 8, 8.1, 10 macOS 10.11 - 10.12, 10.14 Chrome OS™ v55+ Only a single video output can be used at one time, HDMI® or VGA. If a display is connected to each video output port at the same time, then the HDMI® port will take priority USB enabled computer system with available USB 3.0 port or USB-C port (using adapter). 1 - Link (Green) 1 - Activity (Yellow)



Data Sheet

	Operating Temperature	0°C to 40°C (32°F to 104°F)
	Storage Temperature	-20°C to 70°C (-4°F to 158°F)
Physical Characteristics	Cable Length	3.7 in [93 mm]
	Color	Black
	Enclosure Type	Plastic
	Product Height	0.7 in [17 mm]
	Product Length	4.9 in [125 mm]
	Product Weight	3.4 oz [97 g]
	Product Width	2.2 in [55 mm]
Packaging Information	Shipping (Package) Weight	0.5 lb [0.2 kg]
What's in the Box	Included in Package	1 - USB 3.0 Multiport Adapter
		1 - USB 3.1 USB-C to USB-A Adapter [6 in. / 152.4 mm)
		1 - Driver CD
		1 - Instruction Manual

Product appearance and specifications are subject to change without notice.