

# Delock Professional Computer Podcasting Microphone with XLR connector and 3 pin stereo jack male + adapter cable for Smartphone and Tablet

## Description

This professional condenser microphone by Delock can be used for high-quality voice and vocal recordings.

### Optimal recordings

The microphone has a high-quality **16 mm condenser chip** and a **cardioid polar pattern (unidirectional)** and therefore ideally captures the sound. Due to high power, low self-noise and precise performance, even the finest sounds are recorded crystal clear.

### Good windscreen

Due to the included windscreen, the recording quality is further optimized. Disturbing wind noises are optimally filtered.

### Multifunctional application

It can be connected to any PC or laptop via the **detachable XLR to 3 pin stereo jack cable**. With the **included 4 pin Y-adapter cable**, it can also be connected to a tablet or smartphone.

### Stable & non-slip stand

The metal stand with rubber feet ensures that the microphone stands stable on the table. The microphone holder can be adjusted in a 180° angle as required. The table stand can be easily folded and transported when needed.



## Specification

- Connector: 1 x XLR plug
- Cable:
  - 1 x XLR jack >
  - 1 x 3.5 mm 3 pin stereo jack male
- Y-Adapter:
  - 1 x 3.5 mm 4 pin stereo jack male (CTIA standard) >
  - 1 x 3.5 mm 3 pin stereo jack female microphone
  - 1 x 3.5 mm 3 pin stereo jack female headset
- Directivity: unidirectional
- Sensitivity: -38 dB +/- 3 dB
- Frequency range: 30 Hz - 16 kHz
- Signal-to-noise ratio (SNR): ca. 70 dB
- Self-Noise: max. 16 dBA
- Sound pressure level (SPL): max. 120 dB
- Cable length: ca. 2.5 m
- Colour: black
- Voltage: 1.5 V

## System requirements

- A free stereo port 3.5 mm

## Package content

- XLR microphone
- XLR to stereo jack cable
- Y-adapter cable
- Windscreen

## Item no. 66640


EAN: 4043619666409

Country of origin: China

Package: Retail Box

- Microphone holder
- Table stand

Images



| Interface                 |                                   |
|---------------------------|-----------------------------------|
| connector:                | 1 x XLR Male                      |
| Connector 1:              | 1 x XLR female                    |
| Connector 2:              | 1 x 3.5 mm 3 pin stereo jack male |
| Technical characteristics |                                   |
| Frequency range:          | 30 Hz - 16 kHz                    |
| Voltage:                  | 1,5 V                             |
| Sensibility:              | -38 dB +/- 3 dB                   |
| Signal noise ratio (SNR): | ca. 70 dB                         |
| Directivity:              | uni-directional                   |
| Physical characteristics  |                                   |
| Housing material:         | metal                             |
| Cable length:             | 2.5 m                             |
| Colour:                   | black                             |