

i-SENSYS LBP7200Cdn Specifications Sheet	
Printer Engine	
Print speed	Up to 20 ppm colour and mono (A4)
Printing method	Colour laser beam printing
Print quality	Up to 9600 x 600 dpi with Automatic Image Refinement
Print resolution	Up to 600 x 600 dpi
Warm-up time	Approx. 19 seconds or less from power on
First Page Out Time	Approx. 15 seconds or less
Duty cycle	Max. 40,000 pages per month
Print margins	5 mm-top, bottom, left and right
Media handling	
Paper input (Standard)	250-sheet cassette 50-sheet multi-purpose tray
Paper input (Option)	250-sheet cassette
Paper output	125-sheet face down
Media types	Plain paper, Recycled paper, Heavy Paper, Transparency, Coated Paper, Label, Index card, Envelope
Media sizes	Cassette (Standard and optional): A4, B5, A5, Legal, Letter, Executive, Statement, Foolscap, 16K, Envelope DL, Envelope COM10, Envelope C5, Envelope B5, Custom sizes: Width 100 to 215.9 mm; Length 148 to 355.6 mm. Multi-purpose tray: A4, B5, A5, Legal, Letter, Executive, Statement, Foolscap, 16K, Envelope DL, Envelope COM10, Envelope C5, Envelope Monarch, Envelope B5, Index Card, Custom sizes: Width 76.2 to 215.9 mm; Length 127.0 to 355.6mm.
Media weights	Cassette (Standard and optional): 60 to 220 g/m ² Multi-purpose tray: 60 to 220 g/m ²
Double sided printing	Automatic
General features	
Power requirements	220-240V (±10%) 50/60Hz (±2Hz)
Power consumption	Maximum: 1,070 W or less Active: Average approx. 395 W Standby: Average approx 20.5 W Sleep: average approx 7.5 W Typical Electricity Consumption (TEC): 2.19 kWh/week
Noise level	Sound power ¹ : Active: 7 B or less Standby: Inaudible Sound pressure ¹ : Active: 56 dB(A) or less Standby: Inaudible
Dimensions (W x D x H)	409 mm x 490 mm x 331 mm
Weight	Approx 24.8 kg
Operating environment	Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation)
Control panel	9 LED indicators 1 operation key
Controller	
Memory	16 MB
Printer languages	CAPT (Canon Advanced Printing Technology)
Interface and connectivity	USB 2.0 High-Speed, 10BASE-T/100BASE-TX
Software and printer management	NetSpot Device Installer, Remote User Interface (RUI)

Operating systems compatibility	Windows 2000/Server 2003/XP/Vista/Server 2008 Mac OS X 10.4.1-10.6.x ^{2 3}
Consumables	
All-in-One cartridges	Cartridge 718 Black (3,400 pages ⁴) ⁵ Cartridge 718 Cyan (2,900 pages ⁴) ⁵ Cartridge 718 Magenta (2,900 pages ⁴) ⁵ Cartridge 718 Yellow (2,900 pages ⁴) ⁵
Accessories/ options	
Items	PF-522 (250-sheet cassette)

Standard disclaimer

[1]

[2]

[3]

[4]

[5]

All specifications subject to change without notice

Declared noise emission in accordance with ISO 9296

The Mac driver will be released in July/August 2009 for web distribution only

English driver only

Based on ISO/IEC 19798

Printer ships with 1,200 pages K (Black) and 1,400 pages CMY (Cyan, Magenta and Yellow) starter cartridges